GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI – 110 001

No. F.6/DFS/MS/School/2012/ 2678

Dated 24/07/12

FIRE SAFETY CERTIFICATE

Certified that the – Sarvodaya Kanya Vidyalaya, B-Block, Janak Puri, New Delhi-110058 Comprised of - ground floor plus two upper floors, owned/occupied by Director of Education, Govt. of N.C.T of Delhi has complied with the fire prevention and fire safety requirements in accordance with the National Building Code-IV-2005 and verified by the officer concerned of fire Service on 10.07.12 in the presence of Sh. Dinesh Kumar, and that the building/premises is fit for occupancy class – group-B (educational) with effect from the date of issue of this certificate for a period of - three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Chief Fire Officer Delhi Fire Service

Med Med

Copy to:

- The Principal, Sarvodaya Kanaya Vidyalaya, B-Block, Janak Puri, New Delhi-110058.
- 2. The Director of Education Govt. of NCT of Delhi Old Secretariat, Delhi.
- 3. Divisional Officer (South West) SRD.

Note * :- For general fire safety directives please see overleaf

Following fire safety directives must be adhered to –

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The staff should be trained available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provisions of the Building Bye Laws.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.

INSPECTION REPORT 1. Name & address of the building: Sarvodaya Canya Vidayalaya - B Block, 2. Type of Occupancy 3. Type of Case : New Case/ Renewal 4. Details of previous NOC : Letter No. HIL 5. Fire Safety directives letter No Dated: F6 OPS ms/2011 1411 6. Date of inspection 7. Name of the Inspecting Officers: HIL ANETA 8. Name and designation of officers from the building side 9. Year of Construction · 10. Applicant's letter No. M0259 dt S. Minimum Standards on fire NBC Provided at site No. prevention and fire safety U/R 33 Remarks Requirement MR/NMR 1 Access to building Road width 12 mm MR Gate width 370 Cms Width of internal road 10R Number, Width, Type & Arrangement of Exits a. Number of staircases 3 N60 mR Upper Floors - u -Basements Mu b. Width of staircases 142,126 L1260m MR Upper Floors -4u. Basements MIC c. Protection of exits Fire check door MR Pressurization

MR

R

R

R

2 Mos

2.55 mtn

100 × 210

MR

MR

MR

e. No. of continuous staircases to terrace

g. Width of Corridor

h. Door Size

3	Compartmentation.					
	Fire check door	MR				
e i i	Sealing of electrical shafts					
0 H	Fire Rating of shaft door					
	Water Curtain					
	Fire Dampers					
	Smoke Management System.					
	Basements	MR				
	• Upper floors	30 a/c per hour				
	PPC 10015	12 a/c per hour				
'. 	Fire Extinguishers					
	Total numbers	R	P	MR		
	Types		16400	-u-		
	1S marking	THE	ABE types	-u -		
	First-Aid Hose Reels,	ISI marked	Mes	~		
	Total numbers on each floor	R	P	MR		
	Length of hose reel hose	20	7 Noo-	-u -		
	Nozzle diameter	30 m 5 mm	~ · · · · · · ·	-4-		
5				-4-		
	Automatic fire detection and alarming system.					
	Location of Main Panel					
	Location of Repeater Panel					
. f.	Alternate source of power					
	Hooters' Location					
	MOEFA	MR				
	Public Address System.	Ne				
0	Automatic Sprinkler System.	MR				
N .	Basement	Mu				

The same

• Upper Floor	20		
Sprinkler above false ceiling	-		
Internal Hydrants	MR	0	MR
• Size of riser/down-comer	NR	P (100 mm)	MR
 Number of hydrants per floor 		2 Mo each A	
Hose Box			MR
2 Yard Hydrants.		2 Nos-4-	4-
my diants,	MR		
Total number of hydrantsHose Box			
- surping carrangements.	HR		
Ground Level			
Discharge of main Pump			
→ Head of Main pump			r Is
Number of main pumps			
> Jockey Pump out put			
> Jockey pump head			
Standby Pump out put			
Standby Pump Head			
> Auto Starting/ Manual			
stopping,			
> Pump House Access			
Terrace level			
Discharge of pump	R	4 SOLP M 2 Nos	MR
➤ Head of the pump	R	Somm each	mr
> Power Supply	R	ρ	MR
> Auto Starting of pump	P	40	MR
14 Captive Water Storage for fire fight	ing.		1
 Underground tank capacity 			
> Draw-off connection			

	> Fire service inlet			
	> Access to tank	+		
	Overhead Tank capacity			
		R	10000 Um	MR
15	Exit Signage.	R	0	MR
16	Provision of Lifts.	MR		
	Pressurization of Lift Shaft			
	• Pressurization of Lift lobby			
	• Communication In lift Car			
T.	• Fireman's Grounding Switch			
	• Lift Signage			
, , , , , , , , , , , , , , , , , , ,	Lift Diguage			
17	Standby power supply	NR		
18	Refuge Area.	MR		
1,	> Total Area			
	> Location			
19	Fire Control Room	110		
		MK		
ļ	Detector System Panel			
	• Flow Switch Panel			
	PAi System Panel			
	Batter backup			
	Building Floor Plans			
20	2 1.00 to 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.0			
	Protection of special Risks, if any:	NR		
	a line and the second s			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer

Name 41. L. ANESA

Designation Dir Hiecr.

Signature of the Inspecting Officer

Name

Designation