GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO.F6/DFS/MS/GH/2012/27 11

Dated: 24/07/12

FIRE SAFETY CERTIFICATE

Certified that M/s White Palace Guest House located at 3034, Turkman Gate, Delhi comprised of Basement floor(Commercial use), ground floor (Commercial use), first floor (Reception + 05 guest rooms), second floor (06 guest rooms), third floor (06 guest rooms) & fourth floor (02 rooms for staffs and store) was granted NOC by this department vide letter No. F.6/DFS/MS/GH/08/2937 dated 24-10-2008. The premises was re-inspected by the officer concerned of this department on 14-07-2012 in presence of Mehboob Ali, owner of the guest house and found that the party has converted 05 guest rooms into 04 guest rooms at first floor (04 guest rooms + reception), 06 guest rooms into 04 guest rooms at second floor (04 guest rooms), 06 guest rooms into 04 guest rooms & 01 staff room at third floor (04 guest rooms + 01 staff room) & 02 rooms for staff & store into owners residence at fourth floor (02 rooms for owners residence). The said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class residential (guest house) with effect from 14107 [12 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules, 2010.

Issued on 14/07/12 at New Delhi by.

Chief Fire Officer
Director
Delhi fire service

Copy to: -

1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

2. The Manager, M/s White Palace Guest House, 3034, Turkman Gate, Delhi

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

Appendix Services	INSPECTI	ON REPORT					
Lifet - m. lan Court House 3034 Turkman Gale							
1.	Name & address of the building: While palace Coust House, 3034, Turkman Gale,						
2.	Type of Occupancy : Lodging House / Eating House / Club : Renewal / New case						
3.	Type of Case : Renewal	new case	4/00/1837 Dated	24/10/20pg			
4.	. Type of Case : Reflewary From east : Reflewary From east : Letter No. Fe DFs MS G H/08 1937 Dated: 24 10 10 10 10 10 10 10 10 10 10 10 10 10						
5.	11126						
6.							
7.	1	iattopadnyay, ADC	<i>J</i> (11Q)				
8.	8. Name and designation of officers from the building side Mehboob Ali', Owner						
	from the building side	988					
	Teal of Construction		4/2012				
	. Applicant s letter 110.	NBC	Provided at site	Remarks			
S.	Minimum Standards on fire	Requirement	110vided at 510	MR/NMR			
No.	prevention and fire safety U/R 33	Requirement					
1	Access to building			MR			
	Road width		08 mt				
	Gate width	_	from the road	MR			
	Width of internal road		•) Commonweal			
2	Number, Width, Type & Arrangement of Exits						
	a. Number of staircases						
	Upper Floors	01	01	MR			
	Basements						
	b. Width of staircases		-				
2.5		- Characteristics of the Control of	1.0(20)	MR			
	Upper Floors						
	Basements c. Protection of exits	MA	MA				
	Fire check door	MA	n o	-			
	Pressurization	N) A	N A				
	e. No. of continuous staircases to terrace	01	01	MR			
		FM N	MA	Company of the Compan			
	g. Width of Corridor		MA	p			
	h. Door Size	MA	•0	-			
		MA	N/m				
3	Compartmentation.	Not required					

GF - Commercial we Ist floor - O4 Quest rooms + Reception and floor - O4 Quest rooms + O1 staff room yeth floor - O4 Quest rooms + O1 staff room yeth floor - Owner's residence. Jp.

While palace Cerust House, 3034, Tutkman Gale, Delhort

	Fire check door	MA	MA	_ ~	
	 Sealing of electrical shafts 	MA	m) A	~	
	 Fire Rating of shaft door 	MA	MA		
	Water Curtain	MA	MA		
	Fire Dampers	MA	MA		
4	Smoke Management System.				
	• Basements	30 a/c per hour	MA		
	Upper floors	12 a/c per hour			
			no		
5	Fire Extinguishers				
	• Total numbers 5	Walir Co, -3	provided	MR	
4	· Types co, water co,	CQ - 3	poorided	MR	
	IS marking	ISI marked	provided	mR	
6	First-Aid Hose Reels.		1		
	Total numbers on each floor		provided	MR	
	• Length of hose reel hose	30 m	povidad	IYR	
	Nozzle diameter	5 mm	provided	Me	
7	Automatic fire detection and alarming system.				
	Type of detectors	N) A	Ma		
	Location of Main Panel	MA	MA	_	
	Location of Repeater Panel	MA	MA	- Alexander	
	Alternate source of power	74	N/A		
	Hooters' Location	MA	N/A	· .	
8	MOEFA	MA	MA	, t	
9	Public Address System.	Required	poonided	MR	
10	Automatic Sprinkler System.				
	• Basement	Required	posvided	MR	
	Upper Floor	MA	NA.	_	
	 Sprinkler above false ceiling 	Mr	MA	-	
11	Internal Hydrants		•		
	Size of riser/down-comer	MA	MA	-	

4

Whele Palace Cenest House, 3034, Turkman Gate, bethi

	Number of hydrants per floor	MA	MA	-	
	Hose Box	MA	MA		
Y	Yard Hydrants.				
	Total number of hydrants	MA	NA		
	Hose Box	MA	MA		
3 1	Pumping Arrangements.		-0		
	Ground Level	MA	MA		
	Discharge of main Pump	MA	MA	Common Co	
	➤ Head of Main pump	MA	MA	-	
	Number of main pumps	n na	MA		
	Jockey Pump out put	MA	NA	-	
	Jockey pump head	MA	MA		
	> Standby Pump out put	MA	MA		
	Standby Pump Head	MA	MA		
	> Auto Starting/ Manual	N) A	N A		
	stopping Description Access	50 a	MA		
	Pump House AccessTerrace level	MA		MR	
	Terrace levelDischarge of pump	225 LPM	MS LPM		
	Head of the pump	30mt	30 ml-	MR	
	> Power Supply	Required	provided	mr_	
	Auto Starting of pump	_	Starting smitch pro	netw Mrz_	
14	Captive Water Storage for fire fighting.				
	Underground tank capacity	MA	MA		
	> Draw-off connection	MA	MA		
	Fire service inlet	MA	MA		
	> Access to tank	NA	MA		
	 Overhead Tank capacity 	2500 lb.	2500 18	MR	
15	Exit Signage.	Required	Provided	MR	
16					
10	Pressurization of Lift Shaft	MA	MA		

0

				4
	Pressurization of Lift lobby	n) 4	no	_
	Communication In lift Car	MA	MA	-
	Fireman's Grounding Switch	MA	Mo	
	Lift Signage	MA	MA	_
17	Standby power supply	Required	15 KVA	m 12
18	Refuge Area.	'	-	
	> Total Area	MA	MA	- Albany
	> Location	N/17	MA	Application of the Control of the Co
19	Fire Control Room	,		
	Detector System Panel	MA	MA	_
	Flow Switch Panel	MA	MA	_
	 PA System Panel 	Wh	· MA	1
	Batter backup	MA	MA	
	Building Floor Plans	MA	MA	
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	one CO2 lipse fire externuster found providences glect pand	mp
	1			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to /grant / renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer Name

Designation

Signature of the Inspecting Officer
Name (M.K. CHATTOPADHYAY)
Designation: - Assistant Divisional Officer

Do (center) Atutan