## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No F 6 / DFS / MS / 2012 / GH / 2723

Dated 2 6/0)/12

0

## FIRE SAFETY CERTIFICATE

Certified that the "Raja Inn" Guest House, located at 5, Arakashan Road, Pahar Ganj, New Delhi, comprised of Basement + Ground + Four upper floors having 39 guest rooms (Basement is used for storage purposes, Ground floor has Reception + 04 guest rooms + Lobby, First floor has 08 guest rooms, Second floor to fourth floor has 09 guest rooms at each floor, Terrace floor is sealed) was granted NOC by this department vide letter No F 6 / DFS / MS / GH / 2009/ 2003 dated 07.07.2009. The premise was re-inspected by the officer concerned of this department on 20.07.2012 in the presence of Mr. Harish found that the said Guest House have deemed complied with fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" A-I with effect from 2.6/07.//L. for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 2.6/0.7//2... at New Delhi.

Chief Fire Officer Delhi Fire Service

Copy to: -

- 1. The Owner, Raja Inn, Guest House, located at 5, Arakashan Road, Pahar Ganj, New Delhi.
- 2. The Addl. Comm. of Police (Lic) First Floor, Police Station Defence Colony, New Delhi.

Conditions for the validity of fire safety certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.
- 3. All the staff members must know the correct method operation of fire fighting system.
- 4. Any lapse rendering fire fighting system/equipment non-functional shall be risk and responsibility of the management.
- 5. This inspection report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. This NOC is for Guest Rooms only.

IN	SPECTION REP	ORT	
1. Name & address of the building:			A.K. Road Paha
2. Type of Occupancy :	Res/diabal	Cquest h	00%)
3. Type of Case	Old lex (	Renovel)	
4. Details of previous NOC	Letter No		
5. Fire Safety directives Letter No.:	NA		
6. Date of inspection	20/07//2		
7. Name of the Inspecting Officer:	ATULGA	R48 D.S.	yadav ·
3. Name and designation of Officer	Me Age	smal	
from the building side			
9. Year of Construction	Before 198	Pb (Ax p	of the Inthe
10. Applicant's letter No. : 2744	3/Add/cP/	Lic(Fr) 0	tatul 8/5/12
Minimum standards on fire prevention and fire safety U/R 33	BBL Requirements	Provided at site	Remarks MR/NMR
Access of building Road width		l.	
	NA	AND	MR Coldige
• Gate width	NA		
Width of internal road	WA	ACTION AND AND ARRANGED AND ACTION ASSESSMENT AND ACTION ASSESSMENT AND ACTION ASSESSMENT ASSESSMEN	
Number, width, Type & Arrangemen	its of exits		
a. Number of staircases	Jal	Ore	. MR
↑ Upper floors	oal	are	MR
Basements b. Width of staircases	TWO	TWO	MR
• Upper floors	0 80M	0.854	MR
Basements	0 Dong	0.05 hd	MR
c. Protection of exits Fire check door	NIA		
* Pressurization	14/4		
d. No of continuous staircase to terrace	NA	8 1	
to terrace	000	000	mR

	e. Width Of Corridor			
	with of compo	MA		
5 8	f. Door Size	h/()		
		14/4		
3.	Compartmentation			
	Fire check door	41/0		
9		NA	2 2	
	<ul> <li>Sealing of electrical shafts</li> </ul>	41/0		<u> </u>
		MA		0
	<ul> <li>Fire Rating of shaft door</li> </ul>		3	
	***	NA		
	<ul> <li>Water Curtain</li> </ul>	1///		B 0 0
	2. 2	NA		
11	• Fire Dampers	CONTROL PROCESSOR CONTROL OF THE SECURE OF T	TOTAL - II - ON THE REAL PROPERTY CONTRACT OF THE PROPERTY OF	AND PROPERTY AND
		NA		*
4.	Smoke managements System	1		
	Basements	30 a/c per hour	11/0	
ž.		- a to per nour	NA	2 0
-	■ Upper floors	12 a/c per hour	11/0	
		la de por noch	N/4)	
5,	Fire Extinguishers	•		
	<ul> <li>Total numbers</li> </ul>	15005	U/	m n
5		13.65		MR
	• Types		WT, 60,00	MO
	10	ISI marked	, - 0   1	TIL
	• IS marking.		UK	MO
6.	First - Aid Hose Reels	and the state of t		111/2
	Total numbers on each floor		1.	The second secon
	Total littinders on each Hoor	othe	Yea	MP
	<ul> <li>Length of hose reel hose</li> </ul>		1 1	110
	zongm of nose reel nose	30 mg	45	mp
-	<ul> <li>Nozzle diameter</li> </ul>			
		5 mm	45	mR
7	Automatic fire detection and alarming	g system		The state of the s
	<ul> <li>Type of detectors</li> </ul>	- 110		
× 1		NAI	y 0	
	<ul> <li>Location of Main Panel</li> </ul>	NIA		
	T and	14/11/		
	<ul> <li>Location of Repeater Panel</li> </ul>	MA		
	A.L.	1177		
	<ul> <li>Alternate source of power</li> </ul>	NA		-
	* Hooters' Lacation	The second section is the second section of the section		9 e
	<ul> <li>Hooters' Location</li> </ul>	NA		The state of the s
8.	MOEFA	YES	Urc	
9.	Public Address System Intlan	42	JES !	MR
10.	Automatic Sprinkler System	P	9)	MR
ķ	<ul> <li>Basements</li> </ul>	yk	LIE I	0 ()
8	<ul> <li>Upper Floor</li> </ul>	0.7	7	mR
	-	NA	MA	NIA
		1 1	1117	. 777

	* Sprinkler above false ceiling	N//	and and continuence and the continuence of the continuence and the	
111	Internal Hydrants	11/4	The state of the s	
	Size of riser/down-comer	h 11		
	of Hoof/down Comer	MA		
	<ul> <li>Number of hydrants per</li> </ul>	11/0	The second secon	•
	floor	NA		
		11/0		
10	* Hose Box	NH		
.12.	J CH CHILD			
	<ul> <li>Total number of hydrants</li> </ul>	NA		
1.3.	Hose Box	NA		The state of the s
1	1 0 5			
	Ground Level		The second less as a second se	
	<ul> <li>Discharge of main pump</li> </ul>	NA		
	Head of main nump			
	Head of main pump	N/A		
4	Number of main pumps	-		
	or mant panips	NA		V 0 0
	Jockey pump out put	NICO	The same and the s	
		14/4		
	Jockey pump head	N/A	The last section and building the section of the se	
	G 11 -	13/1)		•
	Standby Pump out put	NIA	The second secon	
1 8	> Standby Pump Head	1//		
	Standby Pump Head	NA		
	Auto Staring/Manual	///		
и	stopping .	N/A		
		41.60	to the same of the	
	> Pump House Access	NA		1
	<ul> <li>Terrace level</li> </ul>	11000	114	
		950 ypm	45	MR
	<ul><li>Discharge of pump</li></ul>	Qamt	- U	
	TT-1-0.1	9014	95	MR
	Head of the pump	UR	(de	mΩ
	Power supply	12		
	1 owel supply	110	1 10	m O
	➤ Auto starting of pump		95	1118
14.	Captive water Storage for fire fighting	<u> </u>	<i>U</i>	
	<ul> <li>Under ground tank capacity</li> </ul>	01/0		•
		14/4)		Λ.
	Draw of connection	1/0		was represented that the contract of the contr
		11/4		2
	Fire service inlet	NA		
	A A A A A A A A A A A A A A A A A A A	0 / 0 7		
	Access to tank	NA	t <sub>o</sub>	•
	Overhead Tank capacity	101000		0.0
	overnead rank capacity	10,000.	J>	MR

15	Exit Signage	VS.	Uh	
16.	Provision of Lifts		1 1)	· MR
	<ul><li>Pressurization of Lift Shaft</li><li>Pressurization of lift lobby</li></ul>	MA		
	Communication in lift Car	r/p		
	Fireman's Grounding Switch	NA		
17.	Example Lift Signage  Standby power supply	MA		
18.	Refuge Area	Yes	YES	m R
	> Total area	N/A		
	▶ Location	NA		
19.	Fire control room			
	<ul><li>Detector system panel</li><li>Flow Switch Panel</li></ul>	NA		•
	PA System Panel	MA		
	> Batter backup	NA	10 to	
	Building Floor Plans	NA		
20	C. T. I. P.	NA		•
20.	Special Fire Protection Systems for Protection of special Risks, if any;	NA		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/issue shortcomings as noted at serial numbers

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name ATULGARG

Name Dacson vie singh yeder

Designation DO/CC

Designation ADO (c. a)