GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, CONNAUGHT PLACE, NEW DELHI-110001

No. F6/MS/DFS/GH/2012/ 2798

Dated: 27/07/12

FIRE SAFETY CERTIFICATE

Certified that the Tara Palace Guest House located at 419, Esplanade Road, Cycle Marker, Delhi-110006 comprised of ground floor (Reception + Lift Lobby + Commercial use), 1st floor (Commercial use), 2nd floor (17 guest rooms + 02 store rooms), 3rd floor (16 guest rooms + 02 store rooms + Kitchen for Staff), terrace floor (D.G. set room + Mumty + Lift machine room + water tanks) total 33 guest rooms was granted NOC by this department vide letter No. F6/DFS/MS/GH/2010/2559 dated 03-09-2010. The premises was re-inspected by the officer concerned of this department on 16-07-2012 in the presence of Sh. Sushil Kumar Goyal and status of guest rooms /building is as under :- The building is comprised of ground floor (Reception + Office and lift lobby + Commercial use), 1st floor (Commercial use), 2nd floor (18 guest rooms + 01 Store room), 3rd floor (16 guest rooms + 01 Pantry (Kitchen), + 01 dining hall + 01 Store room) terrace floor (D.G. set room + Mumty + Lift machine room + water tanks) 34 guest rooms and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy of 34 guest rooms with effect from .2.7./......2012 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued .2.7./.o.2/12... at New Delhi.

Copy to :-

CHIEF FIRE OFFICER DELHI FIRE SERVICE

- 1. The Addl. Commissioner of Police (Lic.), First Floor, P.S. Defence Colony, New Delhi 110049
- 2. M/s Tara Palace Guest House, 419, Esplanade Road, Cycle Marker, Delhi-110006.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

INSPEC	TION REPORT		
1 1	Taxa Palace	419 Espe	anado o-
Name & address of the building:	cycle mi	allow Zope	200
2. Type of Occupancy	1 110	rkee Del	Lu -/1 206
Type of Case	ice, achieve	(Guett Hous	2)
1 Dotnila o	Saset Renewal 1	A company of the same of the s	
5. Fire Safety directives letter No :-	NoF6/MS/DFS	G. 4/20 10 10 - 10	
.6. Date of inspection	N.A	(6-11/2010/2534) atc	03-09-
7. Name of the t	16-07-2	0/9	
7. Name of the Inspecting Officers:	Dhagn iii		
and designation of officers	Dhagon vie s,	igh yadar	
from the building side	ei cucon		
9. Year of Construction	tot.	Klemas Goy	al.
1 / / DD11 con 1 / 1	weller was	0	The second secon
Minimum Standards on fire	23/-33/Adde	C.P/Aic(A) dt	4.21: #2-2
prevention and fire safety U/R 33	NBC	Provided at site	l l
Account of the safety U/AC 33	Requirement		Remarks
Access to building	and the second s	The same of the sa	MR/NMR
Road width	the property of the second	The second secon	
Gate width	N.A	N.A	MA
Width of internal road	N. A	NA	NA
And the second of the second o	N-A	Committee and the second secon	10.01
Number, Width, Type & Arrangement	of II-te	MIA	N.F
a. Number of staircases	A ANAITS		
* Upper Floors	*		
* Basements		Three (2+1)	M·R
	N. A	N. A	MA
b. Width of staircases			/V. FT
* Upper Floors	<u> </u>	83 cms 95 cms	M. A
* Basements	(2)	1.39 mtes each	to accommend
c. Protection of exits	N. A	N. A	N. A
* Fire check door			
	N. A	N. A	N. A
ⁿ Pressurization	N. A	N. A	N. A
c. No. of continuous staircases to terrace		N. A	N.A
g. Width of Corridor		The second state of the se	
h. Door Size	N. A	N-A	N.A
	N.A	N. A	N.A.

contd:

Taxa Palace, 419, Esplanade Road, cycle market, Delli-11006.

Co	unpartmentation.		ha	
2 5	Fire check door			
	 Sealing of electrical shafts 		N. A	
3.	• Fire Rating of shaft door		70 //	
	• Water Curtain			7
	 Fire Dampers 			
5	moke Management System.		\	
	• Basements	30 a/c per hour	N.A	N. A
	 Upper floors 	12 a/c per hour	N. A ratural ventilation	m.R
				5 ¹⁰
	Fire Extinguishers			
	• Total numbers		16 (Sixteen) w.coz and coz	m.R
	• Types	101	Type	M.R
	• IS marking	1SI marked	yes	M-R
	First-Aid Hose Reels.			
	Total numbers on each floor	one	one	m. R
-	 Length of hose reel hose 	30 m	yes	m.R
,	Nozzle diameter	5 mm	yer	M. K
1	Automatic fire detection and alarmin	g system.		
200	 Type of detectors 			
2	Location of Main Panel	A		
	Location of Repeater Panel		NA	
7	• Alternate source of power			<u> </u>
	• Hooters' Location			and the second s
	* Moders Location			
8	MOEFA	yes -	Provided Provided	m.R
9	Public Address System.	yes yes	Provided	M-K
10	Automatic Sprinkler System.			
	• Baselment	N.A	N.A.	N. A conta:

Tala Palace, 4/9 Esplanade Road, cycle market, solli-1/006.

• Upper Floor	N.A N.A	N. A	N.A
Sprinkler above false ceiling	N. A	N. A "N.A	N.A N.A
Internal Hydrants			
Size of riser/down-comerNumber of hydrants per floor		100 mm.	M·R
• Hose Box		Two	M.R
Yard Hydrants.		Two at each	M.R.
and segments.	•		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
* Total number of hydrants		N.A _	
* Hose Box		N.O.	
Amping Arrangements.	•		
↑ Ground Level			The second secon
Discharge of main Pump			The second secon
> Head of Main pump			The second of th
> Number of main pumps			The second secon
> Jockey Pump out put		NA	
> Jockey pump head		1	The second secon
> Standby Pump out put			
> Standby Pump Head			
> Auto Starting/ Manual			
stopping	The second secon	The commence of the commence o	<u> </u>
> Pump House Access	Make white publishing the goal season are the season of th	,	
* Terrace level			
> Discharge of pump	900 L.P.	M 900 L.PM	M.R.
> Head of the pump	30 MTE	8 30 M 188	M.R.
> Power Supply	Electrici	900 L.P.M 8 30 M tes to Electricity	N.A
> Auto Starting of pump	yes	2 Electricity Provided	M.R
[4] Captive Water Storage for fire fighting	Constitution of the Consti		
 Underground tank capacity 	N.A	N.A	NA
> Draw-off connection	N. A	N.A	n. A

contd:

	Fire service inlet Access to tank	N.A		1
	Overhead Tank capacity	N.A	N.A N.A	N.A
15	Exit Signage.	10,000 lite		MA.
16	Provision of 1 :c-	Yes	D.	N.R
	Pressurization of Lift Shaft	ft from geo.	rend floor to 3-81	M-R
	Pressurization of Lift Shaft	N.A	N. A.	
	Communication In lift Car	N.A	The state of the s	N.A
	Fireman's Grounding Switch	yes	N. A Yes	N.A
	* Lift Signage	Yes	The state of the s	m.R
17	and the same of th	yes	yes	m·R
18	Standby power supply		yes	W.V
	Refuge Area.	The second secon	D.G. Set (SOKUA)	M·R
	Total Area	The playing as the management of the second		the second secon
1)	Location		NA -	
1772	Eire Control Room		N.A	to the second se
	Detector System Panel	the base that the state of the base of the		
	* Eldw Switch Panel			and here of the second and the secon
	* PAi System Panel	the same of the sa		-
	* Balter backup		N.A	
- American	Building Floor Plans			
). (Special Fire Protection Systems C			The state of the s
]	Protection of special Risks, if any:		W: A	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Tola Palace, 419 Esplanade loss, cycle market, selli-11006 19

Signature of the Inspecting Officer

Name

Designation

Do. (central) 19/07/12

Signature of the Inspecting Officer

Name Dhalm vil singlyada.

Designation Assistant sivisione Officel (certial)