## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No F 6 / DFS / MS / 2012 / GH / 28 41

Dated 03/08/12

## FIRE SAFETY CERTIFICAT

Certified that the "City Palace" Guest House, located at 12, Arakashan Road, Pahar Ganj, New Delhi, comprised of Ground + Four upper floors having 19 guest rooms (Ground floor has Reception, First to Third floor has 05 guest rooms at each floor, Fourth floor has 05 guest rooms but one room is being used for staff kitchen, Terrace floor having 01 staff room sealed) was granted NOC by this department vide letter No F 6 / DFS / MS / GH /2009/ 1827 dated 23.06.2009. The premise was re-inspected by the officer concerned of this department on 24.07.2012 in the presence of Mr. Mayank Dubey found that the said Guest House have deemed complied with fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" A-I with effect from O2/o2/o2. for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .0.3/.08/./2..... at New Delhi.

Chief Fire Officer Delhi Fire Service

ML

Copy to: -

- 1. The Owner, City Palace Guest House, located at 12, Arakashan Road, Pahar Ganj, New Delhi.
- 2. The Addl. Comm. of Police (Lic) First Floor, Police Station Defence Colony, New Delhi.

Conditions for the validity of fire safety certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.
- 3. All the staff members must know the correct method operation of fire fighting system.
- 4. Any lapse rendering fire fighting system/equipment non-functional shall be risk and responsibility of the management.
- 5. This inspection report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. This NOC is for Guest Rooms only.

OldCool PSS area

	<u>IN</u>	SPECTION REP	<u>ORT</u>	
	1. Name & address of the building:	M/S CILY /	ralace,	12, A.K. Road
		<u> Pahat gaz</u> Resideatial (		()
	3. Type of Case :	Renewal (O)	ld (oge)	
	4. Details of previous NOC :	Letter No /8/30/	Add/CP/40	datel 9/04//
	5. Fire Safety directives Letter No.:		·	
	6. Date of inspection :	93/07/12		- 1511
	7. Name of the Inspecting Officer:	ATULGA	29 8 D.S	S. Gadal
	8. Name and designation of Officer			•
£	from the building side  9. Year of Construction :  10. Applicant's letter No. :	Before 200 40203/Add	01 (AS F 11 CP/LIC da	by Tenl tonfu ted 21/09/2
S	Minimum standards on fire	BBL	Provided at	Remarks MR/NMR
No 1.	prevention and fire safety U/R 33 Access of building*	Requirements	site	
	Road width	NA	3 mt	00
	Gate width	NA		
	Width of internal road	WA		
2.	Number, width, Type & Arrangeme	nts of exits		
	a. Number of staircases	000	are	MR
•	• Upper floors	Oal	ose	MR
	Basements	MA		
	b. Width of staircases		1	
	• Upper floors	0.8 mg	0.92043	MR
	Basements	MA	W/A	
	<ul><li>c. Protection of exits</li><li>Fire check door</li></ul>			
ę	9	MA.		
10	<ul><li>Pressurization</li><li>d. No of continuous staircase</li></ul>	WA		
	to terrace	one.	oal	MR

	Wild oos			
	e. Width Of Corridor	NA		
5	f. Door Size	NA		•
3.	Compartmentation	1711		6
	Fire check door			
	THE CHECK GOOT	K1/n		
	Sealing of electrical shafts	NA		* '
	Fire Rating of shaft door	N/A.		y y
	Water Curtain	NA	,	
	Fire Dampers	NA		
4.	Smoke managements System			
	<ul> <li>Basements</li> </ul>	30 a/c per hour		
		o are per nour	NIA	ē.
	• Upper floors	12 a/c per hour	NA	
5.	Fire Extinguishers		1///	o.
	Total numbers	7/		×
	Total numbers	Wefve	12 MS	MP
	• Types			11
	Types	TOT	WT, COS, DCP	MP
	a IC mode	ISI marked		
6.	• IS marking		ys	MR
0.	First – Aid Hose Reels			9
	Total numbers on each floor	One	48	MR
	<ul> <li>Length of hose reel hose</li> </ul>	Bonh	ys	mR
	Nozzle diameter	5 mm	ys	MP
7.	Automatic fire detection and alarming	System		
	Type of detectors	1 / ·		
		NA		
	Location of Main Panel	N/A		. *
8	• Location of Repeater Panel	N/A		0
	Alternate source of power	NA		
	Hooters' Location	WA		o
8.	MOEFA	x//n		
9.	Public Address System /Talacan	10		
10.	Automatic Sprinkler System	45	75	Me
	Basements	1/60		
	• Upper Floor	NA	i.	
	Sprinkle 1	MA .		0
11.	Sprinkler above false ceiling  Internal II. I	NA		
11.	Internal Hydrants			
	<ul> <li>Size of riser/down-comer</li> </ul>	NIA		
		· V		

	N 1 01 1	T		1, 500,000
1	Number of hydrants per	N/A		
	floor	(0)		
12.	Hose Box *  Yard Hydrants	NA		v
12.		1/0		
	<ul><li>Total number of hydrants</li><li>Hose Box</li></ul>	MH		•
13.		MA	`	
13.	Pumping Arrangements			
	Ground Level		1	
	Discharge of main pump	NA		
•	➤ Head of main pump	NA		
	Number of main pumps	NA	4	
8	Jockey pump out put	N/A		
	Jockey pump head	MA		
	Standby Pump out put	NA		4
La de la constante de la const	Standby Půmp Head	N/A.		
	➤ Auto Staring/Manual	100		
	stopping	NA		
		1/10		
	Pump House Access	N/I+		,
	<ul> <li>Terrace level</li> </ul>			
	Discharge of pump	225 Spm	45	MR
٥	➤ Head of the pump	30 MK	y	MR
	Power supply	B	B	MR
14.	Auto starting of pump	Y	P	MR
14.	Captive water Storage for fire fighting	g		¥
	<ul><li>Under ground tank capacity</li><li>Draw of connection</li></ul>	NA.		
	Fire service inlet	N/F		
	> Access to tank	1100		
	°	MA		
	Overhead Tank capacity	2500 19	CK	MP
15	Exit Signage	V2	(se	00.0
16.	Provision of Lifts.	F)	7)	. 111
	Pressurization of Lift Shaft	MA		
	Pressurization of lift lobby	MA		
•	Communication in lift Car	NA		
		/		

	<ul><li>Fireman's Grounding</li><li>Switch</li><li>Lift Signage</li></ul>	NA		· · · · · · · · · · · · · · · · · · ·
17. 18.	Standby power supply	N/A		1
10.	Refuge Area  > Total area	1/4	Js.	Me
19.	Fire control room	MA	,	0
	<ul><li>Detector system panel</li><li>Flow Switch Panel</li></ul>	WA		
	<ul><li>➢ PA System Panel</li><li>➢ Batter backup</li></ul>	NA	Y	
20.	Building Floor Plans  Special Fire Protection Systems for  Protection of	WA		
	Protection of special Risks, if any;	NA		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the shortcomings as noted serial

Signature of the Inspecting Officer

Name

Signature of the Inspecting Officer

Name Dholon vie ringh yodlor

Designation

Designation AD