GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No F 6 / DFS / MS / 2012 / 9/3/ 2827

Dated 02/08/2012

FIRE SAFETY CERTIFICAT

Issued on ... 6.2 0.8 2012 at New Delhi by.

Chief Fire Officer Delhi Fire Service

orch

Copy to: -

- 1. The Addl. Comm. of Police (Lic) First Floor, Police Station Defence Colony, New Delhi.
- 2. Kapoor Inn, F-39, East of Kailash, New Delhi - 110065,

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be uses as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

- 1. Name & address of the building:- Kapoor Inn,F-39,East of Kailash,New Delhi-110065.
- 2. Type of occupancy:- Residential Lodging or Rooming Houses.
- 3. Type of case:- Renewal
- 4. Details of previous NOC:-F6/DFS/MS/GH/2008/2384 dated 21/08/08
- 5. Fire safety directives No.- No
- 6. Date of inspection: 16/07/12.
- 7. Name of the inspecting officer:- A.D.O. S.S. Kaushik
- 8. Name & designation of officer

From the building side:- Mr. Amrit Lal Kapoor.

- 9. Year of construction:- 1978
- 10. Applicant's letter No:- Nil. dated 15/06/12 basement, ground + 3 upper floors for 17 guest rooms

	rooms Old Case					
S.No.	Minimum Standards on fire	BBL	Provided at	Remarks		
	Prevention and fire safety U/R 33	Requirement	site	MR/NMR		
1.	Access to Building					
	1) Road width	12 mtr.	Provided	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arrange					
	A. Number of staircases					
	1. Upper floors	1 Nos.	Provided	MR		
	2. Basements	2 Nos.	Provided	MR		
	B. Width of staircase					
	1. Upper floors	Required Adcase	Provided 1250	MR		
	2. Basements	Old Case	Two 125 x 70	MR		
			Provided (m)			
	C. Protection of exits		•			
	1. Fire check door	N/A	DT/A	27/4		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous staircase	One	N/A	N/A		
	to terrace	One	One	MR		
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 mtr.	1 mtr.	MR		
•	Compartmentation	T IIICI.	IVIIX			
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
•	Smoke Management System					
	1) Basements	30 a/c per hour	Exhaust fan	MR		
-	2) Upper floors	12 a/c per hour	N/A	N/A		
	Fire Extinguishers					
	1) Total numbers		14 Nos.	MR		
	2) Types		ABC &W.Co2	MR		
	3) ISI marking	ISI Marked	Yes	MR		
	First-Aid Hose Reel					

	1) Total number of each floor			Entre V
	2) Length of hose reel hose	One	1 at each floor	
	3) Nozzle diameter	30 m	Yes	MR
7.		5 mm	Yes	MR
7.	Automatic Fire Detection & Alarmin 1) Type of detectors			22.73.20.20.
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
		N/A	N/A	N/A
	4) Alternate source of power5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	N/A	N/A	N/A
9.		Yes	Provided	MR
10.	Public Address System	N/A	N/A	N/A
10.	Automatic Sprinkler System			
	1) Basement	Yes	Provided	MR
	2) Upper floors	N/A	N/A	N/A
11.	3) Sprinkler above false ceiling	N/A	N/A	N/A
	Internal Hydrants			100 100 700 700
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per floor	N/A	N/A	N/A
2.	3) Hose box	N/A	N/A	N/A
4.	Yard Hydrants	н		
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
3.	P. Parkers			14/11
J.	Pumping Arrangement			
	Ground level	N/A	N/A	N/A
	a) Discharge of main pump	N/A	N/A	N/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	
	h) Auto starting/Manual stopping	N/A	N/A	N/A
	2) Terrace level	1071	IN/A	N/A
	a) Discharge of pump	Required	450 LPM & 180 LPM	MR
	b) Head of pump	Required	35 mtr.	MR
4.	c) Power supply	Yes	Provided	MR
	d) Auto starting of pump	Yes	Yes	MR
•	Captive Water Storage for Fire Fightin	ıg		1111
	1) Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A N/A
	b) Fire service inlet	Yes	Provided	
	c) Access to tank	N/A	N/A	MR N/A
	d) Over head tank capacity	5,000 ltrs.	5,000 ltrs.	MR
	Exit Signage.	Yes	Provided Provided	
5.	Provision of Lifts.		1 TOVICEU	MR
	a) Pressurization of lift shaft	27/4		
		N/A	N/A	N/A
	b) Pressurization of lift lobby c) Communication in lift car	N/A		N/A
		N/A	N/A	N/A
	d) Fireman's switch	Yes		MR

	e) Lift signage	N/A	N/A	N/A
17	Stand by Power Supply	Yes	D.G. Set	MR
17.	Refuge Area	N/A	N/A	N/A
18.	Total area location	N/A	N/A	N/A
10	Fire Control Room	N/A	N/A	N/A
19.	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for		ecial Risk, if any:	N/A

The fire protection system provided in the building were checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rules 35 of the Delhi Fire Service Rules 2010/

Signature of the inspecting officer

Signature of the inspecting officer

Name

Designation

Name: - S.S.Kaushik.

Designation:- Assistant Divisional Officer.

Dosouth

56/7/12