## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

NO. F6/MS/DFS/9H/2012/2833

DATED: 03/08/12

## FIRE SAFETY CERTIFICATE

Certified that the M/S Shyama International Inn C-5/32 Safderjung Development Area New Delhi comprise of Basement(Storage), ground plus three upper floors(23 Guest Rooms) was granted N.O.C by this department wide letter no. F6/MS/DFS/GH/09/2264 Dt.27/07/2009.. The premises re-inspected by the officers concerned of Fire Service on 10/07/2012 in the presence of Mr. Umesh Singh and found that the said Guest House have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of Delhi Fire Service Rules,2010 and that the premises fit for occupancy class Lodging or Rooming House of Group-A "with effect from which is a period of three years, subject to conditions as mentioned below.

Issued on .0.3./. 08/12 at New Delhi by

Chief Fire Officer Delhi Fire Service

Copy To:-

1. Shyama International Inn C-5/32 Safderjung Development Area, New Delhi.

2. The Addl. Commissioner of Police (Lic.) first floors, Police Station, Defence Colony, New Delhi.

## Conditions for the validity of fire safety certificate

- 1. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- 2. Building Sanctioning authority may verify any deviation with regard to the construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- 3. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- 4. The basement shall be used strictly as per the provisions of Building Bye laws.
- 5. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules-2010. The form is available on www.dfs.delhigo/t.nic.in

3		INSPECT	ION REPOR	RT			
1		Shyama International Inn, C-5/32,Safdarjung Devlopment Area, N Delhi					V
2	Type of Occupancy	Residential	& Lodging "A	ı		and the second second	
3	Type of case	Renewal		57			
4	Details of previous NOC	F6/MS/DFS/GH/2009/2264 Dated 27/07/2009.					
5	Fire safety directives letter No	No					
6	Date of inspection	10/7/2012					
7	Name of the inspecting Officers : Name and designation of officers from the building side	Mr.Umesh Singh					
8	from the building side	Basement, Ground+3 Upper floors 23 guest Room					ms.
9	Year of construction	1981					
		1		2	Old Case		
40	Applicant's letter No.	20067/Ada	I. C.P/Lic.(H)	20/06/2012		ž I	
10 S. NO.	Applicant's letter No.  Minimum Standards on fire prevention and fire safety U/R 33	NBC Req	uirement/Old case		ided at site	Remarks MR / NMR	
1	Access to building			L			
	1) Road width	Required		18 Mtrs		MR	
	2) Gate width	N/A		N/A		N/A	
	3) Width of internal road	N/A		N/A		N/A	
2	Number, width Type & arrangement of	exits					
	a. Number of staircases	1					1,
	,						
	1. Upper floors	Old case	W	Provided 2		MR	
	2. basements	Old case		Provided 2	2Nos	MR	
	b. Width of staircase			Dravidad (	ONION + 99 (m. Par)		
	1. Upper floors	Required		Provided 2Nos + 22 (m cac)		11111	-
	2. basements	Required		Provided 2Nos 1-504-1-20		MR Old ca	se
	c. Protection of exits					1.1/4	-
	1. Fire check door	N/A		N/A		N/A	
	Pressurization     No. of continuous staircase to terrace	N/A Requied		N/A 2 Nos. Stairs Provided		N/A MR	
	e. Width of corridor	N/A	N/A		N/A		
	f. Door size	1 Mtr		Provided		MR	
3	Compartmentation.						
	1. Fire check door	N/A		N/A		N/A	
	2. Sealing of electrical shafts	N/A		N/A		MR	
	3. Fire Rating of shaft door	N/A		N/A		N/A	
	4. water curtain	N/A		N/A		N/A	
	5. Fire dampers	N/A		N/A		N/A	
4	Smoke Management system.						
	basement	30 a/c per hour 12 a/c per hour		Exhust Fans Provided		MR	
	upper floors			Natural v	antilation	MR	
5	Fire Extinguishers			-		T	
	total numbers			15 Nos		MR	_
	Types	4		ABC, Co2 & W.Co2		MR	4
	ISI marking	ISI	-	Yes		MR	-
6	First-Aid Hose Reels.					1	-
	total numbers on each floor	One		Provided		MR	-
	Length of Hose reel hose	30 m		Provided		MR	-
	Nozzle Diameter	5 mm		Provided		MR	

	Automatic fire detection and alarmin	N/A	N/A	N/A	
	Type of detectors		N/A	N/A	
	location of Main Panel	N/A	N/A	N/A	
	location of Repeater panel	N/A	N/A	N/A	
	Alternate source of power	N/A	N/A	N/A	
	hooter's location	N/A	Provided	MR	
	MOEFA	Required		N/A	
)	Public Address System.	N/A	N/A		
0	Automatic Sprinkler System.		NI/A	N/A	
	basement	N/A	N/A	N/A	
	upper floors	N/A	N/A	N/A	
	sprinkler above false ceiling	N/A	N/A	114/7	
1	Internal Hydrants		151/2	N/A	
•	Size of riser/down-corner	N/A	N/A	N/A	
	Number of Hydrants per floor	N/A	N/A	N/A	
	hose Box	N/A	N/A	114/75	
12	Yard Hydrants.		1	N/A	
-	total number of hydrants	N/A	N/A	N/A	
	hose box	N/A	N/A	IN/A	
13	Pumping arrangements				
13	1. Ground level		<u> </u>	NI/A	
	a. Discharge of main Pump	N/A	N/A	N/A	
	b.Head of main pump	N/A	N/A	N/A	
	c.Number of main pumps	N/A	NOW NO	N/A	
	d.jockey pump out put	N/A	N/A	N/A	
	e.jockey pump head	N/A	N/A	N/A	
	f. Standby Pump output	N/A	N/A	N/A N/A	
		N/A	N/A		
	g.Stanby Pump head	N/A	N/A	N/A	
	h.Auto Starting/Manual stopping	N/A	N/A	N/A	
	pump house access	14/7			
	2.Terrace level	Old case	180 LPM Provided	MR	
	a. Discharge of pump	Old case	Provided	MR	
	b. head of the pump	Required	Provided	MR	
	c. Power supply	Required	Provided	MR	
	d. Auto starting of pump	riequired	1 Tovidou		
14	Captive water storage for fire figl	nting			
14	Underground tank capacity	N/A	N/A	N/A	
	a. Draw-off connection	N/A	N/A	N/A	
	b. fire service inlet	N/A	N/A	N/A	
	c.Access to tank	N/A	N/A	N/A	
		5000 ltrs.	5000 Ltrs.	MR	
	Over head tank Capacity	Required	Provided	MR	
15	Exit Signage.	T toquir ou			
16	Provision of lifts.	N/A	N/A	N/A	
	a. Pressurization of lift shaft	N/A	N/A	N/A	
	b. pressurization of lift lobby	N/A	N/A	N/A	
	c. communication in lift car		Provided	MR	
	d. Fireman's grounding switch	Rrquired	Provided	MR	
	e. Lift signage	Required	Provided	MR	
17		Required	Not Required		
18	Refuge Area.		Not rioquirou		
	total area				

19	Fire cont	rol room					
	a. detecto	r system Panel	N/A	N/A	N/A		
		vitch Panel	N/A	N/A	N/A		
	c. PA sys	em Panel	N/A	N/A	N/A		
	d. Battery		N/A	N/A	N/A		
		floor plans	N/A	N/A	N/A		
20		cial Fire Protection systems for protection of special risks, if any:					

The fire protection systems provided in the building were checked and found functional at the time of inspection. Keeping in view the substantial compliance of ne minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rules 35 of the Delhi Fire Service Rules 2010. Accordingly DFA is put up for your approval and signature please.

Signature of the inspecting officer

Name

D. P. Bhardwaj

Designation : Divisional Officer (South)

Signature of the Inspecting Officer

Name

S.S. Kaushik

Designation

A.D.O. (BCP)