GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No F 6 / DFS / MS / 2012 / 5H / 28 / 1

Dated 09/08/12

FIRE SAFETY CERTIFICATE

Certified that the "Indo Continental" Guest House, located at 8490-91, Arya Nagar, Pahar Ganj, New Delhi, comprised of Basement + Ground + Four upper floors having 21 guest rooms (Basement is used for storage, Ground floor has Reception + 01 guest room + 01 office, First to Fourth floor has 05 guest rooms at each floor) was granted NOC by this department vide letter No F 6 / DFS / MS / GH /2010/ 216 dated 21.01.2010. The premise was re-inspected by the officer concerned of this department on 25.07.2012 in the presence of Mr. Ashok found that the said Guest House have deemed complied with fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" A-I with effect from \$\infty \infty \frac{1}{2} \infty \frac{1

Issued on .09/.08./12..... at New Delhi.

Chief Fire Officer Delhi Fire Service 6

Copy to: -

- 1. The Owner, Indo Continental Guest House, located at 8490-91, Arya Nagar, Pahar Ganj, New Delhi.
- 2. The Addl. Comm. of Police (Lic) First Floor, Police Station Defence Colony, New Delhi.

Conditions for the validity of fire safety certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.
- 3. All the staff members must know the correct method operation of fire fighting system.
- 4. Any lapse rendering fire fighting system/equipment non-functional shall be risk and responsibility of the management.
- 5. This inspection report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. This NOC is for Guest Rooms only.

| 1 | | PECTION REPO | | |
|-----|--|--|----------------|-------------------|
| ю | 1. Name & address of the building: | M/S Indo A-C-Road R81 Serted (GU | Contraca Pakas | tal ,0490/91 |
| ۰ | 2. Type of Occupancy : | esidestral (Gu | iestrase) | |
| | 3. Type of Case : - | Lenewal (ala | (Ocol) | |
| 2 | 4. Details of previous NOC : Le | etter No | | |
| | 5. Fire Safety directives Letter No. : | <i>M</i> / | <u>A</u> | |
| (| 6. Date of inspection : | 25/07/12 | | |
| , | 7. Name of the Inspecting Officer: | ATUGE | ARG 2 059 | adav |
| | 8. Name and designation of Officer | MY AShat | | |
| | from the building side | · (- a a | a (Al har | - real available |
| , | 9. Year of Construction : | 36 hos 200 | I C IBPO | Infile) |
| | 10. Applicant's letter No. : - | 31303/AddCf | / LidH) a | tated 28/05/12 |
| | | • | | |
| S | Minimum standards on fire | BBL | Provided at | Remarks MR/NMR |
| No | prevention and fire safety U/R 33 | Requirements | site | remarks wild will |
| 1. | Access of building | | | |
| | Road width | NA | 3nt | Me |
| | • Gate width | NA | | 8 9 2° § 8 |
| | Width of internal road | WIA | | 1 1 1 |
| 2. | Number, width, Type & Arrangement | s of exits . | | , |
| | a. Number of staircases | one | one | are/mr |
| | • Upper floors | one | are | · MR |
| | Basements | crae | one | MR |
| 4 | b. Width of staircases | 0 1 | | |
| | • Upper floors | 0.8 mg | 1.20 m | MR |
| • | • Basements | o. Oms | 1.00 | m R |
| | c. Protection of exits | | | |
| | Fire check door | MA | 8 | |
| | Pressurizationd. No of continuous staircase | NA | | |
| 8/1 | to terrace | cool | me | m R |

| | WY LI CO. | | | |
|-----|---|-----------------|------------|----------------|
| | e. Width Of Corridor | NA | | |
| | f. Door Size | 11.0 | | |
| 3. | Comment | NA | | |
| 3. | Compartmentation | | | |
| | Fire check door | 1/10 | | e |
| | | NIH | | |
| | Sealing of electrical shafts | NA | | |
| | Fire Rating of shaft door | MA | | |
| | Water Curtain | WA | | v |
| | Fire Dampers | LX/A | | |
| 4. | Smoke managements System | 177 | | |
| | Basements | 30 a/c per hour | | 9 |
| | | 30 a/c per nour | NA | |
| | • Upper floors | 12 a/c per hour | 12.0 | |
| | | 12 die per nour | NA | |
| 5. | Fire Extinguishers | | / / | |
| | Total numbers | Tea | Ten | |
| | | 1-(100 | Hen | MR |
| | Types | • | WT, CONDIA | A D |
| | | ISI marked | 101/10(| 11 2 |
| | IS marking | | Les | (11 |
| 6. | First – Aid Hose Reels | | 1) | 9) |
| | Total numbers on each floor | an | one | me |
| | • Length of hose reel hose | 30 mk | K | Me |
| | Nozzle diameter | 5 mm | W. | MD |
| 7. | Automatic fire detection and alarming | g system | | |
| | Type of detectors | 1100 | | |
| | | NA | | , ^N |
| | Location of Main Panel | WA | | |
| | Location of Repeater Panel | N/h | | |
| | Alternate source of power | Nh | | |
| | Hooters' Location | 6/10 | | |
| 8. | MOEFA | NA | | |
| 9. | | | | |
| 10. | Automatic Sprinkler System // | | | |
| | Basements | V/3 | | |
| | | 79 | 9 | MA |
| | • Upper Floor | NA | | |
| 11. | • Sprinkler above false ceiling Internal Hydrants | NA | | |
| | | | 3 | 9 |
| | Size of riser/down- comer | NA | | V |
| | | () | | |

| _ | 6 0 | - | | |
|-----|--|----------|------|---------|
| | Number of hydrants per | AVA | | |
| | floor | 1 1 1 1 | | |
| | Hose Box | NA | | |
| 12. | Yard Hydrants | 1777 | | |
| | Total number of hydrants | A //h | | |
| | Hose Box | MA | | |
| 13. | | NH | | |
| 13. | Pumping Arrangements | (| | |
| | Ground Level | | | |
| | 9 | 1/10 " | | |
| | Discharge of main pump | WH | | |
| | | 1/1 | | |
| | Head of main pump | 14/1 | | 0 |
| | | 1/16 | | |
| | Number of main pumps | 11/1 | | |
| 3 | | 101/10 | | |
| | Jockey pump out put | MA | | |
| | | N1/0 | | |
| 48 | Jockey pump head | WIT | | |
| • | 6 | | | |
| | Standby Pump out put | NIA | | |
| | , | 10/11 | | |
| | Standby Pump Head | NA | | |
| | ➤ Auto Staring/Manual | 17/1 | | |
| | stopping | 4)4 | | |
| | stopping | 1011 | | |
| | Pump House Access | WA | | |
| | Terrace level | 1971 | , | |
| | o Terrace level | | | |
| | Discharge of pump | UC: 1ho | - CM | mo |
| | bischarge of pump | 730400 | ' /) | 11/1/2 |
| | ➤ Head of the pump | 20m-1 | 10 | no O |
| | Head of the pump | 3019 | | . /// 0 |
| - | > Power supply | y | UR | YK |
| | Power supply | | | |
| | A 1 1 1 C | me | me | na (i) |
| | Auto starting of pump | 111 | 0011 | 11/12 |
| 14. | Captive water Storage for fire fighting | g | | |
| | Under ground tank capacity | WA | | |
| | Draw of connection | PA | | |
| | Fire service inlet | WA | | |
| | Access to tank | dia | | |
| | | N/71 | | |
| | Overhead Tank capacity | | | |
| 15 | Exit Signage | 42 | 11/ | |
| 16. | Provision of Lifts. | | 75 | MQ |
| | or Direction | | V | |
| | Pressurization of Lift Shaft | | | |
| | r 1035ull Zation of Lift Shaft | WA | | |
| * | Pressurization of lift lobby | 7 / 1 0 | | |
| | Pressurization of lift lobby | WA | | |
| | Communication in lift Car | | | |
| | Communication in lift Car | MA | | 0 |
| | | 1/1+ | | |
| | | <i>)</i> | | |

| | Fireman's Grounding | | |
|-----|---|-------|----|
| | Switch > Lift Signage | NA | |
| 17. | Standby power supply | WA | 0 |
| 18. | Refuge Area | 48 45 | ne |
| | Total areaLocation | WA | * |
| 19. | Fire control room | A/A | |
| | Detector system panelFlow Switch Panel | N/A | |
| | PA System Panel | A A | |
| | ➢ Batter backup➢ Building Floor Plans | NA | |
| 0. | Special Fire Protection Systems for | WIX | |
| | Protection of special Risks, if any; | N/A | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the shortcomings as noted serial numbers

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name D. S. yedav

Designation

Designation ADO