## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No F 6/DFS/MS/2012/GH/2948

Dated 0 9/08/12

## FIRE SAFETY CERTIFICATE

Certified that the "Sindh Palace" Guest House, located at 7966, Arakashan Road, Pahar Ganj, New Delhi, comprised of Ground + Four upper floors having 09 guest rooms (Ground floor has Reception + 01 guest room, First to Fourth floor has 02 guest rooms at each floor) was granted NOC by this department vide letter No F 6 / DFS / MS / GH /2009/ 2212 dated 23.07.2009. The premise was re-inspected by the officer concerned of this department on 06.08.2012 in the presence of Mr. Suresh found that the said Guest House have deemed complied with fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" A-I with effect from ... 29./.08./.1... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on  $... \bigcirc .$   $9. /. \alpha \otimes /. /.2...$  at New Delhi.

Chief Fire Officer
Delhi Fire Service

## Copy to: -

- 1. The Owner, "Sindh Palace" Guest House, located at 7966, Arakashan Road, Pahar Ganj, New Delhi.
- 2. The Addl. Comm. of Police (Lic) First Floor, Police Station Defence Colony, New Delhi.

Conditions for the validity of fire safety certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.
- 3. All the staff members must know the correct method operation of fire fighting system.
- 4. Any lapse rendering fire fighting system/equipment non-functional shall be risk and responsibility of the management.
- 5. This inspection report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. This NOC is for Guest Rooms only.

add Cost Splarea

		11/2	PECTION REPO	<u>DRT</u>	377		
	1.	Name & address of the building:	M/S Stack	palace	7966, A.K. Road		
			Pahong	anj.			
	2.	Type of Occupancy	Residential (	- guedena	se)		
	3.	Type of Case : 4	eld (Renev	val)	A de la constant de l	b	
	4.	Détails of previous NOC : L	etter No FG DPS	1ms14H/20	109/2012 datd 20	107/09	
•	5.	Fire Safety directives Letter No. : -	N/A				
	6.	Date of inspection :	6/8/12				
	7. Name of the Inspecting Officer: ATUGARY & D-5. Yadav						
	8.	Name and designation of Officer	My Cuza	ih.			
	from the building side						
	0		Refor 200	2 (Asb	& Oul mill	()	
	9.	Year of Construction :-	20170	CIA	20 out moft		
	10	Applicant's letter No.	29499/Add	CP/VC	later 18/5/1		
				7			
					,		
S	. N	Minimum standards on fire	BBL	Provided at	Remarks MR/NMR		
No	p	revention and fire safety U/R 33	Requirements	site	Remarks WIOTVIVIK		
1.	F	access of building					
		• Road width	N/A				
٥		• Gate width	NA				
		<ul> <li>Width of internal road</li> </ul>	N/A		, a		
2.	N	Number, width, Type & Arrangements of exits					
		a. Number of staircases	me	CORP	M D		
				200	0 0		
		• Upper floors	oral	One	MK		
		<ul><li>Basements</li><li>b. Width of staircases</li></ul>	N/A	N/A	NAM R		
		<ul><li>Upper floors</li></ul>	0 0 +				
			0.0mg	1.15 mg	MR		
		• Basements ·	N/A		•		
		c. Protection of exits					
		• Fire check door	N/A				
		<ul><li>Pressurization</li><li>d. No of continuous staircase</li></ul>	N/A	5			
٥		to terrace	0006	One	MR		

	e. Width Of Corridor			~>
	o. Width Of Coffidor	NA		*
	f. Door Size	7/10		V
		NA		
3.	Compartmentation			
	<ul> <li>Fire check door</li> </ul>	01/h		
-		JN//-		e
	<ul> <li>Sealing of electrical shafts</li> </ul>	N/A		
	• Fire Rating of shaft door	NA		g e
	Water Curtain	N/A		
	Fire Dampers	NA		7
4.	Smoke managements System	1		
	Basements	30 a/c per hour	1.10	
		30 are per nour	I N/A	
	<ul> <li>Upper floors</li> </ul>	12 a/c per hour	NVD	
5.	Fire Ford'	1	144	
J.	Fire Extinguishers			
	• Total numbers	6	CIX	m D
	• Types			
	Types	ISI marked	W1, 602	MR
	IS marking	151 marked		
6.	First – Aid Hose Reels		(1)	o IN E
	Total numbers on each floor	N/A		
	• Length of hose reel hose	NIA		0
	Nozzle diameter	N/A		
7.	Automatic fire detection and alarming	2 system		
	Type of detectors	5 System		100
	9	N/17.		
	Location of Main Panel	N/A		
	Location of Repeater Panel	NA		
	Alternate source of power	N/A		
	Hooters' Location	NA		
8.	MOEFA	NA		
9.	Public Address System	ys	mk	· M (i)
10.	Automatic Sprinkler System	V	- ( )	m S
	Basements	NA		
	• Upper Floor	NI		0
11.	• Sprinkler above false ceiling Internal Hydrants	NA	76.3	
		MI		
	Size of riser/down-comer	N/4)	4.1	
			1	

	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			
	Number of hydrants per	M1/1		
	floor	VIT		
10	• Hose Box	NA		
12.	Yard Hydrants			
	<ul> <li>Total number of hydrants</li> </ul>	N/A		
6	Hose Box	WA		
13.	Pumping Arrangements	17/		
	Ground Level			,
		-10		
	Discharge of main pump	NIA		
	➤ Head of main pump	N/A		
	> Number of main pumps	NP		
	> Jockey pump out put	NA		
	Jockey pump head	N/A		
8	> Standby Pump out put	NA		a
	Standler Develop	NIA		
	<ul><li>Standby Pump Head</li><li>Auto Staring/Manual</li></ul>	J P I		
	<ul><li>Auto Staring/Manual stopping</li></ul>	NIT	1	
0		.110		
	Pump House Access	N/H		
	Terrace level			
		NIO		
	Discharge of pump	14/2		- N
	➤ Head of the pump	N/A		
	Power supply	NA		
	<ul><li>Auto starting of pump</li></ul>	NA		e* a
14.	Captive water Storage for fire fighting	J		
	Under ground tank capacity	NA		
	> Draw of connection	A// A		·
	Fire service inlet	n// /		
	Access to tank	14.44		
		N/L)		
	<ul> <li>Overhead Tank capacity</li> </ul>	HILA		
15	Exit Signage	1101	M	0.0
16.	Provision of Lifts.	42	1	11 8
	9	f .		
	Pressurization of Lift Shaft	6//0		
		N/H		
	Pressurization of lift lobby	NIA		
8	Communication in lift Car	NIN		
		Parent		

	<ul><li>Fireman's Grounding</li><li>Switch</li><li>Lift Signage</li></ul>	N/A			~
17. 18.	Standby power supply Refuge Area	N/A	W	0	
	<ul><li>Total area</li><li>Location</li></ul>	N/A	98	MR	h
19.	Fire control room  Detector system panel	NA			0
	<ul><li>Flow Switch Panel</li><li>PA System Panel</li></ul>	NA NA			
0.	<ul> <li>▶ Batter backup</li> <li>▶ Building Floor Plans</li> <li>Special Fire Protection Systems for</li> </ul>	NA		0 3	
	Protection of special Risks, if any;	NA		0	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the shortcomings as noted at. serial numbers

Signature of the Inspecting Officer

Designation

Signature of the Inspecting Officer