GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No F 6/DFS/MS/2012/9H/2977

Dated 14/08/12

6

FIRE SAFETY CERTIFICATE

Certified that the "Classic Palace" Guest House, located at 8678, Arakashan Road, Pahar Ganj, New Delhi, comprised of Ground + Five upper floors having 12 guest rooms (Ground floor has Reception, First to Fourth floor has 03 guest rooms at each floor, Fifth floor having 02 staff rooms sealed with brick wall) was granted NOC by this department vide letter No F 6 / DFS / MS / GH /2009/ 1881 dated 26.06.2009. The premise was re-inspected by the officer concerned of this department on 07.08.2012 in the presence of Mr. Dewan found that the said Guest House have deemed complied with fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" A-I with effect from 1.14 for \$ / 12... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Chief Fire Officer Delhi Fire Service

Copy to: -

- 1. The Owner, Classic Palace" Guest House, located at 8678, Arakashan Road, Pahar Ganj, New Delhi.
- 2. The Addl. Comm. of Police (Lic) First Floor, Police Station Defence Colony, New Delhi.

Conditions for the validity of fire safety certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.
- 3. All the staff members must know the correct method operation of fire fighting system.
- 4. Any lapse rendering fire fighting system/equipment non-functional shall be risk and responsibility of the management.
- 5. This inspection report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. This NOC is for Guest Rooms only.

| | INSPECTION REPORT |
|----|---|
| 1. | . Name & address of the building: M/S Classic Palace, 8678, A-E. Road |
| 2. | Type of Occupancy : Residential (Guesthase) Type of Case : Old (Leneval) |
| 3. | . Type of Case : Old (teneral) |
| 4. | . Details of previous NOC : Letter No |
| 5. | . Fire Safety directives Letter No.: |
| 6. | Date of inspection : T/O8//2 |
| 7. | Name of the Inspecting Officer: ATOLYARY & D.S. Yadav |
| 8. | . Name and designation of Officer MR DEWAY |
| | from the building side : |
| 9. | Year of Construction : |
| 1 | 0. Applicant's letter No. : 44/33/Add/CP/Lic data DOT//L |
| | |
| T | Minimum standards on fire BBL Provided at Remarks MR (NIMAR) |
| | prevention and fire and II/P 22 Remarks MR/NMR |
| | Access of building Requirements site |
| | • Road width |
| | • Gate width |
| | • Width of internal road WA • |
| + | Number, width, Type & Arrangements of exits |
| | a. Number of staircases One One MR |
| | • Upper floors One one me |
| | • Basements b. Width of staircases |
| | • Upper floors |
| | 0.00mg 1.00mg N/E |
| | • Basements N/A |
| | c. Protection of exits • Fire check door |
| | \sim \sim \sim \sim \sim \sim |
| | Pressurization No of continuous staircase |
| | to terrace ON ON MR |
| | |

| | e. Width Of Corridor | 1.7 | | | * |
|-----|--|-----------------|---------|--------------------------------|--------|
| | - Confidor | NA | ži. | | - |
| | f. Door Size | //// | | | 6 |
| - | , | ·N/H | | | d |
| 3. | Compartmentation | | | | |
| | Fire check door | 4/10 | | 3 | |
| | | NA | | | |
| | Sealing of electrical shafts | NA | | 0 | - |
| | Time Dadi and Calaba | A CO | | | |
| | Fire Rating of shaft door | 14 | of . | | |
| | Water Curtain | NA | | | |
| | water Curtam | 1/7 | | j. | |
| | Fire Dampers | NA | | | |
| 4. | Smoke managements System | 7777 | | ū | |
| | Basements | 30 0/2 200 1 | | | |
| | | 30 a/c per hour | WA | o | |
| | Upper floors | 12 a/c per hour | h // | | |
| | | a o por nour | NA | 200 | 8 |
| 5. | Fire Extinguishers | | 1 , | | |
| | Total numbers | Ten | Ten | M A | |
| | True | | 170 | (10) | |
| | • Types | TOY | WT, Co. | m 0 | |
| | IS marking | ISI marked | 1 | 1 1014 | |
| 6. | First – Aid Hose Reels | | yes. | MR | |
| | Total numbers on each floor | | | 0 | |
| | Term numbers on each floor | Ope | 42 | mp | |
| | Length of hose reel hose | 2 / | 8 | | |
| | 10 | 30ms | ys. | me | |
| | Nozzle diameter | C m ha | 11. | 1 | |
| 7. | Automotic S | 5 mm | 1 | MR | |
| 1. | Automatic fire detection and alarming | g system | | | _ |
| | Type of detectors | AllA | | 0 | |
| | Location of Main Panel | 00/// | | | |
| | Document of Main Panel | NA | | | |
| | Location of Repeater Panel |) | | a . | |
| | Teopetici i dilei | NA | | | |
| | Alternate source of power | hIIA | | | |
| | - | 10/# | | | |
| | Hooters' Location | MAR | | | |
| 8. | MOEFA | 04/1 | | 0 | |
| 9. | Public Address System | N/1) | | ÷ | - |
| 10. | Automatic Sprinkler System | the s | 45 | MD | - |
| | Basements | 61/0 | V | | \neg |
| | • Upper Floor | A COA | | | - |
| | Sprinkler above false ceiling Internal IX. | XID | | | |
| 11. | Internal Hydrants · | 10/7) | | | |
| | Size of riser/down- comer | MIA | | | |
| | Conto | VV/T) | | | |
| | | | | and the property of the second | |

=

| | Number of hydrants per | MA | | • | |
|-----|---|-------------------|-----|-----------------|-----|
| | floor Hose Box | 4200 | | | |
| 12. | Yard Hydrants | NA | 1 | ٠ | |
| 12. | Total number of hydrants | 1// | | | |
| | Hose Box | NA | | | |
| 13. | Pumping Arrangements | NH | | | |
| • | • Ground Level | | | | |
| | Ground Dever | 100 | | | |
| ۰ | Discharge of main pump | N/A | | | 10 |
| | ➤ Head of main pump | MA | | | |
| | > Number of main pumps | MA | | | |
| 3 | Jockey pump out put | NA | | | |
| | > Jockey pump head | NA | | | |
| | > Standby Pump out put | NA | | | |
| | > Standby Pump Head | 1/10 | | | |
| | > Auto Staring/Manual | 11/11 | 1 | | |
| | stopping | WH | | | |
| | Pump House Access | $\Delta I/\Delta$ | | | |
| • | Terrace level | 10/1 | | | |
| | > Discharge of pump | 225 lpm | 45 | MR | |
| * | Head of the pump | 30 | 48 | me | 2. |
| | ➤ Power supply | 45 | ys | ML | 9 |
| 1.4 | > Auto starting of pump | ys | 45 | MR | |
| 14. | Captive water Storage for fire fightin | g / m° | 0 | | |
| | Under ground tank capacityDraw of connection | N/1+ | | 4 | . * |
| | Fire service inlet | 7/2 | | | |
| | > Access to tank | N/IT | | 0 | |
| | recess to tank | WH | | 30.00 San 45.00 | |
| | Overhead Tank capacity | 2500. | LIS | me | |
| 15 | Exit.Signage | Ye | CV. | n | |
| 16. | Provision of Lifts. | () | 7 | 11/12 | |
| • | > Pressurization of Lift Shaft | NA | | | |
| , | > Pressurization of lift lobby | N/A | | | |
| | Communication in lift Car | NA | | | |
| • | | / * / | | | |

| | Fireman's GroundingSwitchLift Signage | NA | | v | |
|------------|--|----------------------|-----|----|---|
| 17. 18. | Standby power supply | NA | | | 0 |
| 10. | Refuge Area > Total area | 4) | ys. | MR | * |
| 19. | Location Fire control room | WA | | | 4 |
| 20. | Detector system panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans Special Fire Protection Systems for Protection of special Risks, if any; | NA NA NA NA | | | 0 |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the as noted serial numbers

Signature of the Inspecting Officer

Name

Designation

Signature of the Inspecting Officer