GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No F 6/DFS/MS/2012/94/2976

Dated |4 | 08 | 12

0

FIRE SAFETY CERTIFICATE

Certified that the "Shere Punjab Inn" Guest House, located at 7877, Arakashan Road, Pahar Ganj, New Delhi, comprised of Ground + Four upper floors having 18 guest rooms (Ground floor has Reception + lobby + Office, First floor has 07 guest rooms, Second floor has 05 guest rooms, Third floor has 06 guest rooms, Fourth floor has 02 staff rooms) was granted NOC by this department vide letter No F 6 / DFS / MS / GH /2009/2009 dated 07.07.2009. The premise was re-inspected by the officer concerned of this department on 07.08.2012 in the presence of Mr. Bedi found that the said Guest House have deemed complied with fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" A-I with effect from 19.08./12. for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 1.4. 58. 1.1.2.... at New Delhi.

Chief Fire Officer
Delhi Fire Service

Copy to: -

- 1. The Owner, Shere Punjab Inn" Guest House, located at 7877, Arakashan Road, Pahar Ganj, New Delhi.
- The Addl. Comm. of Police (Lic) First Floor, Police Station Defence Colony, New Delhi.

Conditions for the validity of fire safety certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.
- 3. All the staff members must know the correct method operation of fire fighting system.
- 4. Any lapse rendering fire fighting system/equipment non-functional shall be risk and responsibility of the management.
- 5. This inspection report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. This NOC is for Guest Rooms only.

ald Cost SPh drec

0

	1	INSPECTION REPORT				
	1.	Name & address of the building:	Shere-Pur Ram	17ab 7m, Nagar,	7877, A.K.Road	
	2.	1 ,	Residential (Suesthase)		
	3.	Type of Case :	ald (Renewed			
	4.	Details of previous NOC :	Letter No Fel DF	3/AS/94/9	1009 29 Acute 7/7/09.	
	5.	Fire Safety directives Letter No.:		14		
			<u>C/8/12</u>	4		
•	7.	Name of the Inspecting Officer:	ATVLGA	eg & Disi	yadaV	
		Name and designation of Officer	MR G	4		
		from the building side				
	9. Year of Construction : Beton 2007 (AS PS verd)				by oled.)	
	9. Year of Construction 10. Applicant's letter No. 10. Applicant's letter No. 10. Applicant's letter No. 10. Applicant's letter No.					
		•			/	
S	M	linimum standards on fire	BBL	Provided at	D. I. M. D. A. D. C.	
No		revention and fire safety U/R 33	Requirements	site	Remarks MR/NMR	
1.		ccess of building	1	Site		
		 Road width 	NA	5 mb	MR	
×		• Gate width	NA			
		 Width of internal road 	AVA			
2.	N	umber, width, Type & Arrangeme	nts of exits			
		a. Number of staircases	Onl	(M)	m	
		 Upper floors 	one	Cool	m e	
		Basements	N/A		7.5.2	
		b. Width of staircases	19/11		,	
		 Upper floors 	0.00ms	1.ovat	MR	
		• Basements	N/A			
		c. Protection of exits				
		• Fire check door	NA			
		Pressurizationd. No of continuous staircase	WA			
		to terrace	and	One	MR	

	e. Width Of Corridor		×		
	c. Width Of Corridor	NA			
	f. Door Size	111			
		I N/A		0	
3.	Compartmentation				
	• Fire check door	-1/-			
		N/A		•	
	 Sealing of electrical shafts 	NIA		9	
		1971	,		
	 Fire Rating of shaft door 	NA			
	W. C.	11.00			
	Water Curtain	NA			
	e Fire D	LVN		0	
4.	• Fire Dampers	MA		*	
1.	Smoke managements System				
	• Basements	30 a/c per hour	N/c A		
	• Unnou flague	10 /	TY A	,	
	• Upper floors	12 a/c per hour	WA		
5.	Fire Extinguishers		, , , ,		
	Total numbers	10	70.00		
		10	760	. MR	
	• Types		107 Ca DO		
		ISI marked	WT, Co-, D(1)	mr	
-	 IS marking 		UL	m O ·	
6.	First – Aid Hose Reels			111 2	
	 Total numbers on each floor 	000 0		5	
		Direc	45	MR	
	 Length of hose reel hose 	30 mt	(M	1.0	
	- N. I. I.		1	MR	
	Nozzle diameter	5 mm	LK	JO R	
7.	Automatic fire detection and alarmin			0.01	
	7. Automatic fire detection and alarming system • Type of detectors				
	71 = = B00000015	NA			
	 Location of Main Panel 	1 / 1 /			
		N/A		19	
	 Location of Repeater Panel 	bl ca			
		11/17)			
	 Alternate source of power 	NIM			
		1°/. M		0	
	 Hooters' Location 	NA)			
8.	MOEFA	A I an			
9.	Public Address System Tatican	11/4)	NA	o	
10.	Automatic Sprinkler System	دلاء	45	MR	
	• Basements	A) (A			
	Upper Floor	NA PARTIES		5	
	Sprinkler above false ceiling	NA			
11.	Internal Hydrants	141,			
	 Size of riser/down-comer 	M/A *		9	
		14/1		1 (2)	

	• Number of hydrants per	NA		
	floor	100		•
12.	Hose Box Varid Hadrage	NA		
12.	Yard Hydrants	h lab		
	Total number of hydrants Hara Parallel	NA		
13.	Hose Box	MA	×	
13.	Pumping Arrangements • Ground Level	1140	E	
	• Ground Level	N/1+		
	Discharge of main pump	NA	y .	
	➤ Head of main pump	N/h		
	Number of main pumps	MA		
,	Jockey pump out put	NA		
e e	Jockey pump head	NA		
	Standby Pump out put	MA		
	Standby Pump Head	NA		6
	> Auto Staring/Manual	10/1		
	stopping	NA	a a	e e
		al ch		
	Pump House Access	11/17	8 *	
Jt.	Terrace level			
٥	Discharge of pump	225 lpm	ys	m e
	➤ Head of the pump	30	yes	MR
	> Power supply	ys	45	mr
1.4	> Auto starting of pump	ys	y	me
14.	Captive water Storage for fire fighting) //A	•	
	Under ground tank capacityDraw of connection	N/H		1
	Fire service inlet	Mt1°		
	Access to tank	NA		
	· · · · · · · · · · · · · · · · · · ·	NH		
	Overhead Tank capacity	2500	ys	mn
15	Exit Signage	Un	Cu	han
16.	Provision of Lifts.	4 >	-15	INK
	•			
	Pressurization of Lift Shaft	NIA		
۰	Dungan i i a a a a a a			
	Pressurization of lift lobby	NA		
	Communication in lift Car	NIA		
		/ /-		

	Fireman's Grounding Switch	NA			
	Lift Signage	NIM			
17.	Standby power supply	NA		-	
18.	Refuge Area	45	45	MP	
	Total area	1.176			
0	Location	N/A			À
9.	Fire control room	1417			
	Detector system panel	N/A		6	
	Flow Switch Panel	20			
	PA System Panel	MA			
-	Batter backup	DA			
5.	Special Fire P. A. Single Plans	NA			
	Special Fire Protection Systems for	NIN			
-	Protection of special Risks, if any;	11/1			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the shortcomings as noted serial numbers

Signature of the Inspecting Officer

Name

Designation

Signature of the Inspecting Officer

Name J. S. yadar.

Designation ADo(e:c)