GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO.F6/DFS/MS/GH/2012/ 3004

Dated: 17/8//2

FIRE SAFETY CERTIFICATE

Certified that M/s Hotel Sai Palace Dx, located at 3790, Tel Mandi, Paharganj, New Delhi comprised of ground floor(01 guest rooms + reception + 01 store), first floor (04 guest rooms), second floor (04 guest rooms), third floor (04 guest rooms) and terrace floor (03 guest rooms) was granted NOC by this department vide letter No. F.6/DFS/MS/GH/09/1783 dated 16-06-2009. The premises was re-inspected by the officer concerned of this department on 01-08-2012 in the presence of Mr. Dutta, Manager of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class residential (guest house) with effect from 1717/12 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules,2010.

Issued on 17/8//2 at New Delhi by.

Chief Fire Officer Delhi fire service

Copy to: -

1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

2. The Manager, M/s Hotel Sai Palace Dx, 3790, Tel Mandi, Paharganj, New Delhi

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT 1. Name & address of the building: M/s Hole Sai palace Dx, 3790, Tel Mande 2. Type of Occupancy : Lodging House / Eating House / Club Pahar Gany, Ten peller 3. Type of Case : Renewal / New case 4. Details of previous NOC : Letter No. F6 DFs MS/GH 05 1783 Dated: 166 2005 5. Fire Safety directives letter No : : 01/08/2012 6. Date of inspection 7. Name of the Inspecting Officers: M.K.Chattopadhyay, ADO(HQ) 8. Name and designation of officers : Mr. Dutta, Managu : 1988 : 20433/ Addl. C.P/Lrc(H) daled 2014/12 from the building side 9. Year of Construction 10. Applicant's letter No. S. Minimum Standards on fire NBC Provided at site Remarks No. prevention and fire safety U/R 33 Requirement MR/NMR 1 Access to building 1 tw 80 MR Road width Directly accessible Gate width MR Width of internal road N/A N/A 2 Number, Width, Type & Arrangement of Exits a. Number of staircases 01 M R being old 01 Upper Floors MA MA Basements b. Width of staircases Upper Floors 1.15-1.31-MR 0.90ml Basements MA c. Protection of exits Fire check door N/A N/A Pressurization N/A N/A e. No. of continuous staircases to terrace 01 01 MR g. Width of Corridor N/A N/A h. Door Size N/A N/A N/A N/A 3 Compartmentation. Not required MY

the second

	Fire check door	N/A	N/A			
	 Sealing of electrical shafts 	N/A	N/A			
	Fire Rating of shaft door	N/A	N/A			
	Water Curtain	N/A	N/A			
	• Fire Dampers	N/A	N/A			
4	Smoke Management System.					
	Basements	30 a/c per hour	N/A	N/A		
	Upper floors	12 a/c per hour				
			N/A	N/A		
5	Fire Extinguishers					
	Total numbers 10	Walter Co2-5	provided	ur		
	• Types water Co, CO2	CO2 - 5	Provided	MR		
	IS marking	ISI marked	provides	m p_		
6	First-Aid Hose Reels.					
	Total numbers on each floor	01	provided	MR		
communicación construción de constru	Length of hose reel hose	30 m	provided	Me		
	Nozzle diameter	5 mm	provided	MR		
7	Automatic fire detection and alarming system.					
A martin and a second a second and a second and a second and a second and a second	Type of detectors	N/A	N/A	20 mar and and had not not not not one one		
	Location of Main Panel	N/A	N/A			
	Location of Repeater Panel	N/A	N/A			
Omitor monatchini diadi (non) di hi assado	Alternate source of power	N/A	N/A			
	Hooters' Location	N/A	N/A			
8	MOEFA	MA	MA			
9	Public Address System.	Reguired	provided	MR		
10	Automatic Sprinkler System.					
man is a plant of the control of the	• Basement	MA	MA	~~ ~		
	Upper Floor Sprinkler shows folgo sailing	N/A	N/A			
	Sprinkler above false ceiling	N/A	N/A	370 MA MA SEC SEC SEC SEC MA MA MA MA MA		
11	Internal Hydrants					
	Size of riser/down-comer	N/A	N/A			



	 Number of hydrants per floor 	N/A	N/A				
	Hose Box	N/A	N/A				
12	Yard Hydrants.						
	 Total number of hydrants 	N/A	N/A				
	Hose Box	N/A	N/A				
13	Pumping Arrangements.						
	 Ground Level 	N/A	N/A	50° 60° 60° 60° 60° 50° 50° 50° 50° 50° 50° 50°			
	Discharge of main Pump	N/A	N/A				
	Head of Main pump	N/A	N/A				
	Number of main pumps	N/A	N/A				
	Jockey Pump out put	N/A	N/A				
	Jockey pump head	N/A	N/A				
	Standby Pump out put	N/A	N/A				
	Standby Pump Head	N/A	N/A				
	Auto Starting/ Manual	N/A	N/A				
	stopping Pump House Access	MA	MA	***			
	Terrace level	~ 6 6	* * * * * * * * * * * * * * * * * * * *				
	Discharge of pump	225 LPM	ms Lpin	MR			
8	► Head of the pump	Smr	25 ont	MR			
	Power Supply	_	Clarks Colle				
	Auto Starting of pump		Startery Switch	MR			
14	Captive Water Storage for fire fightin	g.		* 2			
c	 Underground tank capacity 	N/A	N/A	NO. 200 July 100 100 100 101 101 102 103 105 105			
	Draw-off connection	N/A	N/A				
	Fire service inlet	N/A	N/A				
	Access to tank	N/A	N/A				
	 Overhead Tank capacity 	2500 lh	2500 13	MR			
15	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.						
	 Pressurization of Lift Shaft 	N/A	N/A	~ ~ ~ ~ ~ ~ ~			
	Pressurization of Lift lobby	N/A	N/A				

	Communication In lift Car	N/A	N/A	
	Fireman's Grounding Switch	N/A	N/A	b
	Lift Signage	N/A	N/A	
17	Standby power supply	MA	N 4	
18	Refuge Area.			
	> Total Area	N/A	N/A	
	> Location	N/A	N/A	
19	Fire Control Room			
	Detector System Panel	N/A	N/A	
	• Flow Switch Panel	N/A	N/A	
	PA System Panel	N/A	N/A	
	Batter backup	N/A	N/A	
	Building Floor Plans	N/A	N/A	
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	Ol ABC lybe fire extensusher provided hear gled- panel.	MR_

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to /grant / renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer Name

Designation

Signature of the Inspecting Officer Name (M.K. CHATTOPADHYAY) Designation: - Assistant Divisional Officer