GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DF5/MS/Schore/2012/2995

Dated: 17/8/20/2

FIRE SAFETY CERTIFICATE

To,

The Principal
M.C.Primary Girls School
D-4,Nand Nagri,Delhi-93.

Copy:-

 The Director of Education MCD,Nigam Bhawan, Kashmiri Gate,Delhi.

 The Principal M.C.Primary Boys School D-4,Nand Nagri,Delhi-93. Chief Fire Officer Delhi Fire Service

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: MC Primary School at D-4, Nand Nagri, Delhi -93.

2. Building is comprised of

: Ground +1, upper floor.

3. Type of Occupancy

: Educational

4. Type of Case

: New Case

5. Details of Previous NOC letter :Nil

6. Fire Safety direction letter No : Circular Director of Education dated 1.3..11

7. Date of Inspection

: 2707.12

8. Name of the Inspecting officers:

DO Virendra Singh

9. Name and designation of Officer:

from the building side

: Smt.Santosh (Principal).

10. Year of Construction

-: 2006

11. Applicant's letter No

: letter No.Nil dated 24.04.2012.

NO.	Minimum Standards on fire prevention and fire safety U/R33	Circular Requirement	Provided at Site	Remarks		
1	Access to building	requirement	Joho			
•	Road width		06 Mtrs.	MR		
	Gate width					
	Width of internal road					
2	Number, Width, Type and Arrangement of Exits					
	a. Number of Staircases	02 Nos.	02 Nos.	MR		
	Upper Floor	02 Nos	02 Nos.	MR		
	Basement					
	B. Width of Staircases	6				
		1.5 M	1.5 M	MR		
	Upper Floor	1.5 M	1.5 M	MR		
	 Basement 			1 7 5		
	c. Protection of exits					
	 Fire check door Pressurization No. of continuous staircases to terrace g. Width of Corridor 					
			1No.	MR		
		1.5 mts.	1.5 mts	MR		
	h. Door Size	1.0 Mtrs	1.0 Mtrs	MR		
3	Compartmentation.			21		
	Fire check door			W 100 100 100 100 100 100 100 100 100		
	 Sealing of electrical shafts 			100 Mile 100 Mile 100 Mile 100 Mile 100 Mile		
	Fire rating of shaft door					
	Water curtain					
	Fire Dampers					
4	Smoke Management System.			N.		
	Basement					

	Upper floor					
5.	Fire Extinguishers					
.	Total numbers	5 Nos.	5 Nos.	MR		
	types	ABC & Co2	Provided	MR		
	IS marking	ISI marked	Prrovided	MR		
6	First-aid-Hose Reels.	101 Illaineu	FITOVIded	IVIIX		
0	Total numbers of each floor	T	T			
		9				
	Length of hose reel hoseNozzle diameter		-			
7	Automatic fire detection and alarming system.					
		T				
	Type of detectors					
	 Location of main panel 	other value value value value value dans dans dans dans dans dans dans dans		allow state allow state and a		
			MAN SIGN SIGN SIGN SIGN SIGN SIGN SIGN SIG			
	 Location of repeater panel 					
		2)				
	 Alternate source of power 					
	Hooter's location					
8	MOEFA					
9	Public address System.					
10	Automatic Sprinkler System.					
	Basement					
	upper floor					
	sprinkler above false ceiling					
11	Internal Hydrants					
	size of riser/down-comer					
	Number of hydrants per floor					
	Hose Box			T		
	Tiose Box			3		
12	Yard Hydrants.		2	i		
14	Total number of hydrants			200 100 100 100 100 100 100 100 100 100		
	Hose Box			-		
13						
13	Pumping Arrangements.					
	Ground Level Discharge of main Dump	1				
	Discharge of main Pump Head of Main Pump					
	➤ Head of Main Pump					
	Number of main pumps					
	> Jockey pump out put					
	> Jockey pump head					
	> Standby pump out put					
	> Standby pump Head					
	Auto Starting /Manual		No. (10 all 10 a			
	stopping					
	Pump House Access					
	Terrace Level					
	Discharge of pump					

	Head of the Pump			
	Power supply			
	4 1		И	e set
	Auto Starting of pump		1,2	
			· F	33
14	Captive Water Storage for Fire	8	8 8 5 \$ * Y	
	Fighting.			
	 Underground tank capacity 			
	Draw-off connection			
	Fire service inlet			
	Access to tank			
	 Overhead Tank capacity 		=	
15	Exit Signage.	MAN TOO TOO TOO TOO TOO TOO TOO TOO TOO TO		Main Sale Sale Sale Sale Sale Sale Sale Sale
16	Provision of Lifts.			
	 Pressurization of Lift Shaft 			
	 Pressurization of Lift lobby 	NAME AND THAT THE THAT THE THAT THE THAT THE THAT	NOT THE THE THE THE THE THE THE THE THE TH	
	Communication in lift car			NAME AND ADDRESS OFFI COST STORE STORE STORE STORE STORE
	 Firemen's grounding switch 			Mape state state state state state state state state state
	Lift Signage			
17	Standby power supply			
18	Refuge Area.			
Bo.	Total area			
	 Location 			20 00 00 00 00 00 00 00 00 00 00
19	Fire Control Room			
	Detector system panel			
	Flow switch panel			
	PA system panel			
	Battery backup			
	 Building Floor Plans 			
20	Special Fire Protection systems for	NO CON CON CON CON CON CON CON CON CON C		
	protection of special Risks, if any:			

The fire extinguhers provided in the building were tested/checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer

Name VIRENDRA SINGH

Designation Do(E)

N.C.FO