## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No F 6/DFS/MS/2012/Gn/ 2989

Dated

17/8/12

## FIRE SAFETY CERTIFICATE

Issued on 17/8/12 at New Delhi.

Chief Fire Officer Delhi Fire Service

## Copy to: -

- 1. The Owner, Shivish International" Guest House, located at 7875, Arakashan Road, Pahar Ganj, New Delhi.
- 2. The Addl. Comm. of Police (Lic) First Floor, Police Station Defence Colony, New Delhi.

Conditions for the validity of fire safety certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.
- 3. All the staff members must know the correct method operation of fire fighting system.
- 4. Any lapse rendering fire fighting system/equipment non-functional shall be risk and responsibility of the management.
- 5. This inspection report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. This NOC is for Guest Rooms only.

Old Cost SPI Cost

¥		LINE	PECTION REPO	JRT		
	1.	Name & address of the building:		Interna	abional 7075,	
		<b>o</b> ,	A. Roas	1 New	Ache	
	2.	Type of Occupancy : 7	Residential L	Gushoss		
	3.	Type of Case :-	Reneral ( ol	d(ar)		6
	4.	Details of previous NOC : I	Letter No FG/08	1/AS/GH/S	2009/2232 La	La 2010119
	5.	Fire Safety directives Letter No.:-	N/A	(, -(, , , , )		
0	6.	Date of inspection :-	1/08//2	, ,		
	7.	Name of the Inspecting Officer:	ATULGAR	2 6 05-ya	rdu)	* ************************************
	8.	Name and designation of Officer	DAVENdra	Yshel		3 9
		from the building side	:0		1 ( ~ 1)	
٩	9.	Year of Construction :-	12/0x 200	D ( A8	pro our	
	10	Applicant's letter No.	NL date	1 6/8/15		
		v	ò			
<u>S</u>	I	Airing A 1 1	·			
o No	1	Minimum standards on fire	BBL	Provided at	Remarks MR/NMR	
1.	P	revention and fire safety U/R 33	Requirements	site		
1.	F	access of building				
		• Road width	NA	5 mg	MR	
		• Gate width •	N/A.			
0		<ul> <li>Width of internal road</li> </ul>	NIA			
2.	N	lumber, width, Type & Arrangemen	ats of ovits			·
		a. Number of staircases	Cont	000		
	-		010	are	MR	
		<ul> <li>Upper floors</li> </ul>	Ope	one	MR	
		• Basements	one	one	MR	
		b. Width of staircases		/	and the same of th	
<b>e</b>		• Upper floors	O donne	comp	22R	
		• Basements	0.0 mb	ar Pays	PM2	
		c. Protection of exits			•	
		• Fire check door	NA			
		<ul> <li>Pressurization</li> <li>d. No of continuous staircase</li> </ul>	NIA	1		
		d. No of continuous staircase to terrace	Mm P	200	2 2	
	1	Sec. 18		ane	m p	

				, w.	
	e. Width Of Corridor	NA			
	f. Door Size	WIA		6	
3.	Compartmentation	1.77		- u	
2	• Fire check door	1160	9	4	
		MH		2 1 *	
	<ul> <li>Sealing of electrical shafts</li> </ul>	NA			
	<ul> <li>Fire Rating of shaft door</li> </ul>	NA	3		
	Water Curtain	NA		di e	
	• Fire Dampers	NA	x =		
4.	Smoke managements System	7 7 7		u	
· ·	Basements	20 0/0 1		D 0	
	- Dascincitis	30 a/c per hour	NA	p ,	
	<ul> <li>Upper floors</li> </ul>	12 a/c per hour	WA		
5.	Fire Extinguishers		- ///		
	Total numbers	. 10	Tem		
		10	Ten	ml	
	• Typės	ISI marked	WT, COXDIP	. MR	
	<ul> <li>IS marking</li> </ul>		ys	42/ma	
6.	First – Aid Hose Reels		- 0 -	PSIMIL	
	Total numbers on each floor	BORNIA.	N/A	0	
7	<ul> <li>Length of hose reel hose</li> </ul>	WA	WA		
1	Nozzle diameter	NA	NIA		
7.	Automatic fire detection and alarming system				
	• Type of detectors	1 1/10			
		N/I+		- - ×	
	<ul> <li>Location of Main Panel</li> </ul>	NA			
	<ul> <li>Location of Repeater Panel</li> </ul>	N/A		<b>b</b>	
	<ul> <li>Alternate source of power</li> </ul>	NA			
	<ul> <li>Hooters' Location</li> </ul>	NIA		0	
8.	MOEFA	MA			
9.	Public Address System / Tale Xer	yes	42	m 0	
10.	Automatic Sprinkler System	q	8)	mrz.	
	<ul> <li>Basements</li> </ul>	YES	YES	m R	
	<ul><li>Upper Floor</li></ul>	MA	12)	//I Kananasa	
11	Sprinkler above false ceiling	NA			
11.	Internal Hydrants				
	<ul> <li>Size of riser/down- comer</li> </ul>	NB			

M/s Shiysh International, 7075, A-K-Road.

	Number of hydrants per	1		
	floor .	NA		*
12.	Hose Box	NH		
12.	Yard Hydrants			
	<ul><li>Total number of hydrants</li></ul>	NA	8	• 2
	<ul> <li>Hose Box</li> </ul>	NA		
13.	Pumping Arrangements			
	<ul> <li>Ground Level</li> </ul>	3		
	• Discharge of main pump	NA	-	•
*	➤ Head of main pump	N/A	-	
25	> Number of main pumps	WA		
2	> Jockey pump out put	N/A		
	> Jockey pump head	N/A·		
	> Standby Pump out put	W/H		
	Standby Pump Head	NIA		
	➤ Auto Staring/Manual  stopping	MA		
	D. D	NIM		
•	<ul><li>Pump House Access</li><li>Terrace level</li></ul>	1 1 1		
	Discharge of pump	225/pm	45	MR
	➤ Head of the pump	30 m	ys -	mR
9	> Power supply	yes	45	mR
	> Auto starting of pump	ys 1	95	mR
14.	Captive water Storage for fire fighting	7		
	<ul> <li>Under ground tank capacity</li> </ul>	N/A		
8	Draw of connection	N/A		
	Fire service inlet	NA		0
	Access to tank	NA		
	- 0-1-17-1	9	200	1800
15	Overhead Tank capacity  Evit Signage	2500	2500	TIK
$\frac{15}{16}$ .	Exit Signage .  Provision of Lifts.	45 .	45	MR
10.	I TOVISION OF LITTS.	1		
•	<ul><li>Pressurization of Lift Shaft</li></ul>	NA		
	<ul> <li>Pressurization of lift lobby</li> </ul>	NA		
	Communication in lift Car	MA		

	<ul><li>Fireman's Grounding</li><li>Switch</li><li>Lift Signage</li></ul>	NA		v	
17. 18.	Standby power supply Refuge Area	N/A Yes	Lp Lp	m o	6
19.	➤ Total area ➤ Location  Fire control room	NA NA		11 2	
	<ul> <li>Detector system panel</li> <li>Flow Switch Panel</li> <li>PA System Panel</li> <li>Batter backup</li> </ul>	WA WA		8	
20.	➤ Building Floor Plans  Special Fire Protection Systems for Protection of special Risks, if any;	NA		•	0
	The fire protection systems are	17/4			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the shortcomings as noted serial numbers

Signature of the Inspect

Name

Signature of the inspecting Officer

Designation

Designation