GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No F 6/DFS/MS/2012/ Cn/2990

Dated 17/8/12

FIRE SAFETY CERTIFICATE

Certified that the "Suzi International" Guest House, located at 8483, Arya Nagar, Pahar Ganj, New Delhi, comprised of Ground + Four upper floors having 25 guest rooms (Ground floor has Reception + 01 guest room + 01 office, First to Fourth floor has 06 guest rooms at each floor) was granted NOC by this department vide letter No F 6 / DFS / MS / GH /2009/ 2516 dated 13.08.2009. The premise was re-inspected by the officer concerned of this department on 03.08.2012 in the presence of Mr. Gulshan found that the said Guest House have deemed complied with fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential" A-I with effect from ...1718/12... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Chief Fire Officer Delhi Fire Service

Copy to: -

- 1. The Owner, Suzi International" Guest House, located at 8483, Arya Nagar, Pahar Ganj, New Delhi.
- 2. The Addl. Comm. of Police (Lic) First Floor, Police Station Defence Colony, New Delhi.

Conditions for the validity of fire safety certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire protection measures shall be maintained in perfect working conditions all the times as seen during inspection.
- 3. All the staff members must know the correct method operation of fire fighting system.
- 4. Any lapse rendering fire fighting system/equipment non-functional shall be risk and responsibility of the management.
- 5. This inspection report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. This NOC is for Guest Rooms only.

SP/ green

3	3. Type of Case :	old (Kene	val		
٥ ۷	4. Details of previous NOC : L	etter No FG D	PS/MS/GH	1/204/2516	
4	5. Fire Safety directives Letter No.: ————————————————————————————————————				
İ	6. Date of inspection $\frac{300012}{100012}$				
	Name of the Inspecting Officer: A7ULGARSE DS Jedan				
	V				
	8. Name and designation of Officer from the building side 9. Year of Construction Sefor 2001				
, ,					
				dates 25/06/12	
	10. Applicant's letter No. :	75 13 1700	14011	1 0 (acc. 2) (cs//2	
-	0	-			
S No	Minimum standards on fire prevention and fire safety U/R 33	BBL Requirements	Provided at site	Remarks MR/NMR	
1.	Access of building	1	Ditte.		
	• Road width	N/A	Ant	M D	
	• Gate width	NA	, ,		
	Width of internal road	N/A			
2.	Number, width, Type & Arrangemen	its of exits			
	a. Number of staircases	Oral	one	MR	
٠	 Upper floors 	one	one	mr	
	• Basements	N/A		,	
	b. Width of staircases		0		
	 Upper floors 	0.8 mts	1:20A\$	MR	
**	• Basements	NA			
9	c. Protection of exits				
	 Fire check door 	NIA			
*	D	10/4			
	Pressurizationd. No of continuous staircase	NA			
	to terrace	orol	000	mR	

INSPECTION REPORT

1. Name & address of the building:

2. Type of Occupancy

M/s SVZI International, 8409, A- E. Lour

				,
	e. Width Of Corridor	N/A		Q (2)
	f. Door Size	14/7		
2		NA		
3.	Compartmentation			
	 Fire check door 			
		I NA		
	 Sealing of electrical shafts 	NA		·*
		441		
	• Fire Rating of shaft door	07/-		o
	Water Curtain	N/A		
	Fire Dampers	N/A		9
4.	Smoke managements System	1.///		
	Basements	30 0/0 === 1		
		30 a/c per hour	N/A	/6
	 Upper floors 	12 a/c per hour	1 1///	
-		e por notin	NIA	
5.	Fire Extinguishers	70	1 // 1	0
	 Total numbers 	16	Ten	ma
	9	10	1-011	MR
	Types		WT, Pos. OIP	In O
		ISI marked	1 (00)	MR
	 IS marking 		UK	1200
6.	First – Aid Hose Reels			9111
	 Total numbers on each floor 			V
		one	ye	MP
	 Length of hose reel hose 	anm	1/4	M O
		3011	7)	
	Nozzle diameter	5 m	(10	
7.	Automatic fire detection and alarming	3 /6/		MK
	Type of detection and alarming	g system	V	
	Type of detectors	NI/A		
	• Location of M.: D	14/17		N (N)
	Location of Main Panel	1/0		
	Location of Reporter Paral	10/17		4
	Location of Repeater Panel	n) (A		0
	Alternata consum C	1 1 1		
	Alternate source of power	N/A		
	Hooters' Location	(1/1)		
Q		N/ #1		
8.	MOEFA			
9.	Public Address System Calcole	45	42	mo
10.	Automatic Sprinkler System			mQ
	• Basements	NA		
	 Upper Floor 	NA		9
	Sprinkler above false ceiling	NA		
11.	Internal Hydrants	7 / 1		
	Size of riser/down- comer	N/A		0

M/s Soz / Internation, 8483, A. R. Ren

	Number of hydrants per	0//0		
	floor	11/1+		
•	Hose Box ,	MA		
12.	Yard Hydrants			
	 Total number of hydrants 	NA	3	
	Hose Box	KTA		
13.	Pumping Arrangements	111		
	 Ground Level 	(8		
	Discharge of main pump	NA		
	Head of main pump	MA.		
	➤ Number of main pumps	N/A		
	Jockey pump out put	NA		,
	Jockey pump head	NA	eš	
	Standby Pump out put	NA		
۰	Standby Pump Head	NA		
	> Auto Staring/Manual	/ /)		
	stopping	N/A		
	118	/ / /		
	Pump House Access			
	 Terrace level 	п		
	Discharge of pump	2234pm	ys	me
37	> Head of the pump	30 mg	ys	MR
	Power supply	ys	Kogie	me
1.4	> Auto starting of pump	ys	48	MR
14.	Captive water Storage for fire fighting	7	V	
	Under ground tank capacity	NA		8
	Draw of connection	NA		
	Fire service inlet Access to tank	NITI		
	Access to tank	NA		
	Overhead Tank capacity	2500	US	m D
15	Exit Signage	(1)	A Common of the	MR
16.	Provision of Lifts.	7)		MR
	9	~		
	Pressurization of Lift Shaft	N/A		
	Pressurization of lift lobby	N/A		
	Communication in lift Car	N/A.		
		-		

17. Standby power supply 18. Refuge Area Total area MA		Fireman's GroundingSwitchLift Signage	NA			
Fire control room Detector system panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans 20. Special Fire Protection Systems for Protection of special Risks, if any;		Standby power supply	MA	Ch.		
Detector system panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans 20. Special Fire Protection Systems for Protection of special Risks, if any;		Total areaLocation	N/A N/A	0	mR.	ò
	20.	 Detector system panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans Special Fire Protection Systems for	N/A N/A N/A N/A		9	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the shortcomings as noted serial numbers

Signature of the Inspecting Officer

Name J. S. yadav

Designation

Designation AD. (C.D)

Signature of the Inspecting Officer