GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, CONNAUGHT PLACE, NEW DELHI-110001

No. F6/MS/DFS/GH/2012/ 3 0 99

Dated: 27/08/12

FIRE SAFETY CERTIFICATE

Issued 27./.08/12.. at New Delhi by.

CHIEF FIRE OFFICER
DELHLFIRE SERVICE

Copy to :-

1. The Addl. Commissioner of Police (Lic.), First Floor, P.S. Defence Colony, New Delhi – 110049: wrt...19954/Addl.CP/Lic.(H) dated 19.4.2012

2. M/s Ashwani Lodge Guest House, 8696-99, D.B.G. Road, Pahar Ganj, New Delhi- 110055

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

INSPECTION REPORT

Type of Case 4. Details of previous NOC : Letter No 5. Fire Safety directives letter No 6. Date of inspection 7. Name of the Inspecting Officers 8. Name and designation of officers from the building side 9. Year of Construction	rse/Renewal ~ No. F6/DFs/ms/GH N.A 7-08-2012 h, D. S. Yaa Ashwani 1983 Stas	1/2009/1830 Dated hv (A.D.O.) Gupta (O	23-06-2009 voner)
Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	old care
Access to building	The second secon		pss me
 Road width 	_ N_A -	More then 18 mass	mR
• Gate width	NA	NA	NA
 Width of internal road 	MA	NA	INA
Number, Width, Type & Arrangement of	of Exits		
a. Number of staircases			
 Upper Floors 	01	01	MR
• Basements	· 80 mts	· 80 Mts	M-R V
b. Width of staircases			
• Upper Floors	80 Cms	135 Cms.	MR
* Basements	80 cmg	80 CM8	M.R
c. Protection of exits			
• Fire check door	. MA	MA	NA
Pressurization	NA	NA	NA
e. No. of continuous staircases to terrace	01	01	MR
g. Width of Corridor	NA	NA	NA
h. Deor Size	NA	NA	MA

1	Compartmentation.			
TANK SAME	• Fire check door	MA.		
	 Sealing of electrical shafts 	MA		
- And the company	• Fire Rating of shaft door	NA	1	_
	Water Curtain	NA		
	 Fire Dampors 	HA		_
	Smoke Management System.	<u> </u>		name, a name med monothermonic militar and make all accommon and assume and
-	• Basements	30 a/c per hour	Exhaust fang Natural ventilation	M.R
	 Upper floors 	12 a/c per hour	Natural ventilation	M-R
		2 4		
	Fire Extinguishers			A
1	 Total numbers 	12	12	mR
The same and	Types	~~~	Water Coza A.B.C	nk
	• IS marking	ISI marked	Poovided	MR
	First-Aid Hose Reels.			
	 Total numbers on each floor 	one	one	MR
	 Length of hose reel hose 	30 m	Provided	
İ	Nozzle diameter	5 mm	Brovided	MR
7	Automatic fire detection and alarming	system.		3
	• Type of detectors	MA	_	
	• Location of Main Panel	NA		
	• Location of Repeater Panel	KNA		
	Alternate source of power	NA		2
	Hooters' Location	MA		
8	MOEKA	Yes	Provided	MR
9	Public Address System.	Yes	Provided	mR
10	Automatic Sprinkler System.			
entreum sec et e	* Basement	Yes	Provided	MR

Ashwani Lodge Grest House, 8696-99, B.B.G. Road, Pahar Ganj, New Delhi

		-			
	Upper FloorSprinkler above false ceiling	MA		0 10.00	
	The strategy department of the strategy departme	MA		5 24	
11	Internal Hydrants				*
and the second	 Size of riser/down-comer 				
4	 Number of hydrants per floor 	NA			
Market Springer	• Hose Box	NA			ı
1.3		NA			
1	Vard Hydrauts.		-		
	Total number of hydrants	NA			
13	* Hose Box	NA			
1	Pumping Arrangements.	3			
1	* Ground Level	NA			
	Discharge of main Pump	MA	-11		
	> Head of Main pump	MA			
	Number of main pumps	NA			
and	> Jockey Pump out put		,		
	> Jockey pump head	MA	-	_	
	> Standby Pump out put	MA			
	Standby Pump Head	MA			
	> Auto Starting/ Manual	MA			
	stopping	MA		97	
			,		
	Pump House AccessTerra e level	XM		-	1
	E ischarge of pump	225 LPM,	225 LPM.	mR	1
	· P Head of the pump	30 Mtrs.	30 Mhs.	mRain	yr.
	➢ Power Supply	Electric	Electore	me II	
-	> Auto Starting of pump	And the same of th	Switch Provided	mp	eri!
14	Captive Water Storage for fire fighting.		at G.F.	///	THE RESIDENCE PROPERTY.
	 Underground tank capacity 	MA		to the temperature accommend as assume that the statement was to	18. Publish
	Draw-off connection	MA			
	the state of the s			29 0.0000	4

contd:

Ashwani Lodge, 8696-99, D.B.G. Royd, Pahar Ganj, New Delhi

			e e g9 ³		
	Fire service inlet	NA		~	
	Access to tank	NA	•	\sim	
	 Overhead Tank capacity 	5000 Ctos.	Sooo Cops.	mR	
15	Exit Signage.	Yes	Provided	M	
16	Provision of Lists.				
	* Pressurization of Lift Shaft	MA		_	
	 Pressurization of Lift lobby 	MA	- 68		
***	* Communication In lift Car	MA	44		
	Fireman's Grounding Switch	MA			
	 Lift Signage 	MA			
17	Standby power supply	Yes	D.G. Set	mR	
18	Refuge Area.				
	> Total Area	NA			
100	> Location	NA			
10	Fire Control Room	9 9 9 9			
a manufacture state of the stat	Detector System Panel	NA			
	* Flow Switch Panel	MA		-	
and the second	PAi System Panel	HA			
	Batter backup	MA			
-	Building Floor Plans	MA			
20	Special Fire Protection Systems for Protection of special Risks, if any:	MA		_	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Conta.

Ashweins lodge Guest House, 8696-99, D.B.G. Road Pahar Ganj, New Delli-110055 Signature of the Inspecting Officer Signature of the Inspecting Officer Name Therm vie singh yalow Name

Designation

Desig

1/2) 21/81/12