## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO.F6/DFS/MS/EH/2012/3049

Dated: 22/08/12

0

## FIRE SAFETY CERTIFICATE

Issued on 22/58/12 at New Delhi by.

Chief Fire Officer Delhi fire service

Copy to: -

- 1. The Dy. Health Officer, MCD, Central Zone, Lajpat Nagar, New Delhi
- 2. The Manager, M/s Dunkin Donuts (A unit of Jubilant Foods Works ltd.), N-6, Connaught Circus, New Delhi

## Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

	INSPEC	TION REPORT		
<b>&gt;</b> .				
1	. Name & address of the building:	Dunkin Donuls	, N-6, Connaugh	f circus, Ten
2	. Type of Occupancy : Lodgin	ig house Restaur	ant I	
3	. Type of Case : New C	Case/ Renewal		
4	. Details of previous NOC : Letter	No. FG DES ME 16	=14 /2008 1453 Date	d: 25/5/2009
5	. Fire Safety directives letter No :		( wim pl	y Ristaurant)
	. Date of inspection :	06 08 2012		4
7	. Name of the Inspecting Officers :	M. K. Chattop	adhyay	
8	. Name and designation of officers		0 *	
	from the building side :	Mr. Sumi	t, Manager	- "
9	. Year of Construction :	Before 1947	7	
1(	). Applicant's letter No. : 🖰	014/0/1249/	CS1(UC)/SI-I	daled 20/6/12
S.	Minimum Standards on fire	NBC	Provided at site	Remarks
No.	prevention and fire safety $U/R\ 33$	Requirement		MR/NMR
1	Access to building			
	Road width	Obmir	romer.	MR
	• Gate width	•	Directly accomble	MR
	Width of internal road	MA	MA	Monda
2	Number, Width, Type & Arrangement	of Exits		
	a. Number of staircases	-		Ness
a paragraphic para	• Upper Floors	02	02 (01 main) (01 through Dominos)	MR
	• Basements	St. A	Sealed (Storage)	MR
	b. Width of staircases			
	<ul> <li>Upper Floors</li> </ul>	1,25mt	1. Q Smt, 1. LESmt	MR
	• Basements	-	Scaled (notinua)	Ademos
	c. Protection of exits			_
	<ul> <li>Fire check door</li> </ul>		Fire Checkdoor possyntis at Mey Flows beliver live	MR
THE PERSON NAMED IN COLUMN 1	<ul> <li>Pressurization</li> </ul>	MA	MA	~
	e. No. of continuous staircases to terrace	01	01	MR
	g. Width of Corridor	M) 4	WA	· Common
	h. Door Size	2 to mk	2.0 m/	MP

Compartmentation.

	Fire check door		FCD provides between	MR	
	5 0 10 miles 1200m 240 miles	40.00	twos Cominos & Duaking		
	Sealing of electrical shafts  Fig. 1. C. 1.  C	MA	MA		
	Fire Rating of shaft door	MA	WA	***	
	Water Curtain	Mu	MA	(m-	
	Fire Dampers	a) 4	MA		
4	Smoke Management System.				
	<ul> <li>Basements</li> </ul>	30 a/c per hour	MA	Commence	
The control of the co	<ul> <li>Upper floors</li> </ul>	12 a/c per hour	Exhaust Fan porovida f	MR	
5	Fire Extinguishers  Smore Ventery				
	• Total numbers ©6		pourdes	MR	
	· Types ABC lyke		provided	MR	
	IS marking	ISI marked	provided	MR	
6	First-Aid Hose Reels.		3		
	Total numbers on each floor	Meg. Floor	provided	MR	
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	provided	MR	
	Nozzle diameter	5 mm	provided	MR	
7	Automatic fire detection and alarming system.				
	Type of detectors	Smoke	provided	MR	
	Location of Main Panel	QF	provided	MR	
	• Location of Repeater Panel		s de		
	Alternate source of power	Required	64 KUA provided	MR	
	Hooters' Location	a fluery Floor	Copinal	MR	
8	MOEFA	Required	provided	MR	
9	Public Address System.	Not require	Not requered		
10	Automatic Sprinkler System.				
	• Basement	-	Sealed	MR	
	Upper Floor     Sprinkler above folgo colling	Required	provided	MR	
	Sprinkler above false ceiling	MA	W) A		
11	Internal Hydrants				
	• Size of riser/down-comer	MA	Mx	E/-	

7	N. 1 Cl l c	4.0		
6	Number of hydrants per floor	MA	MA.	
	Hose Box	MA	MA	-
12	Yard Hydrants.			
	<ul> <li>Total number of hydrants</li> </ul>	MA	MA	
	Hose Box	MA	MA	
13	Pumping Arrangements.			
	Ground Level	MA	NA	Control
	<ul><li>Discharge of main Pump</li></ul>	WA	Mr	Ç
	Head of Main pump	Mar	WA	
	Number of main pumps	MA	N)A	_
	Jockey Pump out put	MA	Ma	
	Jockey pump head	WA	MA	
	Standby Pump out put	WA	NA	0.
	Standby Pump Head	7)1	MA	
	Auto Starting/ Manual	WA	MA	
	stopping	AT/A	MA	
	Pump House Access		-	
	Terrace level     Discharge of pures	450LPM	provided	MR
	<ul><li>Discharge of pump</li><li>Head of the pump</li></ul>	30 201	Cepivord	MR
			provider 64 KUA	
	Power Supply  Auto Starting of rough	Required	Starting Smitch	
14	Auto Starting of pump  Captive Water Storage for fire fighting		private dia GF	MR
17			. 0	
	Underground tank capacity	Ma	MA	
	Draw-off connection	WM	MA	
	Fire service inlet	7)1	WA	•
	Access to tank	War	NA	**************************************
	Overhead Tank capacity	S, ovo 1h.	10, 000 th.	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.			
	<ul> <li>Pressurization of Lift Shaft</li> </ul>	MA	MA	-
	<ul> <li>Pressurization of Lift lobby</li> </ul>	MA	w)A	

		7		
	Communication In lift Car	MA	WA	•
	Fireman's Grounding Switch	MA	MA	- 6
	Lift Signage	MA	MA	
17	Standby power supply	Required	SYKUA	MR
18	Refuge Area.			
THE REAL PROPERTY AND ADDRESS OF THE PERSON ADDRESS OF THE PERSON AND ADDRESS OF THE PERSON AND ADDRESS OF THE PERSON AN	> Total Area	W/A	MA	-
	Location	MA	MA	Commence of the Commence of th
19	Fire Control Room			I.
	Detector System Panel	n) a	MA	
	<ul> <li>Flow Switch Panel</li> </ul>	MA	m) A	
	<ul> <li>PA System Panel</li> </ul>	WA	w) A	-
	Batter backup	WV	wa	
	Building Floor Plans	ny 1	MA	-
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	One ABC lyther fire extringuisher provided near Elect panel	MR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew/grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer

Name Designation Signature of the Inspecting Officer

Name M. K. CHATTOPADHYAY Designation ADO (HO)