GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6 | DFS/ms | School/2012 | 3178 Dated: 30 | 08 | 12

FIRE SAFETY CERTIFICATE

Certified that the Rajkiya Sarvodaya Kanya Vidyalaya at Block-20, Trilok Puri, Delhi-91.Comprised of ground plus one upper floor owned/occupied by Rajkiya Sarvodaya Kanya Vidyalaya have complied with the fire prevention and fire safety requirements in accordance with the circular issued by the Director of Education dtd.01.03.2011and verified by the officer concerned of Fire Service on 17.08.2012 in the presence of Sh.Maharaj Singh Principal, of the school and that the building is fit for occupancy class B' Educational Building' with effect from 3.0.1.58.1.2. for a period of three years , subject to conditions printed overleaf.

Issued on 30/08/12 at New Delhi by

Chief Fire Officer Delhi Fire Service

To.

The Principal Rajkiya Sarvodaya Kanya Vidyalaya Block-20, Trilok Puri, Delhi-91,

Copy:-

1. The Joint Director of Education (Land & Estate) Directorate of Education. Lucknow Road, Delhi -54.

2.The Principal Rajkiya Sarvodaya Bal Vidyalaya Block-20, Trilok Puri, Delhi-91,

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1RN-4_

1. Name & address of the building: RSKV at Block-20, Trilok Puri, Delhi -91.

2. Building is comprised of

: Ground +1, upper floor.

3. Type of Occupancy

: Educational

4. Type of Case

: New Case

5. Details of Previous NOC letter: Nil

6. Fire Safety direction letter No : Circular Director of Education dated 1.3.11

7. Date of Inspection

: 17.08.12

8. Name of the Inspecting officers: DO Virendra Singh

9. Name and designation of Officer:

from the building side

: Sh.Maharaj Singh(Principal).

10. Year of Construction

-: 2001 & 2011

11. Applicant's letter No

: letter No.1712 dated 02.07.12

NO.	Minimum Standards on fire	Circular	Provided at	Remarks		
	prevention and fire safety U/R33	Requirement	Site			
1	Access to building					
	Road width		10 Mtrs.	MR		
	Gate widthWidth of internal road		4 Mtrs.	MR		
0	II WE SEL - KING HALL MANUEL IS STREETED IN STREETED AND THE SELECTION OF			· · · · · · · · · · · · · · · · · · ·		
2	Number, Width, Type and Arrangement of Exits					
	a. Number of Staircases	5 Nos.	5 Nos.	MR		
	Upper Floor	5 Nos	5 Nos.	MR		
	Basement		with talk had been deen deen deen deen deen deen dee	MIN SEN MAY COM TON TON TON SEN SEN SEN SEN SEN SEN SEN SEN SEN		
	B. Width of Staircases					
	Upper Floor		1.35 m	MR		
	Basement					
	c. Protection of exits			T T		
	Fire check door		600 With Sale And Sal			
	Pressurization			***************************************		
	e. No. of continuous staircases to terraceg. Width of Corridorh. Door Size					
		1.5 mts.	1.5 mts	MR		
		1.0 Mtrs	1.0 Mtrs	MR		
3	Compartmentation.					
	Fire check door		100 100 100 100 100 100 100 000 000 000	NOT THE THE SER THE THE SER THE SER THE		
	 Sealing of electrical shafts 		Per 100 000 000 000 000 000 000 000 000 00	and this lead data and that they can see you		
	 Fire rating of shaft door 			400 tip tip to 100 to 100 to 100 to		

	Water curtain						
	Fire Dampers		1. 1				
4	Smoke Management System.	*					
	 Basement 						
	Upper floor						
5.	Fire Extinguishers						
	Total numbers	7 Nos.	17 Nos.	MR			
	• types	ABC & Co2	ABC & Co2	MR			
	IS marking	ISI marked	ISI marked	MR			
6	First-aid-Hose Reels.						
	Total numbers of each floor	NOW AND ADDRESS AND ADDRESS AND ADDRESS AND ADDRESS AND					
	Length of hose reel hoseNozzle diameter						
			tion date date date date date after other saler date	hade delig hade basis date date when other other basis			
		WERE THE THE THE THE THE THE THE THE THE TH					
		es .					
7	Automatic fire detection and alarming system.						
	Automatic fire detection and alaming system.						
	Type of detectors						
				CON TANK CAN CAN CAN CAN CAN CAN CAN CAN CAN			
	 Location of main panel 	00 to 01 to 01 to 01 to 10 to 10 to 10 to	AGA MAN ANN ANN ANN ANN ANN ANN ANN ANN AN	407 400 400 400 400 400 400 400 400 400			
		THE NAME HAVE HAVE SHAD SHAD SHAD SHAD SHAD THEN HAVE HAVE HAVE					
	 Location of repeater panel 						
				-			
	 Alternate source of power 			*			
	r ·						
	Hooter's location			NA 100 00 00 00 00 00 00 00 00 00 00			
8	MOEFA			01 CO			
9	Public address System.	MAN TOUR COST COST COST COST COST COST COST COST		507 000 000 000 000 000 000 000 100 100 1			
10	Automatic Sprinkler System.			date also also also also anno anno anno anno anno			
	Basement						
	upper floor						
	sprinkler above false ceiling			W 40 W 40 W 40 W 40 W 40 W			
11	Internal Hydrants			, , , 10			
1.1	size of riser/down-comer						
	Number of hydrants per floor						
	11 B						
	Hose Box			the state of the s			
				* * * * * * * * * * * * * * * * * * *			
12	Yard Hydrants.		3	4			
	 Total number of hydrants 						
	Hose Box		200 AND DOE COM COM COM COM COM COM COM COM COM	(C)			
13	Pumping Arrangements.						
	 Ground Level 						
	Discharge of main Pump						
	Head of Main Pump						
	Number of main pumps						
	Jockey pump out put						
	Jockey pump head						
	Standby pump out put						
	Standby pump Head						

RSKV Filopopuni B-20

		2		
	Auto Starting /Manual			NAME AND THE PART AND THE ADD THE PART AND THE
	stopping	3	27	
	Pump House Access		77 1 207 - 20	
. 7	Terrace Level			
	Discharge of pump		****	Marie and
	Head of the Pump		100 100 100 100 100 100 100 100 100 100	
	Power supply			
My "				2
	Auto Starting of pump			
14	Captive Water Storage for Fire Fighting.			
	 Underground tank capacity 			
	Draw-off connection		570 ST 100 ST	
	Fire service inlet			
	Access to tank			
	 Overhead Tank capacity 		=	
15	Exit Signage.			
16	Provision of Lifts.			
	 Pressurization of Lift Shaft 			
	 Pressurization of Lift lobby 	UNI SEE CO.	NAME AND DESCRIPTION OF THE PART OF THE PART OF	
	 Communication in lift car 			000 400 COT UNI CON CON CON CON CON CON
	 Firemen's grounding switch 	\$100 Mile State Coll State 1000 Mile State State State State State State	NA 100 100 100 100 100 100 100 100 100 10	
	 Lift Signage 		100 500 500 500 500 500 500 500 500 500	MAN MAN HOL HOL HOL HOL HOL HOL HOL HOL
17	Standby power supply			
18	Refuge Area.			
	 Total area 	THE RES LESS LINE AND REST THE REST COST COST COST COST COST		NAME AND ADDRESS A
	 Location 			
19	Fire Control Room			
	 Detector system panel 			
	 Flow switch panel 			
	PA system panel			
	Battery backup			
	Building Floor Plans			
20	Special Fire Protection systems for			
	protection of special Risks, if any:			3

The fire extinguishers provided in the building were tested/ checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer

Name MRENDRA SINGY

Designation

DOCE!

Duccoldozo