GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/9F5/ons/School/2012/33/1

Dated: 11 09 12

FIRE SAFETY CERTIFICATE

Chief Fire Officer Delhi Fire Service

To,

The Principal M.C.Primary Adrash Girls School Block-28,Trilok Puri , Delhi-91

Copy to:-

- The Director of Education MCD,Nigam Bhawan, Kashmiri Gate,Delhi.
- 2. The Principal
 M.C.Primary Adrash Boys School
 Block-28, Trilok Puri, Delhi-91

CONDITIONS:

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management

shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This Fire Safety Certificate may not be treated in any case for regularizations of

unauthorized construction unauthorized use of land if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: MC Primary Balika School at Block -28, Trilok Puri, Delhi -91.

2. Building is comprised of

: Ground +1, upper floor.

3. Type of Occupancy

: Educational

4. Type of Case

: New Case

5. Details of Previous NOC letter :Nil

6. Fire Safety direction letter No : Circular Director of Education dated 1.3.11

7. Date of Inspection

: 17.08.12

8. Name of the Inspecting officers: DO Virendra Singh

9. Name and designation of Officer:

from the building side

: Smt.Kamlesh (Principal).

10. Year of Construction

-: 1993 & 2010

11. Applicant's letter No

: letter No.Nil dated 08.08.2012.

NO.	Minimum Standards on fire prevention and fire safety U/R33	Circular Requirement	Provided at Site	Remarks		
1	Access to building	- L.		· · · · · · · · · · · · · · · · · · ·		
	Road width		6 Mtrs.	MR		
=	Gate widthWidth of internal road		THE NEW YORK THE THE COST COST COST COST COST	100 500 500 600 600 600 600 600 600		
			WH AND THE RES COS COS COS COS COS COS			
2	Number, Width, Type and Arrangement of Exits					
	a. Number of Staircases	02 Nos.	02 Nos.	MR		
	Upper FloorBasement	02 Nos.	02 Nos.	MR		
	B. Width of Staircases			A		
5	Upper Floor		2 Nos.of 1.35M & 1.0 m	MR		
	Basement					
	c. Protection of exits					
	 Fire check door Pressurization No. of continuous staircases to terrace Width of Corridor Door Size Compartmentation.					
			1No.	MR		
		1.5 mts.	2 mts	MR		
		1.0 Mtrs	1.0 Mtrs	MR		
3						
	Fire check door					
	 Sealing of electrical shafts 			No. 404 Sp. 104 105 105 105 105 105 105 105		
	 Fire rating of shaft door 			****		
	Water curtain					
	Fire Dampers	*** *** *** *** *** *** *** *** ***				
4	Smoke Management System.					
	Basement					

	Upper floor					
5.	Fire Extinguishers	7		1		
	 Total numbers 	6 Nos.	6 Nos.	MR		
	• types	ABC & Co2	Provided	MR		
	IS marking	ISI marked	Prrovided	MR		
6	First-aid-Hose Reels.					
	Total numbers of each floor					
	 Length of hose reel hose 					
	 Nozzle diameter 					
7	Automatic fire detection and alarming system.					
	Type of detectors					
	 Location of main panel 					
	 Location of repeater panel 					
	 Alternate source of power 	d , 22d				
		5				
	Hooter's location					
8	MOEFA					
9	Public address System.					
10	Automatic Sprinkler System.					
10	Basement					
	upper floor					
	sprinkler above false ceiling					
11	Internal Hydrants					
	size of riser/down-comer					
	 Number of hydrants per floor 					
	Hose Box					
-				* 1. 1		
12	Yard Hydrants	A77 8 2				
	Total number of hydrants					
	Hose Box					
13	Pumping Arrangements.					
10	Ground Level					
	 Discharge of main Pump 					
	➤ Head of Main Pump					
11	> Number of main pumps					
	> Jockey pump out put					
	Jockey pump head					
	Standby pump out put					
	Standby pump Head			NO. 100: 100: 100: 100: 100: 100: 100: 100		
	> Auto Starting /Manual					
	stopping					
	> Pump House Access					
	Terrace Level					
	> Discharge of pump					

2.	Head of the Pump		~ ~~~~~~~~	als 100 to 040 as an an an an an an
	Power supply		total total data data spor spor spor spor sons sons sons data data data data	
			Settled has	4
	Auto Starting of pump			
			474	
14	Captive Water Storage for Fire			2 2 2 3
	Fighting.		1	*
	 Underground tank capacity 		100 MM NO MA	
	Draw-off connection			
	Fire service inlet			
	Access to tank			
	 Overhead Tank capacity 			
15	Exit Signage.			
16	Provision of Lifts.			
	 Pressurization of Lift Shaft 			
	 Pressurization of Lift lobby 			
	Communication in lift car			
	 Firemen's grounding switch 		two lasts and fine that the case of the first two and	Now the first that that the time one can can
	Lift Signage			
17	Standby power supply			
18	Refuge Area.			
	Total area			
	Location	NAME AND THE THE THE THE THE THE THE THE THE	100 100 100 100 100 100 100 100 100 100	Note that the first also also also take the
19	Fire Control Room			
	 Detector system panel 			
	Flow switch panel	*****	10 10 10 10 10 10 10 10 10 10 10 10 10 1	
	PA system panel			
	Battery backup			
	 Building Floor Plans 			400 500 000 000 000 000 000 000 000 000
20	Special Fire Protection systems for		City 1004 City 1004 City 1005 City 1005 City 1005 City 1005	AND THE COST AND AND COST AND AND AND AND AND AND
	protection of special Risks, if any:	8		

The fire extinguhers provided in the building were tested/checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer
Name VIRENDRA SINGH

Designation