FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [SEE SUB-RULE (1) OF RULE 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/OFS/ms/motel/2012/3418 Dated: 18/09/2012

FIRE SAFETY CERTIFICATE

Certified that the **Pashupati Nath Resort** Kh. No.30-37, Village Jindpur Main G.T. Karnal. Road, New Delhi., comprised of basement, ground floor only with covered area of 2569.2m², 2585.43m², was granted NOC by this department vide letter No. **F6/DFS/MS/GH/2009/2575 dated 11/08/2009.** The premises was re-inspected by the officers concerned of this department on 27/08/2012 in the presence of **Mr. Rohit Gupta** of the **Pashupati Nath Resort** and found that the building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010. Hence the NOC is renewed and premises is fit for **Class-A-1** (i) residential occupancy with effect from! \$\(\lambda \). (1.2.... for a period of three years subject to conditions printed over leaf.

Chief Fire Officer Delhi Fire Service

Ole

Copy to:

1. Mr. Rohit Gupta

Pashupati Nath Resort Kh. No.30-37, Village Jindpur Main G.T. Karnal. Road, New Delhi

2. Add. Commissioner of Police Licensing Unit 1st Floor, PS Defence Colony, New Delhi

Following fire safety directives must be adhered to:-

- 1) All the fire safety arrangement provided their in shall be maintained in good working g conditions at all time.
- 2) Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3) The trained fire fighting staff should be available round the clock.
- 4) Any deviation, with regards to construction etc shall be verified by the concerned building sanctioning agency.
- 5) The basement shall be used strictly as per the provision of building Bye-Laws.
- 6) This certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. This is available on www.dfs. delhigovt. nic.in

May Kindly peruse letter no.42286/Addl. C.P./Lic(H) dated 02/07/12 received from the Addl. Commissioner of Police, regarding renewal of NOC in r/o Pashupati Nath Resort Kh. No.30-37, Village Jindpur Main G.T. Karnal. Road, New Delhi. It was observe that the building is comprised of basement ground plus one upper floor with covered area of 2569.2m², 2585.43m² & 648.16 m². Premises was inspected by the undersigned & the fire safety arrangements are put up on the prescribed Performa.

1. Name &address of the building : Pashupati Nath Resort Kh. No.30-37, Village Jindpur Main

G.T. Karnal. Road, New Delhi.

2. Type of Occupancy : Class-A-1 (i) Residential

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/GH/2009/2575 dated 11/08/2009

5. Fire Safety directives letter No. : F6/MS/DFS/BP/2006/1215 dated 26/05/2006

6. Date of inspection : 27.08.2012

7. Name of the Inspecting Officers : Division Officer Sunil Chawdhary & Dy GEO (NW)

8. Name and designation of officers

From the building side : Mr. Rohit Gupta

9. Year of Construction

10. Applicant's letter No. : 42286/Addl. C.P./Lic(H) dated 02/07/12

INSPECTION REPORT

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	BBL Requirement	Provided at site	Remarks MR/NMR	
1.	Access to building				
	Road width	09mtrs	Provided	M.R	
	Gate width	5 mtr	Provided	M.R.	
	Width of internal road	required	Provided	M.R. —	
2.	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases				
	Upper Floors	6	Provided	M.R.	

	Basement	10	Provided	M.R.
	b. Width of staircases		£	7,0070
	Upper Floors	Old case	Provided	M.R.
	Basement	Old case	Provided	M.R.
	c. Protection of exits			
	Fire check door	Required	Provided	M.R.
	Pressurization	Required	Provided	M.R.
	d. No. of continuous staircases to terrace	6	Provided	M.R.
	e. Width of Corridor	1.5 mtr	Provided	M.R.
	f. Door size	2 mtr	Provided	M.R.
3.	Compartmentation.			
	Fire check door	Required	Provided	M.R.
	Sealing of electrical shafts	Required	Provided	M.R.
	Fire Rating of shaft door	Required	Provided	M.R.
	Water Curtain	N.R.	N.R.	N.R
	Fire Dampers	Required	Provided	M.R.
4.	Smoke Management System.	*		1
	Basements	Required	Provided	M.R.
	Upper floors	Required	Provided	M.R.
5.	Fire Extinguishers		3	.I
	Total numbers	30	Provided	M.R.

	Types	Required	Provided	M.R.
	IS marking	ISI marks required	provided	M.R.
6.	First-Aid Hose Rees.			
	Total numbers on each floor	3	Provided	M.R.
	Length of hose reel hose	30 m required	Provided	M.R.
	Nozzle diameter	5 mm required	Provided	M.R.
7.	Automatic fire detection and alar	ming system.	-	
	Type of detectors	Smoke & Heat	Provided	M.R.
	Location of Main Panel	Ground floor	Provided	M.R
	Location of Repeater Panel	Required	Provided	M.R
	Alternate source of power	Required	Provided	M.R
	Hooter's Location	Required	Provided	M.R
8.	MOEFA	Required	Provided	M.R.
9.	Public Address System.	Required	Provided	M.R.
10.	Automatic Sprinkler system			3
	Basement	Required	Provided	M.R.
	Upper Floor	Required	Provided	M.R.
	Sprinkler above false ceiling	Required	Provided	M.R.
11.	Internal Hydrants			
	Size of riser/down-comer	150 mm	Provided	M.R.

	Number of hydrants per floor	3	3 Provided	M.R.	
	Hose Box	3	Provided	M.R.	
12.	Yard Hydrants.				
2	Total number of hydrants	4	Provided	M.R.	
	Hose Box	4	Provided	M.R.	
13.	Pumping Arrangements.				
	Ground Level				
	Discharge of main pump	2280 LPM	Provided	M.R	
	➤ Head of Main pump	60 mtr	Provided	N.R	
	➤ Number of main pumps	2	Provided	M.R.	
	Jockey Pump out put	180 LPM	Provided	M.R	
	Jockey pump head	60 mtr	Provided	M.R	
	➤ Standby pump out put	2280 LPM	Provided	M.R	
	Standby pump Head	60 mtr	Provided	M.R	
Ş	➤ Auto Starting/Manual stopping	Required	Provided	M.R	
	> Pump Hose Access	Required	Provided	N.R	
	Terrace level	v			
	Discharge of pump	900 LPM	Provided	M.R.	
	➤ Head of the pump	30 mtr	Provided	M.R.	

	> Power supply	Required	N.P	N.M.R.	
	> Auto Starting of pump	N.A.	N.A. 108 000	M.R.	
14.	Captive Water Storage for fire fighting.				
	Underground tank capacity	1 lak	Provided	M.R.	
	> Draw -off connection	Required	Provided	M.R	
	➤ Fire service inlet	Required	Provided	M.R	
	> Access to tank	Required	Provided	N.R	
	 Overhead Tank Capacity 	10,000	Provided	M.R.	
15	Exit Signage.	Required	Provided	M.R.	
16.	Provision of Lifts		7.5%		
	Pressurization of Lift Shaft	No lift	Provided	M.R	
	Pressurization of Lift lobby	Required	Provided	M.R	
	Communication In lift Car	N.A	N.A	N.A	
	Fireman's Grounding Switch	N.A	N.A	N.A	
	Lift Signage	N.A	N.A	N.A	
17.	Standby power supply	Required	Provided	M.R	
18.	Refuge Area		-		
	> Total Area	-) · N.R.) ©	N.R.	N.R.	
	> Location	N.R.	N.R.	N.R.	

19.	Fire Control Room			
	Detector System Panel	N.R.	N.R.	N.R.
	Flow Switch Panel	N.R.	N.R.	N.R.
	> PA system Panel	N.R.	N.R.	N.R.
	➤ Batter backup	N.R.	N.R.	N.R.
	Building Floor plans	N.R.	N.R.	N.R.
20.	Special Fire Protection Systems for	N.R.	N.R.	N.R.
	Protection of special Risks, if any:			

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/

Signature of the Inspection Officer

Signature of the Inspection Officer

Name Syno Chawdhas y

Designation DO (West)

Name

Designation