## GOVERNTMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No: F.6/DFS/MS/2012/ School/3586

Dated: 28/09/12

## FIRE SAFETY CERTIFICATE

Certified that the - M.C. Primary School, C-4-E, Janak Puri, New Delhi-110058 Comprised of - ground floor plus one upper floor, owned/occupied by Director of Education M.C.D has complied with the fire prevention and fire safety requirements in of Education letter No.F.16/Estate/CC/Fire with the Director Safety/2011/3298 to 3398 dated 01.03.2011 and verified by the officer concerned of fire Service on 29.08.12 in the presence of Sh.. Dayanand Rohilla Principal and that the building/premises is fit for occupancy class – group-B (educational) with effect from the date of issue of this certificate for a period of - three years in accordance with rule 36 under rule 37 or sooner cancelled under Rule 40 and subject to unless renewed compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on ...2.8./........at New Delhi.

Chief Fire Officer Delhi Fire Service

Copy to:

1. The Principal, M.C. Primary School, C-4--E, Janak Puri New Delhi-110058.

 The Director of Eduction MCD Nigam Bhawan (Old Hindu Collage Bldg) Kashmere Gate, Delhi.

3. Divisional Officer (South West)
Shanker Road Fire Station, New Delhi

Note \* :- For general fire safety directives please see overleaf

Following fire safety directives must be adhered to –

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The staff should be trained available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provisions of the Building Bye Laws.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.

	INSPECT	ION REPORT		
3. 4. 5. 6. 7. 8.	Details of previous NOC  Fire Safety directives letter No  Date of inspection  Name of the Inspecting Officers:  Name and designation of officers from the building side  Year of Construction	ise/ Renewal  Io. NIC  NIC  29/8/12  ) HIC A	Dated	
S.		Daya Nand	Robilla Po	ncibal.
No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC	Provided at site	Remarks
1	Access to building	Requirement		MR/NMR
				1
	TOUR WILLIN	R	amto	MR
2 m Z	• Gate width	R	2xtmol. U	Me
	Width of internal road			1.02
2	Number, Width, Type & Arrangement of	f Exits		
g * 200	a. Number of staircases	O		
	• Upper Floors		1100	MR
F 31	• Basements		- 4-	-4-
	b. Width of staircases	NIC		
	• Upper Floors	R	150,4150 Cms	MR
	• Basements	· - u -		-u-
18 12	c. Protection of exits	Me		
	• Fire check door			
				1
	• Pressurization			
	e. No. of continuous staircases to terrace	R	TWO	MR
	g. Width of Corridor	R	2.16 mbs	mr
	h. Door Size	R	112 cm	me

3	Compartmentation.	NR				
	<ul> <li>Fire check door</li> <li>Sealing of electrical shafts</li> <li>Fire Rating of shaft door</li> <li>Water Curtain</li> <li>Fire Dampers</li> </ul>					
4	Smoke Management System.					
	Basements     Upper floors	30 a/c per hour 12 a/c per hour				
5	Fire Extinguishers	₽	P:			
	Total numbers Types IS marking		6 Nos 2 Co2 +1 De 1 De P Ju	101		
6	First-Aid Hose Reels.	ISI marked	es	-u		
	<ul> <li>Total numbers on each floor</li> <li>Length of hose reel hose</li> <li>Nozzle diameter</li> </ul>	30 m 5 mm				
7	Automatic fire detection and alarming system.					
	<ul> <li>Type of detectors</li> <li>Location of Main Panel</li> <li>Location of Repeater Panel</li> <li>Alternate source of power</li> <li>Hooters' Location</li> </ul>	system, NY				
8	MOEFA	•				
9		MR		-		
10	Automatic Sprinkler System.	NR				
	Basement					
	Public Address System.  Automatic Sprinkler System.  Basement	MR				

		A	
<ul><li>Upper Floor</li><li>Sprinkler above false ceiling</li></ul>			
Internal Hydrauts	MR		
Size of riser/down-comer			
<ul><li>Number of hydrants per floor</li><li>Hose Box</li></ul>			
			•
Yard Hydrants.	NR		
Total number of hydrants     Hose Box			
TAGGE BOX			
Pumping Arrangements.	MR		
Ground Level			
Discharge of main Pump  Head of Main pump			
<ul><li>Number of main pumps</li></ul>			
> Jockey Pump out put			
> Jockey pump head			
<ul><li>Standby Pump out put</li><li>Standby Pump Head</li></ul>			
<ul><li>Standby Pump Head</li><li>Auto Starting/ Manual</li></ul>			
stopping,			
➤ Pump House Access			
<ul> <li>Terrace level</li> <li>Discharge of pump</li> </ul>			
➤ Head of the pump			
> Power Supply			
➤ Auto Starting of pump			
14 Captive Water Storage for fire fighting	g. NR		
Underground tank capacity			
> Draw-off connection		e	

0 1	A		
	> Fire service inlet		
	> Access to tank		
	Overhead Tank capacity		
5	Exit Signage.		
16	Provision of Lifts.	MR	•
		MR	
	Pressurization of Lift Shaft		
	<ul> <li>Pressurization of Lift lobby</li> </ul>		
	Communication In lift Car		
	• Fireman's Grounding Switch		
. ()	• Lift Signage		
17	Standburge		
18	Standby power supply Refuge Area.	MR	
		MR	
	> Total Area		
07.	> Location		
19	Fire Control Room	NR	
	Detector System Panel		
	• Flow Switch Panel		
	PAi System Panel		
	Batter backup		
	Building Floor Plans		
20	Special Fire Protection Systems for		
	Protection of special Risks, if any:	MR	
	The state of the s		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

(5)

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name H. L. AMEJA

Name

Designation Div. Afficer

Designation