FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [SEE SUB-RULE (1) OF RULE 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADOUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/2FS/ons/EH/2012/3671

Dated: 05//0 /2012

FIRE SAFETY CERTIFICATE

Chief Fire Officer Delhi Fire Service

Str

Copy to:

Barbeque Nation Restaurant (A unit of Barbeque Nation Hospitality Ltd)
 Unit no. 101 and 102 first floor A-7 Netaji Subhash Place, Pitampura, New Delhi

Note:- For general fire safety directives please over leaf.

Following fire safety directives must be adhered to:-

- 1) All the fire safety arrangement provided their in shall be maintained in good working g conditions at all time.
- 2) Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3) The trained fire fighting staff should be available round the clock.
- 4) Any deviation, with regards to construction etc shall be verified by the concerned building sanctioning agency.
- 5) The basement shall be used strictly as per the provision of building Bye-Laws.
- 6) This certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. This is available on www.dfs. delhigovt. nic.in

May Kindly peruse letter no.nil dated 17/08/2012 received from the authrosied Signatory regarding of NOC in r/o Barbeque Nation Restaurant (A unit of Barbeque Nation Hospitality Ltd.) located at Unit no. 101 and 102 first floor A-7 Netaji Subhash Place, Pitampura, New Delhi. Premises was inspected by the undersigned & the fire safety arrangements are put up on the prescribed Performa.

1. Name &address of the building : Barbeque Nation Restaurant (A unit of Barbeque

Nation Hospitality Ltd.) located at Unit no. 101

and 102 first floor A-7 Netaji Subhash Place,

Pitampura, New Delhi

2. Type of Occupancy : Class-D (Assembly)

3. Type of Case : New

4. Details of previous NOC : Nil

5. Fire Safety directives letter No. : Nil

6. Date of inspection : 20.09.2012

7. Name of the Inspecting Officers : Divisional Officer Sunit Chowdhary

8. Name and designation of officers

From the building side : Sh. Manoj

Year of Construction :

9. Applicant's letter No. : nil dated 17.08.12

INSPECTION REPORT

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	NBC/BBL Requirement	Provided at site	Remarks MR/NMR	
· ·	Access to building	of the mall	of the mall	9 0	
	Road width	12 mtrs	50 mtr	M/R	
	Gate width	5 mtr	Provided	M/R	
	Width of internal road	06 mtr	Provided	M.R.	
2.	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases	2 for restaurant	3 for restaurant	M.R.	

Upper FloorsBasementWidth of staircases	N.A.	Provided N.A	M.R. N.A
Basement	N.A.	N.A	N.A
b. Width of staircases	1		
	2 staircase of 1.5 mtr	1.5 mtr, 1.25 mtr	M.R.
 Upper Floors 	width each	& 2 mtr for restaurant	
	N.A.	N.A.	N.A.
 Basement 			
c. Protection of exits			
0. 110.000.001 02 0.222			
 Fire check door 	Required		M.R.
	Required	Provided	M.R.
			1.17
	2 mtr for Restaurant	Provided	M.R.
e. Width of Corridor		2= (2 mtr),	
f. Door size	2 doors 1.5 mtr each	4=(1.25 mtr)	M.R
Compartmentation.			
	Paguired	Provided	M.R.
Fire check door	Required	Tioriaca	
 Sealing of electrical shafts 	Required	Provided	M.R
Eine Dating of shaft door		D '1-1	M.R.
• Fire Rating of shart door	Required	Provided	IVI.N.
Water Curtain	N.A.	N.A.	N.A.
			MD
Fire Dampers	required	Provided	M.R.
Smoke Management System.			
NINGTO TITALING	,	T	
D	NI A	NA	N.A.
Basements	IV.A.	. 1.4	
Upper floors			
£ £	Required	Provided	M.R.
Fire Extinguishers			
Total numbers	10 For the restaurant	10	M.R
3			
	 Pressurization d. No. of continuous staircases to terrace e. Width of Corridor f. Door size Compartmentation. Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Fire Extinguishers	Fire check door Pressurization d. No. of continuous staircases to terrace e. Width of Corridor f. Door size Compartmentation. Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Required Required 2 mtr for Restaurant Required Required	• Fire check door • Pressurization d. No. of continuous staircases to terrace e. Width of Corridor f. Door size Compartmentation. • Fire check door • Sealing of electrical shafts • Fire Rating of shaft door • Water Curtain • Fire Dampers Smoke Management System. Required Provided 2 mtr for Restaurant Provided 2=(2 mtr), 4=(1.25 mtr) Provided

1				
	• Types	ABC & CO ₂	provided	M.R -
	IS marking	ISI marks	provided	M.R
6.	First-Aid Hose Rees.	1	,	
	Total numbers on each floor	1 required	Provided	M.R
	 Length of hose reel hose 	30 m required	provided	M.R
	Nozzle diameter	5 mm required	provided	M.R
7.	Automatic fire detection and alar	ming system.		
	Type of detectors	Smoke & Heat for restaurant	Provided	M.R
	Location of Main Panel	First floor at restaurant level	provided	M.R
	Location of Repeater Panel	N.A.	N.A.	N.A.
	Alternate source of power	Required	provided	M.R
	Hooter's Location	Required	Provided	M.R
8.	MOEFA	Required for Restaurant	Provided	M.R
9.	Public Address System	Not Required	Provided	M.R.
10.	Automatic Sprinkler system			
	Downst	N.A.	N.A.	N.A.
	BasementUpper Floor	Required for the restaurant	Provided	MR
	Sprinkler above false ceiling	Required for the Restaurant	Provided	M.R
11.	Internal Hydrants	1		
	Size of riser/down-comer	150 mm	provided	M.R

	Number of hydrants per floor	1	Provided	M.R J
	• Hose Box	1	Provided	M.R
12.	Yard Hydrants.			
	Total number of hydrants	N.A.	N.A.	N.A.
	Hose Box	N.A.	N.A.	N.A.
13.	Pumping Arrangements.			
	Ground Level	Common for building		
	Discharge of main pump	2280 LPM	Provided	M/R
	Head of Main pump	90 mtr	Provided	M/R /
	> Number of main pumps	2 electric	Provided	M/R
	> Jockey Pump out put	180 LPM	Provided	M.R.
	Jockey pump head	90 mtr 2280 LPM	Provided Provided	M.R.
	Standby pump out put	Diesel		M/R
	Standby pump Head	90 mtr	Provided	M/R
	 Auto Starting/Manual stopping 	Required	Provided	M/R
	➢ Pump Hose Access	Required	Provided	M.R.
	Terrace level			
No. of the Control of	Discharge of pump	450 LPM	Provided	M.R
Transconding of the control of the c	➤ Head of the pump	50 mtr	Provided	M.R /

*				
	Power supply	Required	Provided	M.R
	➤ Auto Starting of pump	Required	Provided	M.R
14.	Captive Water Storage for fire fig	hting.		
	Underground tank capacity	N.A.	N.A.	N.A.
	Draw -off connection	N.A.	N.A.	N.A.
	> Fire service inlet	N.A.	N.A.	N.A.
	Access to tank	N.A.	N.A.	N.A.
•	Overhead Tank Capacity	20, 000 ltrs	Provided	M.R /
15	Exit Signage.	Required	Provided	M.R
16.	Provision of Lifts	For building	For building	
	Pressurization of Lift Shaft	Required	Provided	M.R. /
	Pressurization of Lift lobby	Required	Provided	M.R.
	Communication In lift Car	Required	Provided	M.R.
	Fireman's Grounding Switch	Required	Provided	M.R.
	Lift Signage	Required	Provided	M.R.
17.	Standby power supply	Required	Provided	M.R
18.	Refuge Area	N.R.	N.R	N.R
	> Total Area	N.A.	N.A.	N.A. /
	> Location	N.A.	N.A.	14.74.

				A.
19.	Fire Control Room			
	> Detector System Panel	N.A.	N.A.	N.A.
	> Flow Switch Panel	N.A.	N.A.	N.A.
	> PA system Panel	N.A.	N.A.	N.A.
	> Batter backup	N.A.	N.A.	N.A.
	Building Floor plans	N.A.	N.A.	N.A.
20.	Special Fire Protection Systems	N.A.	N.A.	N.A.
20.	for			
	Protection of special Risks, if any:			

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/.

Signature of the Inspection Officer

Signature of the Inspection Officer

Name Sunil Chaudhary

Name

Designation

Designation D.O (West)

Dy (Fb. Lewis all 2