GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. F6/2F5/ans/School/2012/3838 Dated: 17/10/2012

FIRE SAFETY CERTIFICATE

Certified that the Nigam Pratibha Vidhyalaya, is comprised of Ground floor tin shed S P S rooms, located at Rajouri Garden (Main), New Delhi-110027 have complied with the fire prevention and fire safety requirements in accordance with the Circular No F.16/Estate/CC/Fire Safety/2011/3298-3398 dated 01/03/2011 issued by Director of Education and verified by the officer concerned of Fire Service on 27/09/2012 in the presence of Mrs Nirmala Chaudhary, Principal and that the building / premises is fit for occupancy of Group Class B (Educational) with effect from 17/10/2 for a period of three years, subject to conditions mentioned below.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provision of building bye laws.
- 6. This certificate cannot be treated in any case for regularizations of unauthorized construction
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>WWW.dfs.Delhigovt.nic.in</u>

Issued on 17/10/12 at New Delhi by

Chief Fire Officer Delhi Fire Service

8/08

Copy to:

- 1. The Principal, Nigam Pratibha Vidhyalaya, Rajouri Garden (Main), New Delhi-110027, ID-1556064
- 2. The Director of Education, South DMC Civic Centre New Delhi

***************************************	0		GF	SPSSU	heds
IN	SPECTIO	N REPORT			
ouilding:	Nigem	hat like	Wide	10 6000	Ro

	1. Name & address of the building: ///	am brolebla	Vidualana K	Quinni Golula	
	2. Type of Occupancy :	du-	July, !!	70009 17-110	
	O 710	Case/ Renewal			
	4. Details of previous NOC : Letter No Dated:				
	5. Fire Safety directives letter No : Dir g Sche.				
(6. Date of inspection	19/12			
	7. Name of the Inspecting Officers:	700 SS Tule		THE MINISTER SHAPE STORY (1) AND	
	8. Name and designation of officers				
	from the building side : δ	not Mirmo	de chowd	Kary (Prince	
(9. Year of Construction :/_	955			
1	0. Applicant's letter No. :	il attel 6/	8/12	,	
			NOS-55	7	
G	NOT-1+14 NOR-	17			
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR	
1	Access to building				
	Road width	6m	6M	mla	
	Gate width			- //\	
	 Width of internal road 			Constant of the Constant of th	
2	Number, Width, Type & Arrangement	of Exits			
	a. Number of staircases			7	
	Upper Floors				
	Basements		· ·		
	b. Width of staircases			100 mm and	
	Upper Floors	ii ii		•	
	Basements		1 A		
	c. Protection of exits		<i></i>		
	Fire check door			and an about parties and passes or time a full figure and an analysis of the contract of the c	
	Pressurization				
	e. No. of continuous staircases to terrace			The second secon	
	g. Width of Corridor				
	h. Door Size	Intr	Imtr	10	
3	Compartmentation.	111117	Imir	MIC	
	Fire check door	The state of the s			
	Sealing of electrical shafts				
	Fire Rating of shaft door		.114		
	or shart door		MI		

	FIFE Extinguishers	and a second	and the same			
14.1	Total numbers .	one @ 300 m2	3	m/R		
	• Types	ISI marked	ABC	MIK		
	IS marking	131 marked	yes	m/R m/R no/R		
6	First-Aid Hose Reels.		7.00			
	Total numbers on each floor					
	• Length of hose reel hose	^	10			
	 Nozzle diameter 	30 m	NA			
7		5 mm		l.		
	Automatic fire detection and alarming system.					
	• Type of detectors	. 3				
	• Location of Main Panel					
	Location of Repeater Panel	war in the	ula			
	Alternate source of power	- A A	MI	9		
	Hooters' Location		a			
8	MOEFA					
9	Public Address System.					
10						
10	Automatic Sprinkler System.		MA			
	• Basement					
	Upper Floor					
	Sprinkler above false ceiling					
11	Internal Hydrants	J				
	• Size of riser/down-comer		4) p = 2			
	Number of hydrants per floorHose Box		10			
12	Yard Hydrants.		NIM	7 -		
	•			2		
	Total number of hydrants			ā		
12	Hose Box					
13	Pumping Arrangements.					
	• Ground Level	50	-			
T STATE OF THE STA	Discharge of main Pump		,			
	Head of Main pump					
1	Number of main pumps	^	7 7			
	> Jockey Pump out put					
	Jockey pump head	w s	IN			
	Standby Pump out put		HIM			
	 Standby Pump Head 					
	Auto Starting/ Manual					
	stopping Pump House Access		1 200 200 200			
			C. Linchter D. E.			
	Terrace levelDischarge of pump		212 2 F - SE 28 F 27 H K 1 21 F			
	Head of the nume					

	, a	
14	Captive Water Storage for fire fighting	· /
	Underground tank capacity	
	Draw-off connection	
	Fire service inlet	
	Access to tank	MA
	Overhead Tank capacity	
15	Exit Signage.	
16	Provision of Lifts.	
	Pressurization of Lift Shaft	
	Pressurization of Lift lobby	
	Communication In lift Car	~ M M
	Fireman's Grounding Switch	12 /
	Lift Signage	
17	Standby power supply	
18	Refuge Area.	
	Total Area	
	Location	
19	Fire Control Room	
	Detector System Panel	
	 Flow Switch Panel 	14
	 PA System Panel 	pl la
·	Batter backup	
	Building Floor Plans	
20	Special Fire Protection Systems for Protection of special Risks, if any:	

The fire protection systems provided in the building were test checked and found functional the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention at fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35f the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.....

Signature of the Inspecting Officer

Name

Name

Signature of the Inspecting Officer

Name

ADO(NA)

Designation