GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DFS/as/2012/3778

Dated: 15/10/12

FIRE SAFETY CERTIFICATE

Issued on at New Delhi by

Chief Fire Officer Delhi Fire Service

To,

Sh.Jasbir Singh (Fire Officer)
Fire Department
New Delhi Municipal Council
Palika Kendra, New Delhi -110001.

Copy to:-

The Chairperson New Delhi Municipal Council Palika Kendra, New Delhi -110001.

CONDITIONS: 1. All the means of escape shall be kept free of all type of obstruction all the time. 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency. 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible. 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities. 5. Basement shall used as per BBL. 5. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in. 6. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction/ unauthorized use of land if any. 7. A qualified Fire Officer shall be appointed for the underground shopping mall as per this office letter No.F.6/DFS/MS/78/131 dated 08.06.1978.

INSPECTION REPORT

Name & address of the building:

Palika Bazar, Cannaught Place, New Delhi.

2. Type of Occupancy

: Underground Shopping Complex

3. Type of Case

4. Details of Previous NOC

5. Fire Safety directives No

: F.6/DFS/MS/1976/154 dated 13.10.1976 🗸

6. Date of Inspection

: 07.09.12 and 29.9.12

7. Name of the Inspecting Officer: Dy CFO TS Sharma, DO Virendra Singh and ADO Dharmbir Singh

8. Name of the designation of Officer

From the building side

: Sh.Jasbir Singh (Fire Officer, NDMC)

9. Year of Construction

: 1976

10. Applicant's letter No

: Fire/3137/D dated 04.09.12

S.NO.	Minimum Standards on fire prevention	Old Bldg./ Old	Provided at Site	Remarks MR/NMR		
	and fire safety U/R33	Requirements				
1	Access to building					
	Road width	12 Mtrs	14 & 18 Mtrs.	MR		
	Gate width		6 mtrs.	NAD		
	Width of internal road		-	MR		
2	Number Width Type and A	r	6 mtrs.	MR		
	Number, Width, Type and Arrangement of Exits a. Number of Staircases O7 Nos O8 Nos NAP					
	Upper Floor	07 Nos.	08 Nos.	MR		
	Basement					
	Dasement	07 Nos	08 Nos.&	MR		
	B. Width of Staircases		2 Ramps			
	Upper Floor					
	Basement		***************************************			
	c. Protection of exits	1.5 M	Varies from 1.5	MR		
	Fire check door		Mts.to 2.94mts			
	THE CHECK GOOT	Required	Provided at	MR		
	Pressurization		ESS & AHUs			
	e. No. of continuous staircases to terrace g. Width of Corridor h. Door Size		***************************************	***********		
				NV 300 NN NO 100 N 100 NO		
			3.5 mts.	MR		
			Mostly 1.2 mts	MR		
	Compartmentation.	Required Provided				
	Fire check door '	Required	Provided	MR		
	Sealing of electrical shafts	Required	Sealed	MR		
	Fire rating of shaft door		1hr & 2 hrs.	MR		
	Water curtain	***************************************	********	0 * * * * * * * * 0 * * 4 * 9 * 0		
	Fire Dampers	Required	Provided	MR		
	Smoke Management System.					
	Basement	***************************************	provided	MR		
	Upper floor	12 a/c per hour		***************************************		
	Fire Extinguisher					
	Total numbers	60 no.	60 No.	MR		
	types	ABC & Co2	ABC & Co2	MR		
	IS marking	ISI marked	ISI marked	MR		

	First-aid-Hose Reels. Total numbers of each floor	6 no.	FIOVIACA	MR
	Length of hose reel hose	30 m	Provided	MR
	at diameter	5 mm	Provided	MR
	8 4			
	Automatic fire detection and alarming system.		Provided	MR
	Type of detectors	Smoke	Control Room	MR
	Location of main panel	Required	Provided	MR
	Location of repeater panel Alternate source of power	Security Room	Provided	MR
		Battery & DG Set	Provided	
	u tarda location	Different	Provided	MR
	Hooters's location	Location		
		Required	Provided	MR
8	MOEFA	Required	provided	MR
9	Public address System. Automatic Sprinkler System.	Required	Provided	MR
10	basement	Required	Provided -	MR
	war floor	N/A		and one was not one can say the can be one
	upper floor sprinkler above false ceiling	Required	Provided	MF
	Internal Hydrants	3 4 4		
11_	size of riser/down-comer	100 mm	100 & 150 mm	
	Number of hydrants	06 nos.	07 nos.	MR
	Hose Box	06 nos.	07 nos.	MR
12	Yard Hydrants. Total number of hydrants	6 nos.	6 nos.	MR
		6 nos.	6 nos.	MR
	Hose Box Pumping Arrangements.			
13	Ground Level	Required	Provided	MR
		2850 LPM	2850 LPM	MR
-	Discharge of main Pump	70 Mtrs.	70 mtrs	MR
	Head of Main Pump	1 nos.	1 nos.	MR
	Number of main pumps	225 LPM	450 LPM	MR
	Jockey pump out put	70 Mtrs.	70 mtrs.	MR
	Jockey pump head	2850 LPM	2850 LPM	MR
	Standby pump out put	70 Mtrs	70 Mtrs.	MR
	Standby pump Head	Auto	Provided	MR
	Auto Starting /Manual stopping	Required	Provided	MR
	Pump House Access	печинеи		
	Terrace Level			
	Discharge of pump			***************************************
	Head of the Pump			***********
	Power supply			
	Auto Starting of pump		- KW	
1	4 Captive Water Storage for Fire Fighting		2.00.0001+	MR
_	Underground tank capacity	2,00,000 Ltrs		
-	Draw-off connection	Required	Provided	MR

	Fire service inlet	Required	Provided	MR
	Access to tank	Required	Provided	MR
	Overhead Tank capacity		***************************************	*****
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.			
	Pressurization of Lift Shaft			************
	Pressurization of Lift lobby			*********
	Communication in lift car		*******	************
	Firemen's grounding switch			
	Lift Signage			**********
17	Standby power supply	Required	Provided	MR
18	Refuge Area.			NO. 475 SM
	Total area		No. 600 NO. 600 CO. 600 NO. 600 NO. 600 NO. 600 NO. 600 NO.	Miss and the time of the time of the time.
	Location		Mark Mark Mark Alex Mark Mark Mark Capt along the Mark Mark Mark Alex And Capt	The SP IN SEC OR IN SEC OR IN SEC OR
19	Fire Control Room			
	Detector system panel	Required	Provided	MR
	Flow switch panel	Required	do	MR
	PA system panel	Required	do	MR
	Batter backup	Required	do	MR
	Building Floor Plans	Required	do	MR
20	Special Fire Protection systems for protection of special Risks, if any:		Provided for HT/LT Panels	accepted

The fire protection systems provided in the building were tested checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010. as per office left made. 8.6.1978.

Sign. of the Inspecting Officer

Name

Designation

Sign. of the Inspecting Officer

Name VIRENDRA SINGH

Designation

Sign. of the Inspecting Officer

Name D.S. yadav

Designation ADO(c3)