GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6 DFS/ms/2012/3797

Dated: 15/0/12

FIRE SAFETY CERTIFICATE

Certified that the Shaheed Bhagat Singh Place located at Gole Mkt., New Delhi, comprised of basement, ground plus three upper floors owned by NDMC have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officers concerned of this department on 07.09.12 & 29.09.12 in the presence of Sh.Jasbir Singh (Fire Officer, NDMC) and that the building is fit for occupancy class "Mercantile /Business Class" with effect from 15.10.202 for a period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed overleaf.

Issued on 15/10/2012 at New Delhi by

Chief Fire Officer Delhi Fire Service

To,

Sh.Jasbir Singh (Fire Officer)
Fire Department
New Delhi Municipal Council
Palika Kendra, New Delhi -110001.

Copy to:-

The Chairperson New Delhi Municipal Council Palika Kendra, New Delhi -110001.

CONDITIONS:

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. Basement shall used as per BBL.

5. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.

6. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction/ unauthorized use of land if any.



INSPECTION REPORT

Name & address of the building

: Shaheed Bhagat Singh Place, Goll Mkt., New Delhi.

(B+4+3)

2. Type of Occupancy

Mercantile/Bussiness

3. Type of Case

: New

4. Details of Previous NOC

: Nil

5. Fire Safety directives No

: F.6/DFS/MS/92/ 1556 dated 26.08.92

6. Date of Inspection

: 07.09.12 & 29.09.12

7. Name of the Inspecting Officer: DO Virendra Singh and ADO Dharmbir Singh

8. Name of the designation of Officer

From the building side

: Sh.Jasbir Singh (Fire Officer, NDMC)

9. Year of Construction

: 1990 -91

10. Applicant's letter No

: Fire/323/D dated 15.09.12

S.NO.	Minimum Standards on fire prevention and fire safety U/R33	Old Bldg./ Old Requirements	Provided at Site	Remarks MR/NMR			
1	Access to building						
	Road width Gate width Width of internal road	12 Mtrs	12 Mtrs.	MR			
		*					
		NA OE NO	ATT STO COD AND AND AND AND AND AND AND AND	# C			
2	Number, Width, Type and Arrangement of Exits						
	a. Number of Staircases		T	W 10 40 10 10 41 10 10 10 10 10 10 10 10 10 10 10 10 10			
	Upper Floor	2 Nos.	03 Nos.	MR			
	Basement	2 Nos.	03 Nos.& 2	MR			
			Ramps	9			
	B. Width of Staircases						
	Upper Floor	1.25 M	2 x1.5 M & 1.0 M	MR ·			
	Basement	1.25 M	p1.5 M & 1.0 M	MR			
	c. Protection of exits						
	Fire check door Pressurization	Required	Provided	MR			
	e. No. of continuous staircases to terrace g. Width of Corridor h. Door Size	*** *** *** *** *** *** ***	2 Nos.	MR			
			2.35 mts	MR			
		MR COR COR COR COR COR COR COR COR COR CO	1.20 mts	MR			
3	Compartmentation.	Required	Provided				
3	Fire check door	Required	Provided	MR			
	Sealing of electrical shafts	Required	Sealed	MR			
	Fire rating of shaft door		1hr & 2 hrs.	MR			
	Water curtain		1111 00 2 111 31				
	Fire Dampers	Required	Provided	MR			
4	Smoke Management System.						
	Basement	30a/c per hour	provided	MR			
	Upper floor	12 a/c per hour					
5.	Fire Extinguisher						
	Total numbers	60 no.	60 No.	MR			
	types	ABC & Co2	ABC & Co2	MR			

	IS marking	ISI marked	ISI marked	MR		
	First-aid-Hose Reels.		Ď. sided	MR		
	Total numbers of each floor Length of hose reel hose Nozzle diameter	04 nos.	Provided			
		30 m	Provided	MR		
		5 mm	Provided	MR		
	Automatic fire detection and alarming system.					
	Type of detectors	Smoke	Provided	MR		
	Location of main panel Location of repeater panel Alternate source of power	Required	Control Room	MR		
		Security Room	Provided	MR		
		Battery & DG Set	Provided	MR		
	Hooters's location	Different	Provided	MR		
	Hooters's location	Location				
3	MOEFA	Required	Provided	MR		
9	Public address System.	Required	provided	MR		
10	Automatic Sprinkler System.	Required	Provided	MR		
10	basement	Required	Provided	MR		
	upper floor	Required	Provided	MR		
	sprinkler above false ceiling	N/A	40 M W W W W W W W W W W W	NO. OF MY ME NO THE THE THE ME NO THE ME NO THE ME NO THE ME NO THE		
11	Internal Hydrants					
11	size of riser/down-comer	100 mm	100 & 150 mm	MR		
	Number of hydrants	02 & 3 nos.	Provided	MR		
	Hose Box	02 & 33 nos.	Provided	MR		
12	Yard Hydrants.					
12	Total number of hydrants	7 nos.	Provided	MR		
	Hose Box	7 nos.	Provided	MR		
12	Pumping Arrangements.					
13	Ground Level	Required	Provided	MR		
	Discharge of main Pump	4500 LPM	4500 LPM	MR		
	Head of Main Pump	70 Mtrs.	70 mtrs	MR		
	Number of main pumps	2 nos.	2 nos.	MR		
	Jockey pump out put	450 LPM	450 LPM	MR .		
	Jockey pump head	70 Mtrs.	70 mtrs.	MR		
	Standby pump out put	4500 LPM	4500 LPM	MR		
	Standby pump det pet	70 Mtrs	70 Mtrs.	MR		
	Auto Starting /Manual stopping	Auto	Provided	MR		
	Pump House Access	Required	Provided	MP		
	Terrace Level					
	Discharge of pump	450 LPM	450 LPM	MR		
	Head of the Pump	70 Mtrs	70 Mtrs.	MR		
	Power supply	Auto	Provided	MR		
	Auto Starting of pump	Required	Provided	MR		
10	Captive Water Storage for Fire Fighting.		0			
14	Underground tank capacity		1, 5 0,000 Ltrs.	MR		
	Draw-off connection	Required	Provided	MR		

	Fire service inlet	Required	Provided	MR
	Access to tank	Required	Provided	
3	Overhead Tank capacity	required		MR
15	Exit Signage.	Poquinad (20000 Ltrs.	MR 🗸 🗸
16		Required	Provided	MR
	Provision of Lifts. Only one left Pressurization of Lift Shaft	is there .	4	
		*************	********	
	Pressurization of Lift lobby	*******	*** *** *** *** *	***************************************
	Communication in lift car	Required	Provided	MR
Period and the second	Firemen's grounding switch	Required	Provided	MR
	Lift Signage	******	*******	
17	Standby power supply	Required	250 KVA	MR
18	Refuge Area.		230 KVA	IVIN
	Total area		THE RESIDENCE OF THE RESIDENCE OF THE SECOND STATE OF THE SECOND S	the first the sea and sea (see the table of
	Location		ON HE	THE CO. AND AND ANY THE CO. AND THE
19	Fire Control Room			THE REPORT OF THE PROPERTY AND ADDRESS OF THE PROPERTY
	Detector system panel	Required	D:1-1	
	Flow switch panel		Provided	MR
	PA system panel	N/A	70 ED ED ED ED EN EN EN EN EN EN EN EN EN	the sale CO (40 Kg) and the sale are the tab and an are the tab
		Required	Provided	MR
	Batter backup	Required	Provided	MR
	Building Floor Plans	Required	Provided	MR
20	Special Fire Protection systems for protection of special Risks, if any:	N/A		IVIN

The fire protection systems provided in the building were tested checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Sign. of the Inspecting Officer
Name D. S. Vadar
Designation

Designation ADO (C.D)

Sing. of the Inspecting Officer
Name VIRENDRA SINGN

Designation