GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI-110001

No.F6/DFS/MS/GH/2012/ 3807

Dated : 17 10 112

FIRE SAFETY CERTIFICATE

Issued 17 10 12 at New Delhi by.

Chief Fire Officer Delhi Fire Service

- Copy to:- (1) The Addl. Commissioner of Police, (Lic.), First Floor, PS Defence Colony, New Delhi
 - (2) Gaiety Palace, A-14, Kailash Colony, New Delhi.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

- 1. Name & address of the building:- Gaiety Palace, A-14, Kailash Colony, New Delhi.
- 2. Type of occupancy:- Residential Lodging or Rooming Houses.
- 3. Type of case:- Renewal
- 4. Details of previous NOC:-F6/DFS/GH/MS/2009/3347 dated 10/11/09
- 5. Fire safety directives No.- No
- 6. Date of inspection: 18/09/12
- 7. Name of the inspecting officer:- A.D.O. S.S. Kaushik
- 8. Name & designation of officer

From the building side:- Mr. Virender Sharma.

- 9. Year of construction: 2001.
- 10. Applicant's letter No:- 82505/Addl.C.P./Lic.(H) dated 06/09/12 basement, ground + 3 upper floors for 08 guest rooms at 1st floor Old Case

CNI	floors for 08 guest rooms at 1st floor Old Cas						
S.No.	Minimum Standards on fire	BBL	Provided at	Remarks			
1	Prevention and fire safety U/R 33	Requirement	site	MR/NMR			
1.	Access to Building						
2	1) Road width		Provided	MR			
	2) Gate width	N/A	N/A	N/A			
	3)Width of internal road	N/A	N/A	N/A			
2.	Number, Width Type & Arrangement of Exits		11/11	IVA			
	A. Number of staircases						
	1. Upper floors	2 Nos.	Provided	MR			
15			Tioviaca	IVIIC			
147	2. Basements	2 Nos.	Provided	MR			
	B. Width of staircase	9		TVIIC			
	1. Upper floors	125 cms.	125 cms. &	MR			
		9	90 cms.				
	2. Basements	125 cms.	125 cms. &	MR old case			
		-	90 cms.				
	C. Protection of exits	N/A	N/A	N/A			
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous staircase	one	one	MR			
	to terrace	Ext.	V				
	E. Width of corridor	N/A	N/A	N/A			
3.	F. Door size	1 mtr.	1 mtr.	MR			
o	Compartmentation			12 1			
	1) Fire check door	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
	3) Fire rating of shaft door	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
l	Smoke Management System						
	1) Basements	30 a/c per hour	Exhaust fan	MR			
	2) Upper floors	12 a/c per hour	Exhaust Fan	MR			
5.	Fire Extinguishers						
	1) Total numbers		13 Nos.	MR			
5,	2) Types]	ABC &W.Co2	MR			
	3) ISI marking	ISI Marked	Yes	MR			
•	First-Aid Hose Reel						
	1) Total number of each floor	One	1 at each floor	MR			
	2) Length of hose reel hose	30 m	Yes	MR			
	3) Nozzle diameter	5 mm	Yes	MR			
	Automatic Fire Detection & Alarming System						
-	1) Type of detectors	N/A	N/A	N/A			
	2) Location of main panel	N/A	N/A	N/A			
	3) Location of repeater panel	N/A	N/A	N/A			

	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A MR
	MOEFA	Yes	Provided	
	Public Address System	N/A	N/A	N/A
	Automatic Sprinkler System		Provided	MR
	1) Basement	Yes		N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false ceiling	N/A	N/A	IN/A
1.	Internal Hydrants	77/4	N/A	N/A
	1) Size of riser/down-comer	N/A	N/A N/A	N/A
	2) Number of hydrants per floor	N/A	N/A	N/A
	3) Hose box	N/A	IN/A	14/21
12.	Yard Hydrants	DT/A	N/A	N/A
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	IN/A	14/21
	Pumping Arrangement	3. 1		
•	1) Ground level	N/A	N/A	N/A
	-)	N/A	N/A	N/A
	,	N/A	N/A	N/A
		N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual stopping	N/A	N/A	N/A
	2) Terrace level		6	17.00
	a) Discharge of pump	450 LPM	Provided	MR
	b) Head of pump	35 mtr.	Provided	MR
	c) Power supply	Yes	Provided	MR
	d) Auto starting of pump	Yes	Yes	MR
	Captive Water Storage for Fire Fight	ing	F K-	
14.	Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	Yes	Provided	MR
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	5,000 ltrs.	5,000 ltrs.	MR
5.	Exit Signage.	Yes	Provided	MR
·. i.	Provision of Lifts.			9
10.	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	Yes	Provided	MR
				3.00
	e) Lift signage	Yes	Provided	MR
7.	Stand by Power Supply	Yes	D.G. Set	MR
18.	Refuge Area	N/A	N/A	N/A
***************************************	Total area location	N/A	N/A	N/A
9.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
	Special Fire Protection System for I		' I D'-1- if any	N/A

The fire protection system provided in the building were checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rules 35 of the Delhi Fire Service Rules 2010/

Accordingly DFA is put up please

Signature of the inspecting officer

Signature of the inspecting officer

Name

Designation

Name: - S.S.Kaushik.

Designation:- Assistant Divisional Officer.

1) South

>6/9/W