GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO.F6/DFS/MS/GH/2012/ 3 9 / 5

Dated: 19/10/12_

FIRE SAFETY CERTIFICATE

Certified that M/s Arina Inn located at 38, Netaji Subhash Marg, Daryaganj, New Delhi comprised of ground floor (Bank), first floor (Reception + 09 guest rooms), second floor (10 guest rooms), third floor (10 Guest rooms) and terrace floor (01 store room) have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi fire service Rules 2010 and verified by the officer concerned of Delhi fire service on 09.16..2012 in presence of Mohd. Tariq Anjum, Manager of the guest house and that the building/premises is fit for occupancy class residential (Guest house) for 29 guest rooms with effect from 19/10/12 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 19/10/12 at New Delhi by.

Chief Fire Officer Delhi fire service

Copy to: -

1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delh

2. The Manager, M/s Arina Inn, 38, Netaji Subhash Marg, Daryaganj, New Delhi w.r.t. letter No. 47595-98/Addl.C.P/Lic(H) dated 30-07-2012

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

m

INSPECTION REPORT

1.	Name & address of the building Type of Occupancy	: Anina	a Inn, 38,1	Vetaji Subhash n	rarg, Danya Gan
2.	Type of Occupancy	: Lodging	House / Eating Ho	ouse / Club Men	Delhi Delhi
3.	Type of Case	: Renewa	l / New case		
4.	Details of previous NOC	: Letter N	0.	Dated	0
5.	Fire Safety directives letter No				
	Date of inspection	****	110/2012	3	
7.	Name of the Inspecting Officers	s: M.K.C	hattopadhyay, AD	O(HQ)	- 2
8.	Name and designation of office	rs	N.	PITA	arim Manases
	from the building side	:		And. Tariff Ar	9400
9.	Year of Construction	: <u>be</u>	Fore 1960		1.1.7.7.001
10	. Applicant's letter No.			Addl.c.p (4°C(H)	
S.	Minimum Standards on f		NBC	Provided at site	Remarks
No.	prevention and fire safety U	/R 33	Requirement		MR/NMR
1	Access to building			"Somt (APP)	7.40
	 Road width 		spl. area.	Main Subhash Masq Directly accessible	MR
	• Gate width		-	from the road	MR
	• Width of internal road		N/A	N/A	
2	Number, Width, Type & Arra	ngement	of Exits		
A-2	a. Number of staircases		- Carrieran	-	-
	Upper Floors		01	01	MR (Spl. Orea)
	Basements		N/A	N/A	
	b. Width of staircases		•		
	Upper Floors		0.80mt	1.05 2001	MR
	Basements		N/A	N/A	NAME AND ADD THE REAL PROPERTY.
	c. Protection of exits		N/A	N/A	NAME AND ADDRESS A
	Fire check door		N/A	N/A	
	 Pressurization 		N/A	N/A	MA CO
Service of the servic	e. No. of continuous staircases t	o terrace	01	01	MR
	g. Width of Corridor		N/A	N/A	ONE AND SALE THAT THAT THAT THAT THAT THAT THAT
	h. Door Size		N/A	N/A	
	*		N/A	N/A	
3	Compartmentation.		Not required	MA	* * * * * * * * * * * * * * * * * * * *
	Fire check door		N/A	N/A	

GF + Bank

[st - Reception + 09 gust rooms.

2nd - 10 gust rooms

3nd - 10 Gust rooms

Therrage - 01 store room

y

	Sealing of electrical shafts	N/A	N/A		
	• Fire Rating of shaft door	N/A	N/A		
	Water Curtain	N/A	N/A		
	Fire Dampers	N/A	N/A		
4	Smoke Management System.				
	 Basements 	30 a/c per hour	N/A	N/A	
	Upper floors	12 a/c per hour			
		<u></u>	N/A	N/A	
5	Fire Extinguishers				
	• Total numbers 08		provided	MR	
	• Types ABC & Waler CO2		provided	MR	
	• IS marking	ISI marked	provided	MR	
6	First-Aid Hose Reels.				
	Total numbers on each floor	01	provided	MR	
	 Length of hose reel hose 	30 m	provided	MR	
	Nozzle diameter	5 mm	provided	MR	
7	Automatic fire detection and alarming system.				
	Type of detectors	N/A	N/A	100 MI	
	Location of Main Panel	N/A	N/A	THE RES THE THE WAY AND JOY AND THE RES SAN	
	• Location of Repeater Panel	N/A	N/A	THE SEC SEC SEC SEC SEC SEC SEC SEC SEC SE	
	Alternate source of power	N/A	N/A	(100 ME) 125 CEC CEC ME NO 100 ME NO 100 ME	
	Hooters' Location	N/A	N/A	700 NEW WIND NEW WIN AND AND AND AND AND	
8	MOEFA		* .		
9	Public Address System.		E		
10	Automatic Sprinkler System.				
	• Basement	N/A	N/A	. CON DOM DOM SAND SAND SAND SAND SAND SAND SAND	
	Upper Floor	N/A	N/A		
	Sprinkler above false ceiling	N/A	N/A		
11	Internal Hydrants				
	Size of riser/down-comer	N/A	N/A		
	Number of hydrants per floorHose Box	N/A	N/A		
		N/A	N/A		
		The second secon		and the second s	

N

	Yard Hydrants.			
	 Total number of hydrants 	N/A	N/A	
	Hose Box	N/A	N/A	500 MD
13	Pumping Arrangements.			
	Ground Level	N/A	N/A	
	Discharge of main Pump	N/A	N/A	NV
Wildelick Special water	Head of Main pump	N/A	N/A	20 At the second of the second
	Number of main pumps	N/A	N/A	OFF SET OUT OUT OUT OUT OUT OUT OUT
	Jockey Pump out put	N/A	N/A	TO BE UNITED THE COLUMN THE COLUMN THE
	Jockey pump head	N/A	N/A	500 ADV 400 ESS 500 100 100 100 100
	Standby Pump out put	N/A	N/A	770 470 470 470 470 470 470 470 470 470
	Standby Pump Head	N/A	N/A	
	Auto Starting/ Manual	N/A	N/A	
	stopping Pump House Access	N/A	N/A	
er (Pennis Park Stramman average	Terrace level	*		
market state of the state of th	Discharge of pump	225 LPM	225 LPM	MR
	Head of the pump	25 m/r	25 mt	MR
	Power Supply	-		
	Auto Starting of pump	Reguired	poovided	MR
14	Captive Water Storage for fire fightin	g.		14
	 Underground tank capacity 	N/A	N/A	
	Draw-off connection	N/A	N/A	SEC AND AND AND AND AND ANY AND LOSS AND AND
	Fire service inlet	N/A	N/A	AT THE U.S. AND AND AND AND AND AND AND
SARRAMANANANANANANANANANANANANANANANANANA	Access to tank	N/A	N/A	All All 40 40 40 40 10 40 50 40 50
	Overhead Tank capacity	2500 lbs	5000 lb	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.			
	 Pressurization of Lift Shaft 	N/A	N/A	10 to 10 to 10 to 10 to 10 to 10 to
	• Pressurization of Lift lobby	N/A	N/A	
	• Communication In lift Car	N/A	N/A	TO 50 NO NO SO NO
	• Fireman's Grounding Switch	N/A	N/A	

N

	Lift Signage	N/A	N/A	
17	Standby power supply	N7A	MA	- 1
8	Refuge Area.			
	> Total Area	N/A	N/A	Many and the time time time time time time time tim
	> Location	N/A	N/A	100 MB 100 MB 100 MB 100 MB 100 MB 100 MB 100
19	Fire Control Room			
	Detector System Panel	N/A	N/A	PO 500 00 00 00 00 00 00 00 00 00 00 00 00
	• Flow Switch Panel	N/A	N/A	City and other case case case case case case
	 PA System Panel 	N/A	N/A	The first had him had the one one was
	Batter backup	N/A	N/A	
	Building Floor Plans	N/A	N/A	one see the late of the late o
0.0	Special Fire Protection Systems for Protection of special Risks, if any:	Reguired	provided near Elect panel One ABC lippe feri exterpurstur	MR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to /grant / renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

> Signature of the Inspecting Officer Name (M.K. CHATTOPADHYAY) Designation: - Assistant Divisional Officer

Dolco)
Submitte d please.
Dy eff (NDZ)
15/x11