FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [SEE SUB-RULE (1) OF RULE 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. 66/DFS/ens/9H/2012/3929

Dated: 19 //o /2012

FIRE SAFETY CERTIFICATE

Issued on. 19/10/12 at New Delhi by

Chief Fire Officer Delhi Fire Service

8/C N

Copy to:

Mr. Taneja
 Guest House located at 8-B/10, Sector-15, Rohini Delhi

2. Addl C.P. of Police (Lic.)

1st floor, PS Defence Colony

Note:- For general fire safety directives please over leaf.

Following fire safety directives must be adhered to:-

- 1) All the fire safety arrangement provided their in shall be maintained in good working g conditions at all time.
- 2) Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3) The trained fire fighting staff should be available round the clock.
- 4) Any deviation, with regards to construction etc shall be verified by the concerned building sanctioning agency.
- 5) The basement shall be used strictly as per the provision of building Bye-Laws.
- 6) This certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. This is available on www.dfs.delhigovt.nic.in

May Kindly peruse letter no.54246/Addl.C.P./Lic(H) dated 14/09/2012 received from Addl CP, regarding renewal of NOC in r/o Sunrise Guest House located at 8-B/10, Sector-15, Rohini Delhi. Accordingly premises was inspected & observed that the building comprised Basement, ground floor & three upper floor. Fire safety arrangements are put up on the prescribed Performa:.

1. Name &address of the building : Sunrise Guest House located at 8-B/10, Sector-15, Rohini Delhi

2. Type of Occupancy : Class-A-1 (i) Residential

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/GH/09/3844 dated 18/02/2009

5. Fire Safety directives letter No. : nil

6. Date of inspection : 08.10.2012

7. Name of the Inspecting Officers : D.O. (MN)

8. Name and designation of officers

1

From the building side : Mr. Taneja

9. Year of Construction :

10. Applicant's letter No. : 54246/Addl.C.P./Lic(H) dated 14/09/2012

INSPECTION REPORT

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	BBL Requirement	Provided at site	Remarks MR/NMR	
1.	Access to building				
	Road width	06mtrs	12 mtr	M.R.	
	Gate width	4.5 mtr	More than 5 mtr	M.R.	
	Width of internal road	N.R. Old case	Abutting road from 3 side	M.R.	
2.	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases	1			
	Upper Floors	2	2	M.R.	

Basement	2	2	M/R
b. Width of staircases			
Upper Floors	1.25 mtr	1.25 & 100 c.m.	Old case M.R.
• Basement	1.25 mtr	1.25 & 100 c.m.	Old case M.R.
c. Protection of exits			
Fire check door	N.R.	N.R.	N.R.
Pressurization	N.R.	N.R.	N.R.
d. No. of continuous staircases to terrace			
e. Width of Corridor	1 mtr	1 mtr appr.	M.R.
f. Door size	1 mtr	1 mtr	M.R.
Compartmentation.		1	
Fire check door	N.R.	N.R.	N.R.
Sealing of electrical shafts	N.R.	N.R.	N.R.
Fire Rating of shaft door	N.R.	N.R.	N.R.
Water Curtain	N.R.	N.R.	N.R.
,	N.R.	N.R.	N.R.
Fire Dampers			
Smoke Management System.			
Basements	required	Exhaust fan provided	Old case M.R.
Upper floors	N.R.	N.R.	N.R.
Fire Extinguishers			

l.	Internal Hydrants				
	Sprinkler above false ceiling	No false ceiling	N.R.	N.R.	
	Upper Floor	N.R.	N.R.	N.R.	
	Basement	Required	Provided	M.R.	
10.	Automatic Sprinkler system				
).	Public Address System.	N.R.	N.R.	N.R.	
8.	MOEFA	Required	Provided	M.R.	
-	Hooter's Location	IV.R.	19.14.	IV.N.	
	Alternate source of power	N.R.	N.R.	N.R.	
	Location of Repeater Panel	N.R.	N.R.	N.R.	
		N.R.	N.R.	N.R.	
		N.R.	N.R.	N.R.	
	Type of detectors	N.R.	N.R.	N.R.	
7.	Automatic fire detection and alarming system.				
	Nozzle diameter	5 mm	provided	M.R.	
	Length of hose reel hose	30 m	Provided	M.R.	
	Total numbers on each floor	1	1	M.R.	
6.	First-Aid Hose Rees.		-		
	IS marking	ISI marks	provided	M.R.	
	• Types	ABC & CO ₂ type	ABC & CO ₂ type	M.R.	
	Total numbers	6	10	M.R.	

3.50	Size of riser/down-comer	100 mm	Provided	M.R.
	Number of hydrants per floor	1	Provided	M.R.
	Hose Box	1	Provided	M.R.
12.	Yard Hydrants.			
	Total number of hydrants	N.R	N.R.	N.R.
	Hose Box	N.R	N.R.	N.R.
13.	Pumping Arrangements.		1	F
	Ground Level			
	> Discharge of main pump	N.R	N.R	N.R
	➤ Head of Main pump	N.R	N.R	N.R
	> Number of main pumps	N.R	N.R	N.R
	> Jockey Pump out put	N.R	N.R	N.R
	> Jockey pump head	N.R	N.R	N.R
	> Standby pump out put	N.R	N.R	N.R
	> Standby pump Head	N.R	N.R	N.R
	Auto Starting/Manual stopping	N.R	N.R	N.R
	> Pump Hose Access	N.R	N.R	N.R.
	Terrace level			
	Discharge of pump	450 LPM	provided	M.R.
charles from the same and the same charles	➤ Head of the pump	45 mtr	Provided	M.R.

Power supply	Required	Provided	M.R.
Auto Starting of pump	Required	Provided	M.R.
Captive Water Storage for fire fi	ghting.		
Underground tank capacity			
Draw -off connection	N.R	N.R	N.R
Fire service inlet	N.R	N.R	N.R
Access to tank	N.R	N.R	N.R
Overhead Tank Capacity	10,000 ltr	Provided	M.R.
Exit Signage.	Required	Provided	M.R.
Provision of Lifts			,
Pressurization of Lift Shaft	N.R	N.R	N.R
Pressurization of Lift lobby			N.R
Communication In lift Car	N.R	N.R	N.R
• Fireman's Grounding Switch	N.R	N.R	N.R
• Lift Signage	N.R	N.R	N.R
Standby power supply	N.R	N.R	N.R
Refuge Area			
> Total Area	N.R.	N.R.	N.R.
> Location	N.R.	N.R.	N.R
	Captive Water Storage for fire fit Underground tank capacity Draw -off connection Fire service inlet Access to tank Overhead Tank Capacity Exit Signage. Provision of Lifts Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area Total Area	Captive Water Storage for fire fighting. Underground tank capacity Draw -off connection N.R Fire service inlet N.R Access to tank Overhead Tank Capacity Exit Signage. Provision of Lifts Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply N.R Refuge Area N.R.	Captive Water Storage for fire fighting. Underground tank capacity Draw -off connection N.R

19.	Fire Control Room	*		
	e e	N.R	N.R	N.R
	Detector System Panel		v.	
		N.R	N.R	N.R
	Flow Switch Panel			
	> PA system Panel	N.R	N.R	N.R
	7 Tri system Taner			
	> Batter backup	N.R	N.R	N.R
	P Batter backup	7		
	➢ Building Floor plans	N.R	N.R	N.R
2.7	Daniang From praise			
20.	Special Fire Protection Systems	N.R	N.R	N.R
	for			
	Protection of special Risks, if any:			
				(

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/

Signature of the Inspection Officer

Signature of the Inspection Officer

Name Sunil Chowdhary

Name

Designation D.O.

Designation

9-1,CF.0 -

Verital 1/12

Fit is port up for signature plans