GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, CONNAUGHT PLACE, NEW DELHI-110001

No. F6/MS/DFS/GH/2012/ 3995

Dated: 25/10/12

FIRE SAFETY CERTIFICATE

> CHIEF FIRE OFFICER DELHI FIRE SERVICE

Copy to :-

- 1. The Addl. Commissioner of Police (Lic.), First Floor, P.S. Defence Colony New Delhi–110049 w.r.t. letter No.44157/Addl.C.P./Lic.(H) New Delhi dated 12-07-12
- 2. M/s Mayur Guest House, 5611-18, Basant Road, Pahar Ganj, New Delhi-110055.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

Mayur Guest House, 5611-18, Basant Road, Pahar Ganj, New Delhi-110055

INSPECTION REPORT

1. Name & address of the building : Mayur Guest House, 5611-18, Basant Road, Pahar Ganj, New

Delhi-110055

2. Type of Occupancy : Lodging House

3. Type of Case : Renewal

4. Details of previous NOC : Letter No. F6/DFS/MS/GH/2009/2875 Dated 23- 9-2009

5. Fire Safety directives Letter No. : N/A

6. Date of inspection : 16-10-2012

7. Name of the Inspecting Officer : Sh. D.S. Yadav (A.D.O.)

8. Name and designation of Officer

from the building side : Smt. Kamlesh Bagga (owner)

9. Year of Construction : 2001 Starting Year

10. Applicant's letter No. : 44157/Addl.C.P./Lic.(H) dated New Delhi the 12-07-2012

S No	Minimum standards on fire prevention	BBL	Provided at site	Remarks MR/NMR		
	and fire safety U/R 33	Requirements	(PSS Area)	(Old Case)		
1.	Access of building					
	 Road width 	N/A	6 mtrs. Approx.	MR		
	Gate width	N/A	N/A	N/A		
	 Width of internal road 	N/A	N/A	N/A		
2.	Number, width, Type & Arrangements of exits					
	a. Number of staircases					
	Upper floors	01	01	MR		
	 Basements 	N/A	N/A	N/A		
	b. Width of staircases					
	Upper floors	80 cms	81 cms.	MR -		
	 Basements 	N/A	N/A	N/A		
	c. Protection of exits					
	Fire check door	N/A	N/A	N/A		
	 Pressurization 	N/A	N/A	N/A		
	d. No of continuous staircase to	01	01	MR		
	terrace					
	e. Width Of Corridor	N/A	N/A	N/A		
	f. Door Size	N/A	N/A	N/A		
3.	Compartmentation					
	 Fire check door 	N/A	N/A	N/A		
	 Sealing of electrical shafts 	N/A	N/A	N/A		
	 Fire Rating of shaft door 	N/A	N/A	N/A		
	 Water Curtain 	N/A	N/A	N/A		
	 Fire Dampers 	N/A	N/A	N/A		
4.	Smoke managements System					
	• Basements	30 a/c per hour	N/A	N/A		
	 Upper floors 	12 a/c per hour	Natural ventilation	MR		
5.	Fire Extinguishers					

N/12

1110	 ayur Guest House, 5611-18, Basant R Total numbers 	08	08	MR
	• Types		Water Co2 & A.B.C. type.	MR
	IS marking	ISI marked	Provided	MR
	First – Aid Hose Reels			
	Total numbers on each floor	0.1	01 at 1 st floor	MR
	 Length of hose reel hose 	30 M	Provided	MR
	Nozzle diameter	5 mm	Provided	MR
	Automatic fire detection and alarming sy	vstem		
	Type of detectors	N/A	N/A	N/A
	 Location of Main Panel 	N/A	N/A	N/A
	 Location of Repeater Panel 	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
	 Hooters' Location 	N/A	N/A	N/A
	MOEFA	N/A	N/A	N/A
	Public Address System	N/A	N/A	N/A
	Automatic Sprinkler System			
	Basements	N/A	N/A	N/A
	Upper Floor	N/A	N/A	N/A
	Sprinkler above false ceiling	N/A	N/A	N/A
	Internal Hydrants			
	Size of riser/down- comer	N/A	N/A	N/A
	Number of hydrants per floor	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
2.	Yard Hydrants	Jan 1869 1897		
	Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
3.	Pumping Arrangements			
).	Ground Level			
	 Discharge of main pump 	N/A	N/A	N/A
	Head of main pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
	> Jockey pump out put	N/A	N/A	N/A
	Jockey pump head	N/A	N/A	N/A
	Standby Pump out put	N/A	N/A	N/A
	> Standby Pump Head	N/A	N/A	N/A
	> auto Staring/Manual stopping	N/A	N/A	N/A
	Pump House Access	N/A	N/A	N/A
	Terrace level			
	Discharge of pump	180 LPM	180 LPM	MR
	Head of the pump	30 Mtrs.	30 Mtrs.	MR
	Power supply	Electric	Electric	MR
	➤ Auto starting of pump		Switch provided at reception	MR
4.	Captive water Storage for fire fighting			0
	Under ground tank capacity	N/A	N/A	N/A
	> Draw of connection	N/A	N/A	N/A
	> Fire service inlet	N/A	N/A	N/A
	Access to tank	N/A	N/A	N/A /
	 Overhead Tank capacity 	2500 Ltrs.	2500 Ltrs.	MR 🗸
15	Exit Signage	Yes	Provided	MR
16.	Provision of Lifts			
10.	> Pressurization of Lift Shaft	N/A	N/A	N/A
	> Pressurization of lift lobby	N/A	N/A	N/A

Mayur Guest House, 5611-18, Basant Road, Pahar Ganj, New Delhi-110055

	Communication in lift Car			
		N/A	N/A	N/A
	Fireman's Grounding Switch	N/A	N/A	N/A
1.7	➤ Lift Signage	N/A	N/A	N/A
17.	Standby power supply	YES	D.G. Set	MR
18.	Refuge Area	5	2.0.000	IVIK
	Total area	N/A	N/A	N/A
1.0	> Location	N/A	N/A	N/A
19.	Fire control room			IVA
	Detector system panel	N/A	N/A	N/A
	Flow Switch PanelPA System Panel	N/A	N/A	N/A
	Batter backup Building Floor Plans	N/A	N/A	N/A
		N/A	N/A	N/A
10		N/A	N/A	N/A
20.	Special Fire Protection Systems for Protection of special Risks, if any;	N/A	N/A	N/A

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name

Designation

Name D.S. Yadav Designation ADS (C.D)

Submitted please.