FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE
[SEE SUB-RULE (1) OF RULE 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DB) ms/motel/2012/4008

Dated: 25/10/2012

## FIRE SAFETY CERTIFICATE

Issued on. 25 10 12 at New Delhi by

Chief Fire Officer Delhi Fire Service

Me

Copy to:

Sh. Mittal

Khasra no.66/2, 66/9, 66/12, 66/22, situated at Pooth Khurd, Delhi (Motel),

Note:- For general fire safety directives please over leaf.

Following fire safety directives must be adhered to:-

- 1) All the fire safety arrangement provided their in shall be maintained in good working g conditions at all time.
- 2) Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3) The trained fire fighting staff should be available round the clock.
- 4) Any deviation, with regards to construction etc shall be verified by the concerned building sanctioning agency.
- 5) The basement shall be used strictly as per the provision of building Bye-Laws.
- 6) This certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. This is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

(Lis Ram Parkash)

May Kindly peruse letter no.nil dated 04/09/12 received from the Sh. Suresh Chand Garg., regarding of NOC in r/o Khasra no.66/2, 66/9, 66/12, 66/22, situated at Pooth Khurd, Delhi. It was observe that the building is comprised of basement, ground plus one upper floor & plot area of 152/257.57m. Premises was inspected by the undersigned & the fire safety arrangements are put up on the prescribed Performa.

1. Name &address of the building : Khasra no.66/2, 66/9, 66/12, 66/22, situated at Pooth Khurd,

Delhi (Motel)

2. Type of Occupancy : Class-A-1 (i) Residential

3. Type of Case : New

4. Details of previous NOC : N.A.

5. Fire Safety directives letter No. : F6/MS/DFS/BP/GH/2007/156 dated 17-01-2007

6. Date of inspection : 12.10.2012

7. Name of the Inspecting Officers : Divisional Officer Sunil Chawdhary

8. Name and designation of officers

From the building side : Mr. Mittal

9. Year of Construction : 2007-2008

10. Applicant's letter No. : nil dated 04/09/2012

## **INSPECTION REPORT**

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	BBL Requirement	Provided at site	Remarks MR/NMR
1.	Access to building			
	Road width	12 mtrs	24.39 mtr	M.R.
	Gate width	5 mtr	9 mtr	M.R.
	<ul> <li>Width of internal road</li> </ul>	6 mtr	Provided	M.R.
2.	Number, Width, Type & Arrange	ment of Exits		
	a. Number of staircases	8	Provided	M.R.
	Upper Floors	3	Provided	M.R.

r						
	• Basement	5	Provided	M.R.		
	b. Width of staircases	, 4				
	Upper Floors	1.25 mtr	Provided	M.R.		
	Basement	1.25 mtr	Provided	M.R.		
	c. Protection of exits					
Production and the second	Fire check door	Required	Provided	M.R.		
	<ul> <li>Pressurization</li> </ul>	Required	Provided	M.R.		
de de la companya de	d. No. of continuous staircases to terrace					
	e. Width of Corridor	2 mtr	Provided	M.R.		
3.	f. Door size  Compartmentation.	2 mtr	Provided	M.R.		
	Compartmentation.					
	Fire check door	Required	Provided	M.R.		
Activation and an article and a state of the	Sealing of electrical shafts	Required	Provided	M.R.		
	Fire Rating of shaft door	Required	Provided	M.R.		
	Water Curtain	N.R.	N.R.	N.R.		
	• Fire Dampers	Required	Provided	M.R.		
4.	Smoke Management System.					
	Basements	Required	Provided	M.R.		
	Upper floors	Required	Provided	M.R.		
5.	Fire Extinguishers					
	Total numbers	18	25	M.R.		
	• Types	ABC & CO <sub>2</sub> Required	Provided	M.R.		

	*				
	IS marking	ISI marks required	provided	M.R.	
6.	First-Aid Hose Rees.				
	Total numbers on each floor	3	Provided	M.R.	
	Length of hose reel hose	30 m required	Provided	M.R.	
	Nozzle diameter	5 mm required	Provided	M.R.	
7.	Automatic fire detection and alarming system.				
	Type of detectors	Smoke & Heat	Provided	M.R.	
	Location of Main Panel	Ground floor	Provided	M.R	
	Location of Repeater Panel	N.R.	N.R.	N.R	
	Alternate source of power	Required	Provided	M.R	
	Hooter's Location	All over	Provided	M.R	
8.	MOEFA	Required	Provided	M.R.	
9.	Public Address System.	∧/o† Required	No Provided	M.R.	
10.	Automatic Sprinkler system	4 00 10	2 2	1 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	
	Basement	Required	Provided	M.R.	
	Upper Floor	Required	Provided /	M.R.	
*	Sprinkler above false ceiling	celing.	THE M	NA.	
11.	Internal Hydrants	1			
	Size of riser/down-comer	150 mm	Provided	M.R.	

Number of hydrants per floor	3	3	M.R.	
Hose Box	3	3	M.R.	
Yard Hydrants.		,		
Total number of hydrants	8	9 Provided	M.R.	
Hose Box	8	9 Provided	M.R.	
Pumping Arrangements.				
Ground Level		1		
<ul> <li>Discharge of main pump</li> </ul>	2280 LPM	Provided	M.R	
➤ Head of Main pump	40 mtr	40 mtr	N.R	
> Number of main pumps	3	3	M.R.	
> Jockey Pump out put	220 LPM	Provided	M.R	
Jockey pump head	30 mtr	40 mtr	M.R	
> Standby pump out put	2280 LPM	Provided	M.R	
> Standby pump Head	30 mtr	40 mtr	M.R	
<ul> <li>Auto Starting/Manual stopping</li> </ul>	Required	Provided	M.R	
Pump Hose Access	Required	Provided	M.R	
Terrace level			a.	
<ul> <li>Discharge of pump</li> </ul>	N.R.	N.R.	N.R.	
➤ Head of the pump	N.R.	N.R.	N.R.	
> Power supply	N.R.	N.R.	N.R.	
	• Hose Box  Yard Hydrants.  • Total number of hydrants • Hose Box  Pumping Arrangements.  Ground Level  > Discharge of main pump  > Head of Main pump  > Number of main pumps  > Jockey Pump out put  > Jockey pump head  > Standby pump out put  > Standby pump Head  > Auto Starting/Manual stopping  > Pump Hose Access  Terrace level  > Discharge of pump  > Head of the pump	floor  Hose Box  Total number of hydrants  Hose Box  Hose Box  Fumping Arrangements.  Ground Level  Discharge of main pump  Head of Main pump  Number of main pumps  Jockey Pump out put  Jockey pump head  Standby pump head  Standby pump Head  Auto Starting/Manual stopping  Pump Hose Access  Terrace level  Discharge of pump  N.R.  Head of the pump  N.R.	floor Hose Box  Hose Box  Total number of hydrants Hose Box  Total number of hydrants Hose Box  Frovided  Pumping Arrangements.  Ground Level  Discharge of main pump Head of Main pump  Number of main pumps  Jockey Pump out put  Jockey Pump out put  Standby pump out put  Standby pump Head  Material Standby Provided  Required  Provided  Provided  Provided  Required  Provided  Provided  Provided  Required  Provided  Provided  Provided  Provided  N.R.  N.R.	

	➤ Auto Starting of pump	N.R.	N.R.	N.R.
4.	Captive Water Storage for fire fig	ghting.		
			T	
	Underground tank capacity	100,000	provi ded	M.R.
	D 00	N.R.	N.R.	N.R.
	Draw -off connection	N.R.	N.R.	N.R.
	Fire service inlet			N.R
	> Access to tank	Required	Provided	
	<ul> <li>Overhead Tank Capacity</li> </ul>	10,000	Provided	M.R.
15	Exit Signage.	Required	Provided	M.R.
16.	Provision of Lifts			
				T
	Pressurization of Lift Shaft	N.A	N.A	N.A
	Pressurization of Lift lobby	N.A	N.A	N.A
	Communication In lift Car	NI A	1.7%	
		N.A	N.A	N.A
	Fireman's Grounding     Switch	N.A	N.A	N.A
	Lift Signage	N.A	N.A	N.A
17.	Standby power supply	Required	Provided	M.R
			^ 4	
8.	Refuge Area	A Fo	il <sup>2</sup> 8	9
	T (14	N.R.	N.R.	N.R.
	> Total Area		e g	
	> Location	N.R.	N.R.	N.R.
19.	Fire Control Room	7	,	
	Detector System Panel	7	0 2 2 2 2	ina.
	-	Regnixed	Jor; ded	M.R.

	Flow Switch Panel	N.R.	N.R.	N.R.
		N.R.	N.R.	N.R.
	➤ PA system Panel	N.R.	N.R.	N.R.
2	➢ Batter backup	N.R.	N.R.	N.R.
	> Building Floor plans			
20.	Special Fire Protection Systems for	N.R.	N.R.	N.R.
	Protection of special Risks, if any:			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/. Owner how made minor changes inside the building. Fire safely are inside the building. Fire safely are inside the building this alteration is never the rules. It is recommended to grant Fire safely are minor changes inside the building this alteration is never to this alteration.

Signature of the Inspection Officer

Signature of the Inspection Officer

Name Syml ( Waw of Wo)

Name

Designation Designation

Designation