GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DFS/MS/school/2012/4242

FIRE SAFETY CERTIFICATE

Certified that the M.C.Primary Boys School at Ram Nagar, New Delhi-55, comprised of ground plus one floor owned/occupied by M.C.Primary School have complied with the fire prevention and fire safety requirements in accordance with the circular issued by the Director of Education dtd.01.03.2011and verified by the officer concerned of this department on 11.10.2012 in the presence of Sh.Partap Singh, Principal, of the school and that the building is fit for occupancy class 'B' Educational Building' with effect from 19.111.2012... for a period of three years, subject to conditions printed overleaf.

Chief Fire Officer Delhi Fire Service

ofc Mu

Τo,

The Principal M.C.Primary Boys School,2nd Shift, Ram Nagar Old, New Delhi-55.

Copy to:-

 The Director of Education North Delhi Municipal Corporation Civic Centre ,New Delhi.

 The Principal M.C.Primary Girls School, 1st Shift, Raam Nagar Old, New Delhi-55.

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: MC Primary Boys School at Ram Nagar, New Delhi -55.

2. Building is comprised of

: Ground +1, upper floor.

3. Type of Occupancy

: Educational

4. Type of Case

: New Case

5. Details of Previous NOC letter :Nil

6. Fire Safety direction letter No : Circular Director of Education dated 1.3.11

7. Date of Inspection

: 11.10.12

8. Name of the Inspecting officers: DO Virendra Singh

9. Name and designation of Officer:

from the building side

: Sh.Partap Singh (Principal).

10. Year of Construction

-: 1950

11. Applicant's letter No

: letter No.Nil. dd. 11/10/12

Minimum Standards on fire	Circular	Provided at	Remarks			
prevention and fire safety U/R33	Requirement	Site	,			
Access to building						
Road width		6 Mtrs.	MR			
			ONE COM COM COM COM COM COM COM			
 Width of internal road 						
Number, Width, Type and Arrangement of Exits						
	01 No.	01 No.	MR			
Upper Floor	01 No.	01 No.	MR			
Basement						
B. Width of Staircases		9				
Upper Floor	1.5 M	1.5 M	MR .			
	2					
• Basement						
Protection of exits Fire check door			3			
e. No. of continuous staircases to		1No.	MR			
terrace	1.5 M.	1.5 M	MR -			
h. Door Size	1.0 M	1.0 M	MR /			
Compartmentation.						
Fire check door						
 Sealing of electrical shafts 						
	and and deli set over over the size and and the					
Water curtain						
Fire Dampers						
Smoke Management System.						
Smoke Management System.						
	Access to building Road width Gate width Width of internal road Number, Width, Type and Arrangement Number of Staircases Upper Floor Basement B. Width of Staircases Upper Floor Basement C. Protection of exits Fire check door Pressurization E. No. of continuous staircases to terrace G. Width of Corridor Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire Dampers	prevention and fire safety U/R33 Requirement Access to building Road width Gate width Width of internal road Number, Width, Type and Arrangement of Exits Number of Staircases Upper Floor Basement B. Width of Staircases Upper Floor Basement C. Protection of exits Fire check door Pressurization e. No. of continuous staircases to terrace g. Width of Corridor h. Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire Dampers	prevention and fire safety U/R33 Requirement Site Access to building Road width Gate width Width of internal road Number, Width, Type and Arrangement of Exits A. Number of Staircases Upper Floor Basement B. Width of Staircases Upper Floor Basement C. Protection of exits Fire check door Pressurization E. No. of continuous staircases to terrace G. Width of Corridor D. Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire Dampers Requirement Site Access to Mtrs. 6 Mtra 6 Mtrs. 6 Mtra 6 Mtr			

		T				
	Upper floor					
5.	Fire Extinguishers	0.11	0.11	MD		
	Total numbers	2 Nos.	2 Nos.	MR «		
	• types	ABC & Co2	Provided	MR		
	IS marking	ISI marked	Prrovided	MR		
6	First-aid-Hose Reels.					
	Total numbers of each floor	and the tips to the tips and the tips and the tips and the tips	des des des site leis site del del del del des des	the fee also also had been took took took one		
	 Length of hose reel hose 		1, 1	1		
	Nozzle diameter					
	- A4 A1			****		
	g = 10 - 10					
7 .	Automatic fire detection and alarming system.					
	Type of detectors					
	Type of detectors					
	Location of main panel					
	Location of main panel					
	Location of repeater panel					
	Location of repeater paner					
	Alternate source of power					
	Alternate source of power					
	Hooter's location	-				
8	Hooter's location MOEFA					
			W 100 COL			
9	Public address System.	No. 100 100 100 100 100 100 100 100 100 10	Total team made and place and anno sees total team			
10	Automatic Sprinkler System.					
	Basement					
æ	upper floor					
	sprinkler above false ceiling	POS 1008 1005 COM				
11	Internal Hydrants			1 (144) y and 14 (177) (177) (177) (177) (177) (177)		
	size of riser/down-comer					
				On the same can be see the last too same same		
	Number of hydrants per floor					
	Hose Box	the field dear data and that after the tally tally tally tally belong to				
12	Yard Hydrants.		1			
	Total number of hydrants					
	Hose Box					
13	Pumping Arrangements.					
10	Ground Level					
	Head of Main Pump			10 10 10 10 10 10 10 10 10 10 10 10 10 1		
	> Number of main pumps	\$40 000 004 004 004 004 004 009 109 109 109 009 009 009		THE SEC COL COL COL COL COL COL COL COL COL		
	> Jockey pump out put	THE SEA AND ADD AND THE SEA AND THE SEA AND THE SEA	NA ANA AND NO POS (SS 500 NO AND AND AND AND AND			
	> Jockey pump head		NOT AND			
	> Standby pump out put					
	> Standby pump Head					
	Auto Starting /Manual					
	stopping					
	Pump House Access					
	 Terrace Level 			MET THE THE SEA AND THE SEA AN		

	Head of the Pump	NAS AND SAN AND AND AND AND AND AND AND AND		
	Power supply			
	()			
167	Auto Starting of pump			
	A STATE OF THE STA	a salahir		
14	Captive Water Storage for Fire Fighting.		i	
	 Underground tank capacity 			
	Draw-off connection			
79.6 7	Fire service inlet			
	Access to tank			
	 Overhead Tank capacity 		=	
15	Exit Signage.			
16	Provision of Lifts.		5 9 5 1 8	
	 Pressurization of Lift Shaft 			
	 Pressurization of Lift lobby 			
	 Communication in lift car 			
	 Firemen's grounding switch 			
	Lift Signage			
17	Standby power supply	2 am and an and an are the same and an are the		
18	Refuge Area.		Alle data gate que san terr selv san selv del del des des cer selv selv	
	Total area			
	Location			
19	Fire Control Room			
	 Detector system panel 	App. Ann. (and (and care care care care care care care care		
	Flow switch panel			
	PA system panel			
	Battery backup			
	Building Floor Plans			
20	Special Fire Protection systems for protection of special Risks, if any:			

The fire extinguhers provided in the building were tested/checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Signature of the Inspecting Officer

Name VIRENDRA SINCIN Delhi Fire Service Rule 2010.