GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI – 110001

No: F 6/DFS/MS/2012/ 9 cheel/ 42 30

Dated:- 12/11/12

| FIRE | SAF | ETY | CERT | IFICATE | : |
|------|-----|-----|------|---------|---|
|------|-----|-----|------|---------|---|

| Certified that the Govt Co-Ed Sarvodya Vidyalaga Sawada (44EWRA) Colony A Block Dellin comprised of Gove Control |
|--|
| Clony A Block Delai comprised of Ground + one |
| who as from owned/occupied by The same of the same |
| Complied with the fire prevention and life |
| |
| verified by the officer concerned of Fire Service on 3.//2 in the presence of the concerned of that the building/premises is fit for occupancy |
| huilding with effect from |
| To see year in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under |
| Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service |
| Rules, 2010. |

Issued on 12 11 12 at New Delhl.

Chief Fire Officer
Delhi Fire Service

0/C. 8/m

Copy to:-

· W

1 The frincipal
Covt- Co. Ed Sarvodya School
Shawade (Shewer) Colony
A-Block Delh

2 The Disector of Edu.
Old Sectt Cort by very Delhi
Delhi

Note:-This fire safety certificate is subject to compliance of the condition printed over leaf.

1. All the means of escape shall be kept free of all type of obstruction all the time in

2. All the employees shall be acquainted with the use and maintenance of a fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non — functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.

5. Basement shall be used as per HBC

6. This NOC may not be treated in any case for regularizations of unauthorized construction, if any.

The owner occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

| Name & address of the building Grevi | t. Co. Ed. Sari | odayavidya laza | , Shavola Ghev |
|--|---------------------------|------------------|--|
| . Type of Occupancy: Educati | anas | Colony A-B | lock, Deshi- |
| . Type of Case : New | Case/ R enewal | | |
| . Details of previous NOC : Letter | No | ViL Date | d: |
| Fire Safety directives letter No :Circ | ular, Dir. o | f Edun. 1-3- | 2011 |
| Date of inspection: 31-10 | -2012 | | |
| Name of the Inspecting Officers: | 0-SHYAM | LAL | |
| Name and designation of officers | C. S. 1/2000 | (Privational) | |
| from the building side : | · 3 2 VENVICE | (18)MG pai) | |
| Year of Construction: 200 | 7, Grannos | + one upper | floor) |
| Applicant's letter No. :93 | 7 dated 13- | 9-2012 | participation of the state of t |
| Minimum Standards on fire | Circular, Dir. o | Provided at site | Remarks |
| prevention and fire safety U/R 33 | Requirement | | MR/NMR |
| Access to building | | | |
| Road width | Accessible | 9 m | MIR |
| Gate width | -11- | 5.30 m/ | miR |
| Width of internal road | NIA | NIA | |
| Number, Width, Type & Arrangement | t of Evits | 3 | |
| a. Number of staircases | 2 | 2 | mla |
| Upper Floors | 2 | 2 | MIR |
| Basements | NiL | Niz | NiZ |
| b. Width of staircases | 14) | 14)2 | 79) |
| Upper Floors | 1 ~ | 1.50 m (Each) | miR |
| Basements | 1.5 m | 1.52 m (Each.) | |
| c. Protection of exits | NiL | Ns'L | MIL |
| Fire check door | | | |
| Pressurization | N/R | N/P | N/A |
| | N/R | N/P | · N/A |
| e. No. of continuous staircases to terrace | NIR | MIP | MIA |
| g. Width of Corridor | R | 2.00 m | miR |
| h. Door Size | 1 m | 1.18m & 1.12 | m)R |
| | | (Two dears eache | lane D |

| ('() EM | partmentation. | | | |
|----------|--|-------------------|------------------|--|
| 6 | Fire check door | N/R | N/P | N/A |
| 8 | Scaling of electrical shafts | N/R | N/P | N/A |
| 0 | Fire Rating of shaft door | N/R | N/P | N/A |
| 0 | Water Curtain | N/R | N/P | N/A |
| 6 | Fire Dampers | N/R | N/P | N/A |
| Smok | e Management System. | , | | |
| 0 | Basements | 30 a/c per hour | N/R | N/A |
| 6 | Upper floors | 12 a/c per hour | | |
| | | | N/R | N/A |
| Rine I | Extinguishers | | | |
| 0 | Total numbers | 05 | 10 ABC yes | m)R m)R m)R |
| 0 | Types | ABCONCOZ (2.5K | B) ABC | mjR |
| 6 | IS marking | ISI marked | yes | msR |
| First- | Aid Hose Reels. | | | Politica para de constante de c |
| 0 | Total numbers on each floor | N/R | N/R | N/A |
| - | Length of hose reel hose | 30 m N/R | N/R | N/A |
| 0 | Nozzle diameter | 5 mm N/R | N/R | N/A |
| Autor | natic fire detection and alarmin | g system. | | |
| 69 | Type of detectors | N/R | N/P | N/A |
| 0 | Location of Main Panel | N/R | N/P | N/A |
| | | | | 2.1 |
| 8 | Location of Repeater Panel | N/R | N/P | N/A |
| 8 | Location of Repeater Panel Alternate source of power | N/R N/R | N/P | |
| | Alternate source of power | N/R | N/P | N/A |
| 8 | | | | |
| vi()E | Alternate source of power Hooters' Location FA | N/R | N/P | N/A |
| | Alternate source of power Hooters' Location FA Address System. | N/R N/R | N/P N/P | N/A N/A |
| | Alternate source of power Hooters' Location FA Address System. matic Sprinkler System. | N/R N/R N/R N/R | N/P N/P | N/A N/A N/A |
| vi()E | Alternate source of power Hooters' Location FA Address System. | N/R N/R N/R | N/P N/P | N/A N/A N/A |

| 0 | Upper Floor | N/R | N/P | N/A |
|-----------------------|--|-----|-----------|------|
| 6 | Sprinkler above false ceiling | N/R | N/P | N/A |
| Hester | nal Hydrants | | | |
| • | Size of riser/down-comer | N/R | N/P | N/A |
| 0 | Number of hydrants per floor | N/R | N/P | N/A |
| 6 | Hose Box | N/R | N/P | N/A |
| Vard | Hydrants. | c | | |
| 0 | Total number of hydrants | N/R | N/P | N/A |
| 6 | Hose Box | N/R | N/P | N/A |
| Pumping Arrangements. | | | | |
| 0 | Ground Level | N/R | N/P | N/A |
| | ➤ Discharge of main Pump | N/R | N/P | N/A |
| | ► Head of Main pump | N/R | N/P | N/A |
| | Number of main pumps | N/R | N/P | N/A |
| | Jockey Pump out put | N/R | N/P | N/A |
| | Jockey pump head | N/R | N/P | N/A |
| | > Standby Pump out put | N/R | N/P | N/A |
| | Standby Pump Head | N/R | N/P | N/A |
| | Auto Starting/Manual | | | 1071 |
| | stopping | | * a ** | |
| | Pump House Access | N/R | N/P | N/A |
| | Terrace level | NIR | MIP | NIA |
| | Discharge of pumpHead of the pump | MIR | NIP | NIA |
| | Power Supply | N/R | N/P | N/A |
| | Auto Starting of pump | NIR | NIR | NIA |
| Capti | ve Water Storage for fire fightin | | , , , , , | .,,, |
| 0 | Underground tank capacity | N/R | N/P | N/A |
| p | Draw-off connection | N/R | N/P | N/A |

| | Fire service inlet | N/R | N/P | N/A | | |
|-----|--|----------------|-----|-----|--|--|
| | Access to tank | N/R | N/P | N/A | | |
| | Overhead Tank capacity | MIR | NIP | NIA | | |
| | Exit Signage. | MIR | MIA | MIA | | |
| | Provision of Lifts. | | | | | |
| | Pressurization of Lift Shaft | N/R | N/P | N/A | | |
| | Pressurization of Lift lobby | N/R | N/P | N/A | | |
| | Communication In lift Car | N/R | N/P | N/A | | |
| | Fireman's Grounding Switch | N/R | N/P | N/A | | |
| | Lift Signage | N/R | N/P | N/A | | |
| | Standby power supply | MIR | NIP | MA | | |
| 8 | Refuge Area. | 1 11 - 12 - 13 | e | | | |
| (); | > Total Area | N/R | N/P | N/P | | |
| | Location | N/R | N/P | N/P | | |
| 9 | Fire Control Room | | | | | |
| | Detector System Panel | N/R | N/P | N/A | | |
| | Flow Switch Panel | N/R | N/P | N/A | | |
| | PA System Panel | N/R | N/P | N/A | | |
| | Batter backup | N/R | N/P | N/A | | |
| | Building Floor Plans | N/R | N/P | N/A | | |
| 1() | | NIL | NIL | N/A | | |
| | Protection of special Risks, if any: | | | | | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Recping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi

(c) (co)

Shylad 01/11/2012 (SHYAM CAL Assitt. Divn. officer