GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO.F6/DFS/MS/GH/2012/ 4385

Dated: 26/11/12

FIRE SAFETY CERTIFICATE

Certified that M/s Mahalaxmi guest house located at 7238, Aram Nagar, Qutab road, Paharganj, New Delhi comprised of ground floor (Reception + 04 guest rooms + 01 office), first floor (03 guest rooms + 02 staff rooms) & second floor (02 guest rooms + 03 rooms for owner's use) was granted NOC by this department vide letter No. F.6/DFS/MS/GH/2009/1800 dated 18-06-2009. The premises was re-inspected by the officer concerned of this department on 05-11-2012 in the presence of Mr. Rachit, Manager of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class residential (guest house) with effect from 26/11/12 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules,2010.

Issued on 26/11/12 at New Delhi by.

Chief Fire Officer Delhi fire service

Copy to: -

- 1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi w.r.t. letter No.61473-74/Addl.C.P./Lic(H) dated 19-10-2012
- 2. The Manager, M/s Mahalaxmi guest house, 7238, Aram Nagar, Qutab road, Paharganj, New Delhi

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

	INSPEC	CTION REPORT		
INSPECTION REPORT 1. Name & address of the building: Ms Mahalaxmi Guest House, 7238, Aram Magar 2. Type of Occupancy: Lodging House / Eating House / Ctub PaharGany, Theotethe 3. Type of Case: Renewal / New case 4. Details of previous NOC: Letter No. Folder Ms/GH / 2009/1800 Dated: 18/6/2009 5. Fire Safety directives letter No: 6. Date of inspection: OS 11 Polz 7. Name of the Inspecting Officers: M.K.Chattopadhyay, ADO(HQ) 8. Name and designation of officers from the building side: Mr. Rachit, Manager 9. Year of Construction: 1987-90				
10			1. c.p/4c(H) dat	5 19/10/2012
S.	Minimum Standards on fire	NBC	Provided at site	Remarks
No.	prevention and fire safety U/R 33	Requirement		MR/NMR
1	Access to building		1	
	 Road width 	spl area	15 ont	Me
	Gate width	-	Directly accessible	ME
	Width of internal road	N/A	N/A	
2	Number, Width, Type & Arrangement	of Exits		-
	a. Number of staircases	-		
	Upper Floors	01	01	MR
	Basements	N/A	N/A	AND SEC SEC SEC SEC SEC SEC SEC SEC SEC
	b. Width of staircases	-	-	
	• Upper Floors	0.80m7	0.88mh - 1.07mt	MR
	• Basements	N/A	N/A	
	c. Protection of exits	N/A	N/A	
	Fire check door	N/A	N/A	
	 Pressurization 	N/A	N/A	
	e. No. of continuous staircases to terrace	01	01	MR
	g. Width of Corridor	N/A	N/A	
	h. Door Size	N/A	N/A	
		N/A	N/A	

10

3.	Compartmentation.	Not required			
	Fire check door	N/A	N/A		
	 Sealing of electrical shafts 	N/A	N/A		
	 Fire Rating of shaft door 	N/A	N/A		
	Water Curtain	N/A	N/A		
	• Fire Dampers	N/A	N/A	NO NO. CO. CO. CO. CO. CO. CO. CO. CO. CO.	
4	Smoke Management System.			- :	
	• Basements	30 a/c per hour	N/A	N/A	
	• Upper floors	12 a/c per hour			
			N/A	N/A	
5	Fire Extinguishers				
	• Total numbers 09	1	provided	MR	
	· Types Walto Co, , Co, ABC	3 5	poordes	MR	
	IS marking	ISI marked	provides	m R_	
6	First-Aid Hose Reels.		o months as a second se	- I	
	 Total numbers on each floor 	- OI	provided	MR	
	• Length of hose reel hose	30 m	provide	MR	
	Nozzle diameter	5 mm	poorides	MP	
7	Automatic fire detection and alarming s	ystem.			
	Type of detectors	N/A	N/A	THE REP. LEW SEC. AND COST SEC. SEC. AND	
	Location of Main Panel	N/A	N/A	NAME AND ADD ADD ADD ADD ADD ADD ADD ADD	
	• Location of Repeater Panel	N/A	N/A		
	Alternate source of power	N/A	N/A		
	Hooters' Location	N/A	N/A	* 200 ETC ATC ATC ATC ATC ATC ATC ATC ATC	
8	MOEFA	MA	W.A	•	
9	Public Address System.	Required	porride	ME	
10	Automatic Sprinkler System.				
	Basement	N/A	N/A		
	 Upper Floor Sprinkler above false ceiling	N/A	N/A		
	Springer doore ruise centing	N/A	N/A		

11	Internal Hydrants				
	• Size of riser/down-comer	N/A	N/A		
	Number of hydrants per floor	N/A	N/A		
	Hose Box	N/A	N/A		
12	Yard Hydrants.				
	 Total number of hydrants 	N/A	N/A		
	Hose Box	N/A	N/A		
13	Pumping Arrangements.	*			
	Ground Level	N/A	N/A		
	Discharge of main Pump	N/A	N/A		
	Head of Main pump	N/A	N/A		
	Number of main pumps	N/A	N/A		
	Jockey Pump out put	N/A	N/A		
	Jockey pump head	N/A	N/A		
	Standby Pump out putStandby Pump Head	N/A	N/A		
	Standby Pump HeadAuto Starting/ Manual	N/A	N/A		
	stopping stopping	N/A	N/A		
The state of the s	Pump House Access	N/A	N/A		
	Terrace level			-	
	Discharge of pump	225 LPM	provides	MR -	
	Head of the pump	30m/-	provided	MR	
	Power Supply	-	6 KVA	MR	
1.4	Auto Starting of pump		provided near at	MR	
14	Captive Water Storage for fire fighting	g.			
	 Underground tank capacity 	N/A	N/A		
	Draw-off connection	N/A	N/A	***	
	Fire service inlet	N/A	N/A		
	Access to tank	N/A	N/A		
	Overhead Tank capacity	Worth	provided	MR	
15	Exit Signage.	Required	Provided	MR	

16	Provision of Lifts.			-
2	Pressurization of Lift Shaft	N/A	N/A	
	Pressurization of Lift lobby	N/A	N/A	No. and
	Communication In lift Car	N/A	N/A	
	• Fireman's Grounding Switch	N/A	N/A	
	Lift Signage	N/A	N/A	NAT AND
17	Standby power supply	Required	6KVA	M _P
18	Refuge Area.			
	> Total Area	N/A	N/A	
	Location	N/A	N/A	
19	Fire Control Room			
	Detector System Panel	N/A	N/A	
	Flow Switch Panel	N/A	N/A	
	PA System Panel	N/A	N/A	
	Batter backup	N/A	N/A	
	Building Floor Plans	N/A	N/A	
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	Of ABC lyter for extinguation bonnido near Elect paner	Me_

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to /grant/ renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer Name (M.K. CHATTOPADHYAY)

Designation :- Assistant Divisional Officer

Submitted blease Desi