GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/OFS/ans/school/2012/4626

Dated: 14/12/12

FIRE SAFETY CERTIFICATE

Certified that the M.C. Primary Girls School at Trilok Puri, Block No. 3, Delhi. Comprised of ground floor only with 20 rooms & one hall have complied with the fire prevention and fire safety requirements in accordance with the circular issued by the Director of Education (GNCTD) dated 01.03.2011 and DFS office order dated 18.04.2012 and verified by the officer concerned of of this department on 21.11.2012 in the presence of th Principal, and that the building is fit for occupancy class B "Educational Building" with effect from 14 (2 2012 for a period of three years, subject to conditions printed overleaf.

Chief Fire Officer Delhi Fire Service

Copy to:-

The Principal
 M.C. Primary Girls School
 Trilok Puri, Block No. 3, Delhi

The Principal
 M.C. Primary Boys School
 Trilok Puri, Block No. 3, Delhi

3. The Director
East MCD
Udyog Sadan, Patparganj
Delhi-110092

-4/12-

INSPECTION REPORT

1. Name & address of the building: : M.C.D.Primary School at Trilok

Puri, Block No-3, Delhi -110091

2. Building is comprised of : Ground floor

3: Type of Occupancy : Educational.

4. Type of Case : New

5. Details of Previous NOC letter:

6. Fire Safety direction letter No : Circular Director of Education dated

01.03.2011

7. Date of Inspection : 21-11-2012

8. Name of the Inspecting officers: Gurmukh Singh ADO (LN)

9. Name and designation of Officer: Principal

from the building side

10. Year of Construction : . 1978

11. Applicant's letter No : - Nil - dated 1-10-2012

S.N.	Minimum Standards on fire	Dir. Edn.	Provided at	Remarks
Ο.	prevention and fire safety U/R33	Circular ·	Site	MR/NMR
		Requirement	1	2
1	Access to building	8 - 4' - 4'	e e e	·
	 Road width 	Accessible	30ft	MR
	 Gate width 	12ft	12ft	MR
6	 Width of internal road 	NA	Open ground	MR
2	Number, Width, Type and Arrang	ement of Exits		
	a. Number of Staircases .			
	 Upper Floor 	NA	NA ·	NA
		NA	NA .	NA
	 Basement 	•		
	. •		8	
	D Width of Chaireann	•		10
	B. Width of Staircases	NA	NA	NA
,	Upper FloorBasement	NA .	NA	NA
. *				
	c. Protection of exits	V 8		
v n	The state of the s	NA	NA	NA

				1
1	Fire check door	·································		
	 Pressurization . 	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7		
	e. No. of continuous staircases		***************************************	
	to			
	terrace	•		
	g. Width of Corridor		E	
	h. Door Size	•		* v
3	Compartmentation.	NA	- 0	
	Fire check door			
"	 Sealing of electrical 			
	shafts			
2 2	 Fire rating of shaft door 			
, ,	Water curtain			
	Fire Dampers	The state of the s		200
4	Smoke Management System.	NA		
	Basement			1
	Upper floor			
5	Fire Extinguishers .			
	Total numbers	3 Nos.	4 Nos.	MD
	• types	ABC&CO2		MR
	• ISI marking		ABC& CO2	MR
6	First-aid-Hose Reels.	Req.	Yes.	MR
		· NA	T	
	 Total numbers at ground floor 			
	 Length of hose reel hose 			
	 Nozzle diameter 			
7	Automatic fire detection and alarr	ming system	NA	
	Type of detectors			
	Location of main panel			
	Location of repeater			
	panel			
	Alternate source of .			
	power			
	Hooter's location			
8	MOEFA	NA	NA	NIA
9	Püblic address System.	NA		NA
10	Automatic Sprinkler System.	·NA	NA	NA
	Basement	INA	NA	NA
	upper floor			
	 sprinkler above false ceiling 			
11	Internal Hydrants	NA	NA ·	NA ·
	size of riser/down-comer			1 1/2
W.	•		2 X	•
	0			



- M/4-

	•	,	T	
a :	 Number of hydrants per floor 	NA	NA .	NA
	Hose Box	NA·	NA	NA
12	Yard Hydrants.	NA	NA	NA
	Total number of hydrants			
	Hose Box			
13	Pumping Arrangements.	NA	NA	NA .
	Ground Level			
	➤ Discharge of main Pump			
	➤ Head of Main Pump			
	> Number of main pumps			
	> Jockey pump out put			
	➤ Jockey pump head			
l .	➤ Standby pump out put			
	➤ Standby pump Head			
	➤ Auto Starting /Manual		,	
	stopping			
	➤ Pump House Access			
	. • Terrace Level			
	➢ Discharge of pump			
¥	➤ Head of the Pump			
	> Power supply			
	. > Auto Starting of pump			
14	Captive Water Storage for Fire	NA	NA	NA
	Fighting.			
				•
	 Underground tank 			
	capacity		× 1 × 1 × 1 × 1 × 1 × 1	
	> Draw-off connection			
	> Fire service inlet .			
	> Access to tank			
	Overhead Tank capacity			
15	Exit Signage.	NA.	NA ·	NA
16	Provision of Lifts.	NA	NA	NA
	 Pressurization of Lift Shaft 	•	4	
	Pressurization of Lift lobby			4-1.
	Communication in lift car			
	Firemen's grounding			
	switch	* **		
	Lift Signage			
17	Standby power supply .	NA	NA	NA
18	Refuge Area.	NA	NA	NA
10	Tronge / trou.	13/1	1.47	1.01



			•	
	 Total area 			
	 Location 			
19	Fire Control Room	NA	NA	A.A.
	 Detector system panel 		INA	NA
	Flow switch panel			
•	PA system panel			
	Battery backup			
-	 Building Floor Plans 			
20	Special Fire Protection systems	NA	NA	A L A
	for protection of special Risks, if		IVA	NA ·
7.	any:	8 2 9	n	

The fire protection systems provided in the building were tested checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the Circular of Director Education, GNCTD in the light of office order No. F2/DFS/HQRS/300 dated 18-04-2012 it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Office

Name Gurmakh Sough
Designation Abo (24)

Submitted please.