GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO.F6/DFS/MS/GH/2012/ 467 4

Dated: 18/12/12

FIRE SAFETY CERTIFICATE

Certified that M/s Anas guest house, located at 5161, Fatak Hakim Mahmood Khan, Ballimaran, Chandni Chowk, Delhi comprised of ground floor (08 rooms + 01 hall for 15 beds), first floor (others residence) & second floor (others residence) was granted NOC by this department vide letter No. F.6/DFS/MS/GH/09/2795 dated 15-09-2009. The premises was re-inspected by the officer concerned of this department on 04-10-2012 in the presence of Mohd. Anas, Propreiter of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class residential (guest house) with effect from 18/12/12 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules,2010.

Issued on 18112 at New Delhi by.

Chief Fire Officer Delhi fire service

Copy to: -

1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

2. The Owner, M/s Anas guest house, 5161, Fatak Hakim Mahmood Khan, Ballimaran, Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety
- The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website

INSPECTION REPORT

1	. Name & address of the building:	us Guest Hou	re, 5161, Falaix	Hakim Mahmoo		
2	. Type of Occupancy : Lodgin	: Lodging House / Eating House / Glub Khan, Balle Maran, Del				
3		: Renewal / New case				
4	. Details of previous NOC : Letter					
5						
6	6. Date of inspection : 3 x no12					
7	Name of the Inspecting Officers: M.K.Chattopadhyay, ADO(HQ)					
8						
from the building side : Mohd Arus, propreller						
9						
1(O. Applicant's letter No. : 5	3795/ Addl-C	·P/4×(H) dated	13/8/12		
S.	Minimum Standards on fire	NBC	Provided at site	Remarks		
No.	prevention and fire safety U/R 33	Requirement		MR/NMR		
1	Access to building					
	Road width	Spl-area	main roud from	MR beingold		
	• Gate width	-	Directly accessible	Me		
	Width of internal road	N/A	N/A			
2	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases		*			
	Upper Floors	01	01	MR		
	Basements	N/A	N/A	UND AND AND AND AND AND AND AND AND AND		
	b. Width of staircases	-		-		
	Upper Floors	0.80mlc	0.9407	MR		
	Basements	N/A	N/A			
	c. Protection of exits	N/A	N/A			
	Fire check door	N/A	N/A			
	Pressurization	N/A	N/A	Jan 200 100 AM 100 100 100 100 100 100 100		
	e. No. of continuous staircases to terrace	0	01	MR		
	g. Width of Corridor	N/A	N/A			
	h. Door Size	N/A	N/A			
		N/A	N/A			

9

3	Compartmentation.	Not required	NA	
	Fire check door	N/A	N/A	
	 Sealing of electrical shafts 	N/A	N/A	
	 Fire Rating of shaft door 	N/A	N/A	
	Water Curtain	N/A	N/A	NT NT NT ND 700 ND 400 ND 400 ND 500 ND
	• Fire Dampers	N/A	N/A	
4	Smoke Management System.			
	BasementsUpper floors	30 a/c per hour 12 a/c per hour	N/A	N/A
	11	1	N/A	N/A
5	Fire Extinguishers			
	• Total numbers 03		provided	MR
	• Types water Co. & • IS marking ABC Type	=	provided	me
	• IS marking ABC Type	ISI marked	provided	me
6	First-Aid Hose Reels.	See See		ė.
	Total numbers on each floor	Olat GF	provided	MR
	• Length of hose reel hose	30 m	pourded	MR
	Nozzle diameter	5 mm	provided	MR
7	Automatic fire detection and alarming	system.		
	Type of detectors	N/A	N/A	
	Location of Main Panel	N/A	N/A	~ ~ ~ ~ ~ ~ ~ ~ ~ ~
	• Location of Repeater Panel	N/A	N/A	
	Alternate source of power	N/A	N/A	(00 DJ 40 DJ 40 DB 60 DB 60 DB 60 DB
	Hooters' Location	N/A	N/A	
8	MOEFA	MA	70	o- + + 0 .
9	Public Address System.	MA	MA	
10	Automatic Sprinkler System.	T		
	• Basement	N/A	N/A	
	• Upper Floor	N/A	N/A	
	Sprinkler above false ceiling	N/A	N/A	

11	Internal Hydrants					
`	Size of riser/down-comer	N/A	N/A	WE SE		
	• Number of hydrants per floor	N/A	N/A			
	• Hose Box	N/A	N/A	ON 129 NO 100 NO 100 NO 100 NO 100 NO		
12	2 Yard Hydrants.					
	Total number of hydrants	N/A	N/A	200 200 200 200 300 300 300 300 300		
	Hose Box	N/A	N/A	per per ner ner ner ner ner ner ner ner		
13 Pumping Arrangements.						
THE REAL PROPERTY AND ADDRESS OF THE PERSON	Ground Level	N/A	N/A	700 and 400 feet and 500 feet feet 400 feet feet		
	Discharge of main Pump	N/A	N/A			
	Head of Main pump	N/A	N/A			
	Number of main pumps	N/A	N/A			
	Jockey Pump out put	N/A	N/A	an an to the to the to the total and the tot		
	Jockey pump head	N/A	N/A			
	Standby Pump out put	N/A	N/A			
	Standby Pump Head	N/A	N/A			
	Auto Starting/ Manual	N/A	N/A	Sec. 103. 100 100 100 100 100 100 100 100 100 10		
	stopping	N/A	N/A			
	Pump House Access	N/A	IV/A			
	Terrace level					
	Discharge of pump	225 LPM	provided	MR		
	➤ Head of the pump	WIPM	40ml provided	MR		
	Power Supply		Starling Smitch	04.0		
1.4	Auto Starting of pump	Starting Stritch MR provided near reception				
14	Captive Water Storage for fire fighting		NT/A			
	Underground tank capacity	N/A	N/A			
	Draw-off connection	N/A	N/A	and, and and the last one and the last one and		
	Fire service inlet	N/A	N/A			
	Access to tank	N/A	N/A			
And the control of th	Overhead Tank capacity	2500 1b	provided	rue		
15	Exit Signage.	Required	Provided	MR		

9

16	Provision of Lifts.				
	Pressurization of Lift Shaft	N/A	N/A		
	• Pressurization of Lift lobby	N/A	N/A	40 40 10 10 40 40 10 10 10 10 10	
	Communication In lift Car	N/A	N/A	Man class cast cast cast cast cast cast cast c	
	• Fireman's Grounding Switch	N/A	N/A		
	• Lift Signage	N/A	N/A		
17	Standby power supply				
18 Refuge Area.					
	> Total Area	N/A	N/A	ne de 40 40 10 au de 40 10 au	
	> Location	N/A	N/A	we see see see see see see see see	
19	Fire Control Room				
	Detector System Panel	N/A	N/A		
menen one la Milla, and an and an and	Flow Switch Panel	N/A	N/A		
	PA System Panel	N/A	N/A		
	Batter backup	N/A	N/A		
	Building Floor Plans	N/A	N/A	da, est cla ca. 300 and est to 100 to 100	
20	Special Fire Protection Systems for Protection of special Risks, if any:	Reguired	One Co, lyke fire extensurables found brandas near Eleat panel	MR	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to /grant / renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer Name Designation Signature of the Inspecting Officer Name (M.K. CHATTOPADHYAY) Designation: - Assistant Divisional Officer