GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS : DELHI FIRE SERVICE : CONNAUGHT LANE NEW DELHI-110 001.

No. Foldrsims/2011/500008/3134

Dated: 23/4/11

FIRE SAFETY CERTIFICATE

Certified that the C.P.M. Public School located at G-1/40, Hari Enclave, Sultanpuri, Delhi-110 086, comprised of two blocks. First block consist of ground plus one upper floor and second block consist of ground floor only and less than 9 meters in height, have complied with the fire prevention and fire safety requirement in accordance with Director of Education circular dated 01.03.2011 and verified by the officer concerned of fire service on 15.11.2011 in the presence of Smt. Suman Sharma, Principal and that the building/ premises is fit for occupancy class Educational class with effect from ________________________________ for a period of three years in accordance with rule 36 unless renewed under rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ______ at New Delhi by

Director Delhi Fire Service

Smt. Suman Sharma, Principal, C.P.M. Public School, G-1/40, Hari Enclave, Sultanpuri, Delhi-110 086.

Copy to :

The Director, Dte. Of Education, Old Sectt., Delhi.

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.



INSPEC	TION REPORT		
 Name & address of the building: C.P. Type of Occupancy : Lo. Type of Case : New Companies of previous NOC MA Letter Fire Safety directives letter No : F16 	M. Public. & hood Case/Renewal No. Estate Official 11/2011 R.K. Dahie	Date 2011 3298 - 339	od:
9. Year of Construction			
10 Applicant's letter No. : NO	L dalid	29/9/2011	
S. Minimum Standards on fire No. prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR
Access to building			
 Road width Gate width Width of internal road 	Accessible	Accessible	MR -u-
Number, Width, Type & Arrangement	C TO 14	_	7
Number of staircases Upper Floors Basements	one one	Trus.	MR
b. Width of staircases • Upper Floors	150 cms	120 cms &	mR
Basements	-u-	<u>-u</u>	-w_
Protection of exits Fire check door		_	
Pressurization No of continuous staircases to terrace		-	
g. Width of Corridor In Door Size	15 melina	2 1 melen	mR

		-		900	
3	Compartmentation.		. N.1. A		
	Fire check door		NA		
	 Sealing of electrical shafts 		100	3	
	Fire Rating of shaft door	-			
	Water Curtain		+		
	Fire Dampers		_	-	
4	Smoke Management System.				
	Basements	30 0/0 000 1	NA		
	Upper floors	30 a/c per hour 12 a/c per hour	_	-	
	SPP4: MOOID	12 are per nour			
5	Fire Extinguishers		Provided		
	Total numbers		=7	MR	
	• Types		ABC Type	-42	
	IS marking	ISI marked	15 Marked		
3	First-Aid Hose Reels.				
	 Total numbers on each floor 		-	-	
	 Length of hose reel hose 	30 m			
	Nozzle diameter	5 mm	_	-	
1	Automatic fire detection and alarming system.				
	Type of detectors .	_	-	-	
	 Location of Main Panel 		-	-	
	 Location of Repeater Panel 				
	Alternate source of power		-		
183	Hooters' Location		5	2	
	Hooters Location	-		-	
V .	MOEFA		М.А.		
	Public Address System.		Provided		
0	Automatic Sprinkler System.		N. A		
	Basement				

	 Upper Floor Sprinkler above false ceiling 	-		2	
11	Internal Hydrants		N. I.		
	Size of riser/down-comer		N.A		
	 Number of hydrants per floor Hose Box 				
10		-	-		
12	Yard Hydrants.				
	Total number of hydrants	2,	5	-	
12	Hose Box	2	~	-	
3	Pumping Arrangements.		M.A		
	 Ground Level Discharge of main Pump Head of Main pump 		-	-	
		(e)	2	-	
		-	_	-	
	Number of main pumps		3	1.2	
	 ➢ Jockey Pump out put ➢ Jockey pump head ➢ Standby Pump out put ➢ Standby Pump Head ➢ Auto Starting/ Manual stopping ➢ Pump House Access Terrace level 		5 5	-	
		-		*	
		- 8	h		
		-	50	-	
		-	180	2	
		-		2	
-	Discharge of pump	- 1			
	Head of the pump		_	-	
	➤ Power Supply	-	20		
8	➤ Auto Starting of pump	1	4		
4	Captive Water Storage for fire fighting.				
	 Underground tank capacity 			-	
	Draw-off connection	-	<u>u</u>	1 1 2	

	 Fire service inlet Access to tank 	#			
	Overhead Tank capacity		-		
15		-		1	
16	Provision of Lifts.		Provides		
	 Pressurization of Lift Shaft Pressurization of Lift lobby 	N. A.			
		-			
				F.	
	 Communication In lift Car 			-	
	 Fireman's Grounding Switch 	-			
	• Lift Signage	-	-	_	
17	Standby power supply	-	N.A		
18	Refuge Area.				
	> Total Area	-	NA -		
	> Location	-	-		
19	Fire Control Room				
	 Detector System Panel 	~	-		
	 Flow Switch Panel 	-	<	-	
	PA System Panel		-		
	Batter backup	-		-	
	 Building Floor Plans 			-	
0	Special Fire Protection Systems for Protection of special Risks, if any:	-	-	L	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers

©

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name Shir R. K. Dahiya

Name

Designation ADO

Designation