GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. 66/065/015/schoof/2011/2366 Dated: 05/12/11

FIRE SAFETY CERTIFICATE

Chief Fire Officer Delhi Fire Service

Of Sirling

To,

Principal Govt.Girls Sr.Sec School Dayal Pur,Delhi-94

Copy:-

 The Joint Director of Education (Land & Estate)
 Directorate of Education, Lucknow Road, Delhi -54.

2. Govt Boys Sr. Sec School Dayal Pur, Delhi-94

CONDITIONS

All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management

shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This NOC may not be treated in any case for regularizations of unauthorized

construction unauthorized use of land if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT IDNO 1/04026 1. Name & address of the building: Gorat. Girls Sr Secondary School, Dayalpur 2. Type of Occupancy Educational (Group B) 3. Type of Case New Case/-Renewat 4. Details of previous NOC : Letter No. ______ N. A. ____ Dated: _____ 5. Fire Safety directives letter No : Circular issued by Director of Education. 6. Date of inspection 6. Date of inspection 18-11-2011 Do Virendra Single 7. Name of the Inspecting Officers: 8. Name and designation of officers Principal | HOS Meena Goswami from the building side 9. Year of Construction letter dated 17.11.11. 10. Applicant's letter No. S. Minimum Standards on fire Provided at site Remarks No. prevention and fire safety U/R 33 Requirement MR/NMR Access to building 6 M 12 Mts MR Road width 5 MHs Gate width MR Width of internal road 2 Number, Width, Type & Arrangement of Exits a. Number of staircases Thoree Two MR · Upper Floors Two Three MR Basements b. Width of staircases MR 1.5 MG 1:5 MG · Upper Floors 1.5 Mb ma 1.5 Mt Basements c. Protection of exits · Fire check door Pressurization e. No. of continuous staircases to terrace MR. One g. Width of Corridor 1.5 Mts 2 mts MR

1.0 Mb

1.0 Mb.

MR

h. Door Size

		115-			
3	Compartmentation.	Required	Provided	mr	
	 Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 				
4	Smoke Management System.		. /		
	Basements Upper floors	30 a/c per hour 12 a/c per hour	1	1	
5	Fire Extinguishers				
	 Total numbers Types IS marking 	ABC & CO2 Type ISI marked	42 Nos ABC, water & CO2 1SI Marked	MR Type MR	
6	First-Aid Hose Reels.				
	 Total numbers on each floor Length of hose reel hose Nozzle diameter 	30 m 5 mm			
7	Automatic fire detection and alarming system.				
ş.	 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location 	7			
8	MOEFA				
911	Public Address System.			1	
10	Automatic Sprinkler System. Basement		:		

50	 Upper Floor Sprinkler above false ceiling 	
11	Internal Hydrants	
	 Size of riser/down-comer Number of hydrants per floor Hose Box 	
12	Yard Hydrants.	
	Total number of hydrants Hose Box	
13	Pumping Arrangements.	
	Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump	
	 ➢ Head of the pump ➢ Power Supply ➢ Auto Starting of pump 	
14	Captive Water Storage for fire fighting Underground tank capacity ➤ Draw-off connection	g. :

7.		8
12-	 Fire service inlet Access to tank Overhead Tank capacity 	
15	Exit Signage.	
16	Provision of Lifts.	
	 Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage 	
17	Standby power supply	
18	Refuge Area.	
	➤ Total Area ➤ Location	
19	Fire Control Room	
	 Detector System Panel Flow Switch Panel PAi System Panel Batter backup Building Floor Plans 	
20	Special Fire Protection Systems for Protection of special Risks, if any:	

The fire protection systems provided in the building were test checked and found functional at the to of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire sarequired under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the D-Fire Service Rules 2010/issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer

Name

Designation

Signature of the Inspecting Officer

Name VIRENDRA SING

Designation

DO(E)