GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS : DELHI FIRE SERVICE : CONNAUGHT LANE NEW DELHI-110 001.

No. Re1003/ms/2011/50408//3158.

Dated: 24/1/11

FIRE SAFETY CERTIFICATE

Issued on ______ at New Delhi by

Director

Delhi Fire Service

Dr. Kamla Rana, Vice Principal, Govt. Girls Sr. Sec. School, Adarsh Nagar, Delhi-110 033.

Copy to:

The Director, Dte. Of Education, Old Sectt., Delhi.

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

	INSPEC	TION REPORT				
- 3	Name & address of the hails:	0.01	N. C.	V 20		
8	Type of Occurrence	address of the building : Gort Girls Sr. See School, Adarsh Nagar X				
	Type of Occupancy School					
-	Type of Case : New Case/ Renewal					
	Details of previous NOC N-A: Letter No					
	Fire Safety directives letter No F-16 Estate cc Five Safety 20 η 3298-3398 Δ1-1 Date of inspection [8.])-20 Name of the Inspecting Officers SHR R K ΔΑΗΙΥΑ Name and designation of officers					
-						
5						
	Comment of the State of the					
τ	17 00		Michigan State			
	N 1 11	6, 2002.03 &				
	Minimum Standards on fire	so detred 1	!			
No.		NBC	Provided at site	Remarks		
5.1/.	prevention and fire safety U/R 33	Requirement		MR/NMR		
	Access to building					
	 Road width 	Accessible	- Accessible	mR		
	 Gate width 	- 1		1000		
	 Width of internal road 		10-	211-		
	Number, Width, Type & Arrangement of Exits					
	a Number of staircases	4	5	MR		
	 Upper Floors 		One	- 1		
	 Basements 			-		
	b. Width of staircases	150 Cours	150 cm. eath	MR		
	Upper Floors		ts	-11-		
Ì	• Basements	-	_	-		
	c. Protection of exits	_				
	 Fire check door 					
	 Pressurization 	-	-	18		
	e. No of continuous staircases to terrace	1	-	-		
	g Width of Corridor	La	2			
	h Door Size	12 Melus	2 melens	MR		
	- 200 GIA	Double Down	Double Down	mR		

		COLDO INC.			
		==	-	-	
3	Compartmentation.		NA		
	Fire check door		-	-	
	 Sealing of electrical shafts 	-	2	+	
	Fire Rating of shaft door	_	-	-	
	Water Curtain	-	_	-	
	Fire Dampers	-	-	-	
1	Smoke Management System.	ke Management System.			
	Basements Upper floors	30 a/c per hour 12 a/c per hour	_	4	
			<u> </u>	=	
5	Fire Extinguishers Privided				
	 Total numbers 		17	MR	
	• Types	St.	ABC Type	-u-	
	IS marking	ISI marked	151 Mented	-10	
5	First-Aid Hose Reels.				
	Total numbers on each floor		(-	1	
	Length of hose reel hose	30 m	-	_	
	Nozzle diameter	5 mm			
7	Automatic fire detection and alarming system.				
	Type of detectors .	_	-	-	
	Location of Main Panel	-	-	-	
	Location of Repeater Panel	-	-		
€.	Alternate source of power	-	2	-	
	Hooters' Location		-	=	
É	MOEFA		_	-	
)	Public Address System.	Reput	Provided	ma	
0	Automatic Sprinkler System.		NIA		
	Basement	-	-	-	

は大き

1	The second secon	12.			
	Upper Floor Sprinkler above false ceiling	-		5	
11		-	-		
-11	Internal Hydrants		N-A		
	 Size of riser/down-comer Number of hydrants per floor 	_	^	120	
	Hose Box		-		
10				-	
12	Yard Hydrants.		N.A	- 11	
	 Total number of hydrants Hose Box 		14.04		
13		~		-	
	Pumping Arrangements.		NA	-	
	Ground Level D:	~	-	-	
	➤ Discharge of main Pump ➤ Head of Main pump	^	H.	-	
	or water pump	-	1 = 1	e _{ve}	
	➤ Number of main pumps ➤ Jockey Pump out put		+		
	reserve a trump out put	-	-		
	 Jockey pump head Standby Pump out put 	-	Cer C		
1	> Standby Pump Head > Auto Starting/ Manual stopping > Pump House Access * Terrace level	1 2	-	-	
Ì		-	2		
		-			
-		-	_	_	
a	Discharge of pump	_	_	-	
	➢ Head of the pump	5 -2 3	-		
	Power Supply		-	_	
	➤ Auto Starting of pump	-	-	2	
4 (Captive Water Storage for fire fighting.	NA			
	Underground tank capacity	-	-		
1	➢ Draw-off connection	-	=	-	

	 ➢ Fire service inlet ➢ Access to tank 	-		-	
1.5	Overhead Tank capacity		4	_	
15	Exit Signage.	le, l	Roserded	ma	
16	Provision of Lifts.				
	Pressurization of Lift Shaft	_		-	
	 Pressurization of Lift lobby 	~	J	5	
	Communication In lift Car	-		-	
	 Fireman's Grounding Switch Lift Signage 	-	V.		
2015-00-	Digitage	=	2	-	
17	Standby power supply		N.A		
18	Refuge Area.				
	> Total Area > Location		N.A	240	
19			enter ite-	-	
17	Fire Control Room		N.A		
	Detector System Panel		2	_	
	Flow Switch Panel	-		2	
	PA System Panel	-		_	
	Batter backup	-		-	
2540	Building Floor Plans	-		-	
20	Special Fire Protection Systems for Protection of special Risks, if any:	=		-	

The fire protection systems provided in the building were test checked and found functional at the time of inspection

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers....

(3)

Signature of the Inspecting Officer

Shin R. K. Dahiya

Designation AD7

Signature of the Inspecting Officer

Name

Designation