GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELH HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. f6/0 f5/ms/school/2011/3364 Dated: 05/12/11

FIRE SAFETY CERTIFICATE

Chief Fire Officer Delhi Fire Service

To,

Principal
Govt.Girls Sr.Sec School
A-Block, Nand Nagri, Delhi-93.

Copy:-

- The Joint Director of Education (Land & Estate)
 Directorate of Education,
 Lucknow Road, Delhi -54.
- Principal Govt.Boys Sr.Sec School A-Block, Nand Nagri, Delhi-93.

Kand 2011

CONDITIONS

1. All the means of escape shall be kept free of all type of obstruction all the time.

 All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

 All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management

shall be responsible.

 Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This NOC may not be treated in any case for regularizations of unauthorized

construction unauthorized use of land if any.

 The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1	Name & address of the building :(GG Sr. Soo. Se	hool, A-Block	NandMan:			
2	The contract of the contract o	lucational' (Delli-93			
3	tri e e	New Case/-Renewal-					
4	. Details of previous NOC : Lett	: Letter No N. A Dated: -					
5	12,000,000	1000000					
6	Date of inspection As per curcular daled 01-03-11 21-11-11						
7	Name of the Inspecting Officers: Do Vnendra Single						
8	Name and designation of officers						
	from the building side	it Breda J. Bas	Ma. Vice Pris	respal			
9	Year of Construction	1991					
10	0. Applicant's letter No.	de	led 21-1.	1-11			
S. No	Minimum Standards on fire prevention and fire safety U/R 33	NBC Civallar Requirement	Provided at site	Remarks MR/NMR			
1	Access to building						
	Road width	6 Mts	9 mts	MR.			
	Gate width	-	4 mts	MR			
	Width of internal road	-	-				
2	Number, Width, Type & Arrangement of Exits						
	a Number of staircases	Two r	Three	MR			
	 Upper Floors 	Two	Three	MAR			
	 Basements 	-	-	_			
	b. Width of staircases	1.5 mb	1.5 mb	MR			
	Upper Floors	1.5 mts	1.5 Mts	mn			
	Basements	1	1	1			
	c. Protection of exits		1				
	Fire check door			/			
	 Pressurization 		-/-	/			
	e. No. of continuous staircases to terrac	ce One	Two	MR			
	g. Width of Corridor	1.5 MG	1.5 puts	mr			
	h. Door Size	1 avo mm	12000mm	mr			

			/			
3	Compartmentation.			/		
	Fire check door					
	 Sealing of electrical shafts 			1		
	 Fire Rating of shaft door 	- /				
	Water Curtain	1				
	Fire Dampers	1				
4	Smoke Management System.					
	Basements	30 a/c per hour	1			
	Upper floors	12 a/c per hour	- /			
			1			
5	Fire Extinguishers					
	Total numbers	12 Nos	15 Nos	MR		
	• Types -	12 Nos Ansel Con Type	ABCE Costype	MR		
	IS marking ISI mar.		151 Marked	MR		
6	First-Aid Hose Reels.					
	 Total numbers on each floor 		/	1		
	 Length of hose reel hose 	30 m	- /	1		
	Nozzle diameter	5 mm	/	1		
7	Automatic fire detection and alarming system.					
	Type of detectors		Ţ.			
	Location of Main Panel		1	-		
	Location of Repeater Panel			/-		
10				1		
	Alternate source of power					
	Hooters' Location	1				
8	MOEFA		1	-		
9	Public Address System.		1			
10	Automatic Sprinkler System.					
	Basement					

83	 Upper Floor Sprinkler above false ceiling 	
11	Internal Hydrants	
	 Size of riser/down-comer Number of hydrants per floor Hose Box 	
12	Yard Hydrants.	
	Total number of hydrants Hose Box	
13	Pumping Arrangements.	
	 Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump 	
14	Underground tank capacity Draw-off connection	ag.

r								
	£0	> Fire service inlet				Ť.		
		> Access to tank						1
		Overhead Tank capacity) K 1					
	15	Exit Signage.						
1	16	Provision of Lifts.		MEX				
		Pressurization of Lift Shaft						
		Pressurization of Lift lobby						
		Communication In lift Car		-				
	20	Fireman's Grounding Switch				40		
1		T 10 C1						
1		som organize				-		
	17	Standby power supply						
	18	Refuge Area.					_	
		➤ Total Area		on I				
		> Location						_,_
	19	Fire Control Room				100		
		Detector System Panel			1 = 1			
		Flow Switch Panel						
		PA System Panel			,			
		Batter backup				-		
		Building Floor Plans		8 2	- 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
	20	Special Fire:Protection Systems for						
	N.	Protection of special Risks, if any:				k -	1	

The fire protection systems provided in the building were test checked and found functional at the of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire strequired under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

· -

Signature of the Inspecting Officer

Name

Designation

Signature of the Inspecting Officer

Name Vinendra Singh

Designation 10 (E)