GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELH HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. 66/065/05/ school/2011/3365

Dated: 05/12/11

FIRE SAFETY CERTIFICATE

Issued on...... S / 12-/-1/.....at New Delhi by

Chief Fire Officer Delhi Fire Service

Principal
Govt.Girls Middle School
Nandnagari Extn. F-I/II, Delhi-93,

Copy:-

The Joint Director of Education (Land & Estate)
Directorate of Education,
Lucknow Road, Delhi -54.

CONDITIONS

1. All the means of escape shall be kept free of all type of obstruction all the time.

All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

 All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management

shall be responsible.

 Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This NOC may not be treated in any case for regularizations of unauthorized

construction unauthorized use of land if any.

 The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available or www.dfs.delhigovt.nic.in

	INSPEC	CTION REPORT		Tin Shed				
3 4 5	Details of previous NOC : Letter Fire Safety directives letter No : A	cational Case/Renewal No NA - 3 per circ	(Group B	- I/II , Dela				
5	Name of the Inspecting Officers: Name and designation of officers from the building side Ka	1).				
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Civalar Requirement	Provided at site	Remarks MR/NMR				
1	Access to building							
	 Road width Gate width Width of internal road 	6 mts	8 MG 4 ONG	MR				
2	Number, Width, Type & Arrangement	of Exite						
	a. Number of staircases • Upper Floors • Basements b. Width of staircases • Upper Floors • Basements c. Protection of exits • Fire check door • Pressurization e. No. of continuous staircases to terrace g. Width of Corridor	Ground blane						
	h. Door Size	1'5 mg	1's Mts	MR				

30%

[]] 9

3	Compartmentation.								
-	Fire check door								
	 Sealing of electrical shafts 								
	 Fire Rating of shaft door 	. /		1					
	Water Curtain								
	 Fire Dampers 	1/-							
4	Smoke Management System.								
	• Basements	30 a/c per hour	1.	1					
	 Upper floors 	12 a/c per hour		-					
5	Fire Extinguishers								
	Total numbers	04	04	MR					
	• Types	ABC/Cortype	ABC & one Carty 151 Marked	KO MR					
	IS marking	ISI marked	151 Marked	MR					
6	First-Aid Hose Reels.								
	Total numbers on each floor	-		1					
	 Length of hose reel hose 	30 m	/-						
	Nozzle diameter	5 mm	/	1					
7	Automatic fire detection and alarming system.								
	Type of detectors		1						
	Location of Main Panel			/					
	Location of Repeater Panel			-					
	- 10			-					
i s	Alternate source of power	-/	- /						
	Hoofers' Location								
8	MOEFA			A .					
9	Public Address System.		/						
10	Automatic Sprinkler System.								
	Basement								

181	Upper Floor Sprinkler above false ceiling		-		/		1	
11	Internal Hydrants							
	 Size of riser/down-comer Number of hydrants per floor Hose Box 							
12	Yard Hydrants.					,		
	Total number of hydrants Hose Box							
13	Pumping Arrangements.	-0						
	• Ground Level ➤ Discharge of main Pump ➤ Head of Main pump		=					
	 Head of Main pump Number of main pumps Jockey Pump out put 	7 -	ā.					
	 Jockey pump head Standby Pump out put 							
	 ➤ Standby Pump Head ➤ Auto Starting/ Manual stopping 						-	
	> Pump House Access • Terrace level							
	Discharge of pump ➤ Head of the pump		2 11 4	- 37	1 5 6 6			
	Power SupplyAuto Starting of pump				1			
14	Captive Water Storage for fire fighting.							
	Underground tank capacity Draw-off connection			-				

-	4.		- I			10
	➤ Fire service inlet		1		1	-
	Access to tank		1 -		/	
	Overhead Tank capacity	3 "		- :/:		-/-
15	Exit Signage.			3		
16	Provision of Lifts.	2.5	10			
	Pressurization of Lift Shaft	2	× 1		7	
	Pressurization of Lift lobby					
	Communication In lift Car					
92	Fireman's Grounding Switch	1		1 3	+	
	Lift Signage	1	(4)	100	-	
	23.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1				001	
17	Standby power supply		*	12	1	
18	Refuge Area.			St .		
	> Total Area			I I		
	> Location					
19	Fire Control Room				W	
	Detector System Panel	1		. 21		
	Flow Switch Panel			177		
	PAi System Panel	1		1		
	Batter backup	1		H Tola		
	Building Floor Plans				1	
20	Special Fire Protection Systems for		2 2 2			
	Protection of special Risks, if any:		2 -	- 32	1	
					1	

The fire protection systems provided in the building were test checked and found functional at the of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Fire Service Rules 2010/- issue shortcomings as noted at serial numbers.

Signature of the Inspecting Office Name Name Designation Designation