GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT LANE NEW DELHI-110 001.

No. F6/065/ms/school/2011/3295

Dated: 01 12 11

FIRE SAFETY CERTIFICATE

Certified that the M.C. Primary Girls School located at Madanpur Dabas, Delhi-110 081, comprised of ground plus one upper floor and less than 9 meters in height, have complied with the fire prevention and fire safety requirement in accordance with Director of Education circular dated 01.03.2011 and verified by the officer concerned of fire service on 16.11.2011 in the presence of Principal and that the building/ premises is fit for occupancy class Educational class with effect from older rule37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on _____ at New Delhi by

Director

Delhi Fire Service

OIGALL 4

29/11

Principal, M.C. Primary Girls School, Madanpur Dabas, Delhi-110 081,

Copy to:

The Director, Kashmiri Gate, Delhi.

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

| | INSPEC | CTION REPORT | | | |
|-----------|---|---|-------------------------------------|-------------------|--|
| 4 | Details of previous NOC NA: Letter Fire Safety directives letter No : F-16 | Case Renowal No. Estate Cc Fu 11 2011 En R. K. Dahu A. | Date Lefety 2011 32 | ed: | |
| | 0. Applicant's letter No. : N | | L | | |
| S. No. | Minimum Standards on fire prevention and fire safety U/R 33 | NBC | Provided at site | Remarks MR/NMR | |
| 1 | Access to building | | | | |
| | Road width Gate width Width of internal road | -Accessible | -Accessible | m R | |
| 2 | Number, Width, Type & Arrangement | of Evite | | | |
| | a Number of staircases Upper Floors Basements Upper Floors Upper Floors Basements C. Protection of exits Fire check door Pressurization | 150 cm | Two | MR -1 | |
| | e. No. of continuous staircases to terrace g. Width of Corridor h. Door Size | Our 1/2 melus Single Donr | 1 melens 2 melens Double Down | | |

| | Compartmentation. | ======================================= | | - Tenant | | |
|---|--|---|------------|----------|--|--|
| | Fire check door | | NA | | | |
| Ü | Sealing of electrical shafts | | | | | |
| | Fire Rating of shaft door | | | - | | |
| | Water Curtain | - | _ | | | |
| 1 | Fire Dampers | | | 5- | | |
| 4 | | | | - | | |
| | Smoke Management System. | | · NA | | | |
| | Basements Upper floors | 30 a/c per hour | 19.10 | | | |
| | | 12 a/c per hour | | - | | |
| 5 | Fire Extinguishers | | | | | |
| | Total numbers | | (A O | violed | | |
| | Types | | Three | mire | | |
| | IS marking | IO | 2 - ABC Ty | OF. | | |
| | First-Aid Hose Reels, | ISI marked | 151 Marked | -ei - | | |
| | Total numbers on each floor | | NA | | | |
| | Length of hose reel hose | 20 | | 1 | | |
| | Nozzle diameter | 30 m 5 mm | | | | |
| | Automatic fire detection and alarming | 1 5 mm | | - | | |
| | • Type of the | N.A | | | | |
| | Type of detectors Location of Marian | | _ | 6 | | |
| | robation of Main Panel | | | | | |
| | Location of Repeater Panel | | | | | |
| | Alternate source of power | ~ | * | | | |
| | Hooters' Location | - | | 6 | | |
| 1 | | - | - | | | |
| | MOEFA | | NA | | | |
| 1 | Public Address System. | Rejuid | | A. A. | | |
| 1 | Automatic Sprinkler System. | | Provided | mp | | |
| 1 | Basement | 1,9 1,3 | | | | |

The state of the s

| | Upper Floor Sprinkler above false ceiling | Ę. | - | - | |
|-----|--|------|--|----------|--|
| 11 | | - | The state of the s | | |
| 300 | Internal Hydrants N.A. | | | | |
| | Size of riser/down-comer | - | 100 | 60 | |
| | Number of hydrants per floor Hose Box | 2 | | <u>e</u> | |
| | | 22 | | - | |
| 12 | Yard Hydrants. | | | | |
| | Total number of hydrants | | | 6 | |
| | Hose Box | # | | - | |
| 13 | Pumping Arrangements. | NA | | | |
| | Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual | - | - | | |
| | | - | | * | |
| | | _ | | (2) | |
| | | | | | |
| | | | | | |
| | | - | | | |
| | | | - | | |
| | | in . | * | - | |
| | | + | | * | |
| | stopping | | 4 | 8 | |
| | > Pump House Access | | | | |
| | Terrace level | - | - | | |
| | ➤ Discharge of pump | - | · · · · · · · · · · · · · · · · · · · | | |
| | ➢ Head of the pump | - | | <u></u> | |
| | ➤ Power Supply | 4 | TO I | | |
| | ➤ Auto Starting of pump | - | - | | |
| 4 | Captive Water Storage for fire fighting. | N.A | | | |
| | Underground tank capacity | - t- | - | 1=- | |
| | > Draw-off connection | - | _ | 1 300 | |

| | Fire service inlet Access to tank Overhead Tank capacity | - | - | - |
|-----|--|----------|---------|----|
| 15 | Exit Signage. | Ryund | - | - |
| 16 | Provision of Lifts, | Kyund | Pronded | mR |
| | Pressurization of Lift Shaft | - | NA | |
| | Pressurization of Lift lobby Communication In lift Car | - | | H= |
| | Fireman's Grounding Switch | - | 74 | |
| | • Lift Signage | • | | |
| 17 | Standby power supply | | - | - |
| 18 | Refuge Area. | | NA | 2 |
| | ➤ Total Area | | N.A | |
| | ➤ Location | + | | - |
| 19 | Fire Control Room | | - | 12 |
| | Detector System Panel | | NA | |
| | Flow Switch Panel | | | - |
| | PA System Panel | <u>~</u> | | 16 |
| | Batter backup | | - | F |
| | Building Floor Plans | - | | |
| 0 5 | Special Fire Protection Systems for | + | • | - |
| P | rotection of special Risks, if any: | | | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer

Name R. K. Dahrys

Designation Asst. Div. Officer

Signature of the Inspecting Officer

Name

Designation