GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS : DELHI FIRE SERVICE : CONNAUGHT LANE NEW DELHI-110 001.

No. RE 1 DR3/M3/2011/5 choof / 3135

Dated: 24/11/11

FIRE SAFETY CERTIFICATE

Issued on ______ at New Delhi by

Director

Delhi Fire Service

Of Mu

(3/1)

Shri R.C. Yadav, Principal, Rajikiya Pratibha Vikas Vidyalaya, Narela, Delhi-110 040.

Copy to:

The Director, Dte. Of Education, Old Sectt., Delhi.

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

INSPE	CTION REPORT		
4. Details of previous NOC N ★: Lette 5. Fire Safety directives letter No : P 16 6. Date of inspection 7. Name of the Inspecting Officers : Sh 8. Name and designation of officers from the building side 9. Year of Construction : 2	Case/Renewal r No. Estate ce Fre 11.2011 n R.K. Da	Date Safety/ce/2011/	
S. Minimum Standards on fire	DC/CPMED-V		t. 4.10.2011
No. prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR
Access to building			
Road width Gate width	Acceptable	Accessible	MR
e Width of internal road			- u-
Number, Width, Type & Arrangement	-612 tv	_	
a Number of staircases	7		
Upper Floors	These	Three	MK
Basements		Fluce	-22
b. Width of staircases	~		
Upper Floors	15 Bough	150 cm	mp
Basements		t	
c. Protection of exits	1000	<u></u>	
Fire check door	•	_	7-
Pressurization	-	_	2
			-
e. No of continuous staircases to terrace g. Width of Corridor	Thee	Fire	me
h Door Size	12 Melin	2 Melins	
The second secon	Simple Don	Double Dow	MR

				- 1	
			_	-	
3	Compartmentation.		NA		
	 Fire check door 	-	6	900 0	
	 Sealing of electrical shafts 	24	-		
	 Fire Rating of shaft door 			- 3	
	Water Curtain		-		
	Fire Dampers	_		~	
4	Smoke Management System.				
	Basements	30 a/c per hour			
	 Upper floors 	12 a/c per hour		200	
	427	3/31		741	
5	Fire Extinguishers		Provided		
	 Total numbers 		34	mR	
	• Types		ABC Type		
	IS marking	ISI marked	151 marked	-u	
6	First-Aid Hose Reels.				
	 Total numbers on each floor 		15	MR	
	 Length of hose reel hose 	30 m	9 e my	-	
	Nozzle diameter	5 mm	5 mil	==	
7	Automatic fire detection and alarming system.				
	Type of detectors				
	 Location of Main Panel 	-		2.2	
	 Location of Repeater Panel 				
15,5	Alternate source of power		-		
	Hooters' Location				
8	MOEFA		Promised	mr_	
9	Public Address System.		Provided	- He-	
10	Automatic Sprinkler System.		NA.		
	Basement				

SHE LINE

	Upper Floor	-				
	Sprinkler above false ceiling		_			
1	Internal Hydrants					
	Size of riser/down-comer Number of hydrants per floor	NR	Promelad	MR		
	Hose Box	.7	Ou	-		
2	N 199	-		1		
4	Yard Hydrants.		Provide	P		
	 Total number of hydrants Hose Box 	NR	Two	MR		
3	Pumping Arrangements.		Prowelad	- KC		
	Ground Level	NR		-		
	 Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access 	HR	-	100		
		NR		-		
		N.R.		152		
		NR				
		NR		8		
		NR		160		
		NR	-			
		NR	-	7		
	 Pump House Access Terrace level 					
	 ➤ Discharge of pump 	900 LPM	Provided	mR		
	Head of the pump	40 mby	Provided	- K		
	➤ Power Supply Auto Starting of	Not Repund		**		
	Auto Starting of pump	Not Roger d	_			
+	Captive Water Storage for fire fighting.					
1	 Underground tank capacity 	HR	50,000 Lho	ma		

	 Fire service inlet Access to tank Overhead Tank capacity 	Acersolde 10,000 Mm	Access ble	mil	
15	Exit Signage.	174 0000	200	ma	
16	Provision of Lifts.		Provided		
	Pressurization of Lift Shaft Pressurization of Lift lobby Communication In No. 2		- N.Y	-	
		_		150 1	
	Communication in lift Car		-	-	
	 Fireman's Grounding Switch Lift Signage 	-		r	
LEW AND			**		
17	Standby power supply		N. A	_	
18	Refuge Area.				
	➤ Total Area ➤ Location	-	1.0		
19	Fire Control Room			~	
			N.A		
	Dotter of System Faller			100	
	 Flow Switch Panel 	-	-		
	 PA System Panel 		>		
	Batter backup				
	Building Floor Plans	_	-	=	
0	Special Fire Protection Systems for Protection of special Risks, if any:	-	-	-	

The fire protection systems provided in the building were test checked and found functional at the time of inspection

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

(5)

Signature of the Inspecting Officer

Name Shin R. K. Dahys

Designation ADO

Signature of the Inspecting Officer

Name

Designation