GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS : DELHI FIRE SERVICE : NEW DELHI-110 001.

No. F6/DFS/MS/2011/3617

Dated: 19/12/11

FIRE SAFETY CERTIFICATE

Issued on). 9. /1.2. /.ll...... at New Delhi by

Director Delhi Fire Service

Of All

Shri Rajat Arora, Proprietor Fine Food Product, A-3, Phase-III, Badli Industrial Area, Delhi-110 042.

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

	INSPECTION REPORT 1. Name & address of the building: FINE FOOD PRODUCT, BADLI INDUSTRIAL 2. Type of Occupancy : INDUSTRIAL BUILDING 3. Type of Case : New Case/ Renewal 4. Details of previous NOC NA: Letter No. Dated: 5. Fire Safety directives letter No: As per NBC Part IV CBBL 6. Date of inspection : 28.11.2011 7. Name of the Inspecting Officers: Shar R. K. Daluys, Add.			
4	Type of Occupancy New C Details of previous NOC NA: Letter Fire Safety directives letter No: As Date of inspection: 28.11	USTRIAL BU ase/Renewal No	ULDING Date	
ç	Year of Construction 200			
1	0. Applicant's letter No.			
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR
1	Access to building			
	 Road width Gate width Width of internal road 	9 Meluz Accersible	10 Miless Accessible	mR —u
2	Number, Width, Type & Arrangement of	of Exits	<u>-</u>	
	a. Number of staircases • Upper Floors	TWO	Two	mB -uc
	Basementsb. Width of staircasesUpper Floors	-u- 125 cm eah	135 cm 130 cm	m R
	Basementsc. Protection of exitsFire check door	7	_n	- II -
	 Pressurization e. No. of continuous staircases to terrace g. Width of Corridor 	This	Tows	m R
	h. Door Size	100 cms	125 cms	MR

3	Compartmentation.		NA		
	Fire check door		7		
	 Sealing of electrical shafts 	7		-	
	Fire Rating of shaft door	7	•	-	
	Water Curtain		45	-	
	Fire Dampers	-			
4	Smoke Management System.				
	Basements	30 a/c per hour		-	
	Upper floors	12 a/c per hour			
5	Fire Extinguishers		Provided		
	Total numbers		12 <	MR	
	• Types		ABC Type	-u-	
	IS marking	ISI marked	ISI Marked		
6					
	Total numbers on each floor	-	Two	MR	
	Length of hose reel hose	30 m	30 melus	- u-	
	Nozzle diameter	5 mm	5 mm	<u> </u>	
7	Automatic fire detection and alarming system.				
	Type of detectors				
	Location of Main Panel			-	
	Location of Repeater Panel			-	
	Alternate source of power				
	Hooters' Location				
8	MOEFA	Not Romi	resh -	-	
9	Public Address System.	Not Required		-	
		111111111111111111111111111111111111111	Provided		
10	Automatic Sprinkler System.			m	

1 -				
	Upper FloorSprinkler above false ceiling			
11		-		
11	Internal Hydrants			
	Size of riser/down-comer	Rejuried	Pronded	mr
	Number of hydrants per floorHose Box			-
•		Repund	Provided	mR
2	Yard Hydrants.		N.A	
	Total number of hydrants		-	•
3	Hose Box			
	Pumping Arrangements.			
	Ground Level	-		~
	Discharge of main Pump	-		-
	➤ Head of Main pump			
	Number of main pumps			
	> Jockey Pump out put	-		
	> Jockey pump head			-
	> Standby Pump out put			
	> Standby Pump Head			The state of the s
	Auto Starting/ Manual			
	stopping			
20 -	> Pump House Access		Çik Direveliye	
	Terrace levelDischarge of pump	900 Lpm	900 Lpm	mR
	➤ Head of the pump	40 melis	40 melus	- u-
	Power Supply	Required	Priviled	- 4-
	➤ Auto Starting of pump	Repused	Provided	-11-
	Captive Water Storage for fire fighting.			
	Underground tank capacity			
	> Draw-off connection	-		

V E				
	2			
네이 가게 그는 이 에이 아니는 이에 아이를 그렇게 되었다.			1	
Overhead Tank capacity	10,000 Likis	12,000 4/2	me.	
Exit Signage.	Repuised	Parameted	MR	
Provision of Lifts.				
Pressurization of Lift Shaft				
Pressurization of Lift lobby				
Communication In lift Car	•		-	
[] 교육 프로토스 - 이 프로토스 교육 전략 경우면 바로 시민하고 [] - 다시 그리고 그				
~~~~				
Standby power supply	Repurid	Provided 63 KVA	mR	
Refuge Area.				
➤ Total Area				
➤ Location				
Fire Control Room				
Detector System Panel	The same of the sa	Also appearance	And the second	
Flow Switch Panel	1 T 1 T			
PA System Panel	A. A.	The state of the s	_	
Batter backup		Man Carrier Man		
Building Floor Plans				
Special Fire Protection Systems for Protection of special Risks, if any:				
	Provision of Lifts.  Pressurization of Lift Shaft  Pressurization of Lift lobby  Communication In lift Car  Fireman's Grounding Switch  Lift Signage  Standby power supply  Refuge Area.  Total Area  Location  Fire Control Room  Palesystem Panel  Palesystem Panel  Batter backup  Building Floor Plans  Special Fire Protection Systems for	> Access to tank     Overhead Tank capacity  Exit Signage.  Provision of Lifts.  Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage  Standby power supply Refuge Area.  Total Area Location  Fire Control Room  Petector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans  Special Fire Protection Systems for	> Access to tank     Overhead Tank capacity  Exit Signage.  Provision of Lifts.  Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage  Standby power supply Refuge Area.  > Total Area     Location  Fire Control Room  Detector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans Special Fire Protection Systems for	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

(§=)

Signature of the Laspecting Officer

Signature of the Inspecting Officer

Name R. K. Dahiys

Name

Designation ADO

Designation