[See sub-rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. 66/068/ms/schuel/2011/3428

Dated 6 \$ / 12 / 11

FIRE SAFETY CERTIFICATE

Certified that the Goft. Girls Sr. Sec. School No.1, Ghonda, Delhi-53. Comprised of ground plus one upper floor owned/occupied by Govt. Girls Sr. Sec. School No.1, Ghonda, Delhi-53, have complied with the fire prevention and fire safety requirements in accordance with the circular issued by the Director of Education dated 01.03.2011 and verified by the officer concerned of Fire Service on dated 24.11.11 in the presence of Mrs. Sadhna Verma Vice Principal of the school and that the building is fit for occupancy class B' Educational printed overleaf.

Chief Fire Delhi Fire Service

To,

13

Principal

Govt. Boys Sr. Sec. School No.1,

Ghonda, Delhi-53

Copy to:-

The Joint Director of Education (Land & Estate) Directorate of Education, Lucknow Road, Delhi -54.

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1.	Type of Occupancy	+ 5171 57-	sec schrot a	10-1
2.	Type of Occupancy Eclu	Cetional	Thomas Delli-	53
3.	Type of Case : New Ca	se/Renewal	,	
4.	Details of previous NOC : Letter N	lo	Date	d:
5	Fire Safety directives letter No : F-15/	Estate/ce/ Fire	Sately /2011/329	8 to 3318
6	Fire Safety directives letter No : Full 10 Date of inspection : 24	11. 2011	Core. 1.	3. 2017
7	Name of the Inspecting Officers:AL	so syresh	Lingh	
8	Name and designation of officers	* E	× •	
	from the building side : Vì	ce frinci	spel, Shadhna	verma
9	Year of Construction : 194	9.		
10	O. Applicant's letter No.			
S.	Minimum Standards on fire	NBC	Provided at site	Remarks
No.	prevention and fire safety U/R 33	Requirement		MR/NMR
1	Access to building	26		
	Road width	64	MM	MR
	Gate width	4.5 07	5.20 M	MR
	Width of internal road			
2	Number, Width, Type & Arrangement of	of Exits		
	a. Number of staircases	4	4	MR
	Upper Floors	-		
	Basements			
	b. Width of staircases	1.57	1.54	MR
	Upper Floors			~
	Basements			
	c. Protection of exits			
	Fire check door			-
	• Pressurization			-
	e. No. of continuous staircases to terrace		No	_
	g. Width of Corridor	1.57	1.60	HR '
	h. Door Size	1. M	IM	MR

3	Compartmentation.			
	Fire check door		Provi	ded
	 Sealing of electrical shafts 		· ·	
	Fire Rating of shaft door	-		
	Water Curtain			
	Fire Dampers			
4	Smoke Management System.	Manage Control of the		
	Basements	NIA		
	• Upper floors	30 a/c per ho		
5	Fire Extinguishers			
	·	大顿外)	Required L	
	Total numbersTypes	22 1/0	20 NO	7 14
	IS marking		C021AP	
6	First-Aid Hose Reels.	ISI marked	151	H
e		AIN		
	Total numbers on each floor Length of bear and the second of th			-
	Length of hose reel hoseNozzle diameter	30 m		
		5 mm		_
	Automatic fire detection and alarming	system. NIA		
	 Type of detectors 			<u> </u>
	 Location of Main Panel 			
	 Location of Repeater Panel 			
	Alternate source of power			
	Hooters' Location			
N	MOEFA			
- 1	ublic Address System.	HIA		
A	utomatic Sprinkler System.		yes	•
	Basement	HIA		

	• Upper Floor			16
	Sprinkler above false ceiling			_
11	Internal Hydrants			_
	 Size of riser/down-comer 	IVIA		
	• Number of hydrants per floor			
	• Hose Box			
12	Yard Hydrants.			
	Total number of hydrants	NIA		
	Hose Box			
13	Pumping Arrangements.			
	 Ground Level 	1/14		
*	Discharge of main Pump			
	Head of Main pump			
	Number of main pumps	Approximate to		-
	➤ Jockey Pump out put			per
	> Jockey pump head	·		-
	Standby Pump out put			
	Standby Pump Head	, .		
	Auto Starting/ Manual	-		
	stopping			
	> Pump House Access			_ ,
	• Terrace level			
	Discharge of pump Head of the man		A41 1114	-
	Head of the pumpPower Supply			÷
	> Auto Starting of pump			
Cap	tive Water Storage for fire fighting.			
•	Underground tank capacity	MIA		
<u> </u>	Draw-off connection			

	> Fire service inlet			
	> Access to tank			_
	Overhead Tank capacity			
15	Exit Signage.	. ,		
16		MIA		
1	Provision of Lifts.	HIA		
	 Pressurization of Lift Shaft 		- 1	
	 Pressurization of Lift lobby 			
AC 1	 Communication In lift Car 			
	 Fireman's Grounding Switch 			,
	• Lift Signage			· •
17	Standby november 1			
18	Standby power supply	MIA		
10	Refuge Area.	NIA		
	> Total Area	1		re e
	> Location			
19 1	Fire Control Room	MIR		
	Detector System Panel	177.6		
	 Flow Switch Panel 			
	PA System Panel			
	Batter backup			
	Building Floor Plans			
Sp	pecial Fire Protection Systems for			
Pr	otection of special Risks, if any:	1414		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/issue shortcomings as noted at serial numbers.

Sangl

Signature of the Inspecting Officer

Name Suresh Singh

Designation A10

Signature of the Inspecting Officer

Name

Designation