GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F-6/0F-5/018/school/2011/35/0

Dated: 14/12/11

FIRE SAFETY CERTIFICATE

Chief Fire Officer For Director

Delhi Fire Service

To,

Govt. Girls Sr. Sec. School, Sonia Vihar, Delhi-94

Copy to:-

The Joint Director of Education (Land & Estate) Directorate of Education, Lucknow Road, Delhi -54.

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1.	Name & address of the building: 30v	+ Firls Se	nior Secondr	7 School	
2.		Cational	Sonia ni	har	
3.	Type of Case : New Ca	ase/Renewal	9	Į.	
4.	Details of previous NOC : Letter NoDated:				
5.	Fire Safety directives letter No : 15/6/	Bstore / ce/ Au	re Safety / 2011/	3298-6	
6.	Date of inspection :	11.2011	3378 Deser	() (3 · 2 •))	
7.	74.5	so Surech	Singh	•	
8.	Name and designation of officers	•			
	from the building side : Mrs	Kalawati	Bohra Vice	Principal	
		005			
- (Applicant's letter No. : 66	535/57/11-1:	2/236 alched	124	
S.	Minimum Standards on fire		Provided at site	Remarks	
No.	prevention and fire safety U/R 33	Requirement		MR/NMR	
1	Access to building			,	
	Road width		6 M	ε	
	Gate width		6 M.	±	
	Width of internal road				
2	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases	4	4	MR	
	Upper Floors				
×	Basements				
	b. Width of staircases	1.5	1:45, 150 M	MR	
	Upper Floors			. •	
•	Basements			~	
	c. Protection of exits				
	Fire check door		-	-	
	 Pressurization 	-		-	
	e. No. of continuous staircases to terrace	-	No	-	
	g. Width of Corridor	1.5 H	1.5 M	MR	
	h. Door Size	1 M	IM	MR	

				
3	Compartmentation.	100	Provided	is it
	Fire check door			
	 Sealing of electrical shafts 			
	Fire Rating of shaft door	~		
	Water Curtain			
	Fire Dampers			
4	Smoke Management System.	HIA		
	Basements	30 a/c per hour		
	Upper floors	12 a/c per hour		
			-	
5	Fire Extinguishers	Rejurned		
	Total numbers		9 No	MA
	• Types		ABC 5 Kg	MR
	IS marking	ISI marked	151	MR
		Later to the second sec		
6	First-Aid Hose Reels.	N/4		
6	First-Aid Hose Reels. • Total numbers on each floor	N/4		
6		N/4 30 m		
6	Total numbers on each floor		- 0	
7	Total numbers on each floorLength of hose reel hose	30 m 5 mm	-0	
2 2	 Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming s	30 m 5 mm		
	 Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming sometimes Type of detectors 	30 m 5 mm		
	 Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming s Type of detectors Location of Main Panel 	30 m 5 mm		
2 2	 Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming some and the second se	30 m 5 mm		
*	 Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming s Type of detectors Location of Main Panel 	30 m 5 mm		
	 Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming some and the second se	30 m 5 mm		
7	 Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming s Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location 	30 m 5 mm ystem. 4/A		
7	 Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming s Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA	30 m 5 mm		
7 8 9	 Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming statements Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System.	30 m 5 mm ystem. 4/A		
*	 Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming s Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA	30 m 5 mm ystem. 4/A		

The state of the

..

· ·				
	Upper Floor			
	Sprinkler above false ceiling			
1 In	nternal Hydrants	1914		
	Size of riser/down-comer			
	Number of hydrants per floor		4	_
	• Hose Box			
2 1	ard Hydrants.	HIA		
	Total number of hydrants			
8	• Hose Box			
13 1	Pumping Arrangements.	HIA		
	Ground Level			
	> Discharge of main Pump		VI	
	> Head of Main pump	:		
	> Number of main pumps			
	> Jockey Pump out put			
,	> Jockey pump head			
	> Standby Pump out put			
	> Standby Pump Head			~.
	> Auto Starting/ Manual			
8 8	stopping			
	> Pump House Access			
N N	Terrace level		. A ₁	
	> Discharge of pump			
	➤ Head of the pump			
	> Power Supply			
	> Auto Starting of pump			
14	Captive Water Storage for fire fighti	ng. MIA		
/	Underground tank capacity			
	> Draw-off connection			

114 1

*.	> Fire service inlet			
a w	> Access to tank			
	Overhead Tank capacity			
15	Exit Signage.	NIA		
16	Provision of Lifts.	419		
	Pressurization of Lift Shaft			
9	Pressurization of Lift lobby		1.1. Av. 4	
	Communication In lift Car			
	 Fireman's Grounding Switch 	-		-
	• Lift Signage			
17	Standby power supply	HIA		
18	Refuge Area.	NIA		
	> Total Area			
	> Location			
19	Fire Control Room	MIA		T
	Detector System Panel			
	Flow Switch Panel			
	PAi System Panel			
20	Batter backup			
	Building Floor Plans			
20	Special Fire Protection Systems for	MIM		
	Protection of special Risks, if any:			

The fire protection systems provided in the building were test checked and found functional at the tof inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire sarequired under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the D-Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Staph

Signature of the Inspecting Officer

Name

Surrest Sugt

Designation A

Signature of the Inspecting Officer

Name

Designation