#### GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/OFS/MS/School/2011/349/ Dated: 14/12/11

### FIRE SAFETY CERTIFICATE

Certified that the M.C.Primary Girls School no.2 at Mandawali, Delhi-92, comprised of ground plus one upper floor owned/occupied by M/s M.C.Primary Girls School have complied with the fire prevention and fire safety requirements in accordance with with the circular issued by the Director of Education dtd.01.03.2011and verified by the officer concerned of Fire Service on 17.11.2011 in the presence of Smt.H.P.Hastir, Principal, of the school and that the building is fit for occupancy , subject to conditions printed overleaf.

Issued on.....at New Delhi by

Chief Fire Officer Delhi Fire Service

To,

Principal M.C.Primary Girls School no.2 Mandawali, Delhi-92

Copy:-

 The Director of Education MCD, Nigam Bhawan, Kashmiri Gate, Delhi.

Principal M.C.Primary Boys School no.2 Mandawali, Delhi-92

#### **CONDITIONS:**

- 1. All the means of escape shall be kept free of all type of obstruction all the type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

# No -2

## INSPECTION REPORT

		* * * * * * * * * * * * * * * * * * *						
1.	Name & address of the building: MC.D	brimary sc	hod-No-2,1	nandausli				
2.	Type of Occupancy : Educational							
3.	. Now Case, Kenevan							
4.	Details of previous NOC : Letter No							
5.	Fire Safety directives letter No: F-16 Estate ceps/2011/3298 to 3318 It /13.11							
6.	- <del>-   T                                   </del>							
7.	the majoriting different in the second of th							
8.	Name and designation of officers							
	from the building side	it- s.P. A	estis Pr	incipal)				
9.	Year of Construction :	2004-0	5					
10	Applicant's letter No.							
S.	Minimum Standards on fire	NBC	Provided at site	Remarks				
N		Requirement		MR/NMR				
1	Access to building	• * *						
	Road width		6 M	MR				
v	Gate width							
	Width of internal road							
2	Number, Width, Type & Arrangement of	of Exits						
*	a. Number of staircases	2 Nos-	2 Nos-	MR				
v	Upper Floors	2 Nos.	2 pris.	MR				
	• Basements							
	b. Width of staircases	1.5 m	1.5-M	MR				
	Upper Floors	1.5 M	1.5 M	MR				
	Basements							
	c. Protection of exits							
	Fire check door			. :				
	• Pressurization							
	e. No. of continuous staircases to terrace	1 No-	1 No.	MR				
	g. Width of Corridor	1.5 M	2-M	MR				
	h. Door Size	1.0 M	1:0 M	MR				

				4, 5,			
	<u> </u>		<b>~</b>				
3	Compartmentation.	, a		1			
	Fire check door						
8	Sealing of electrical shafts						
5	Fire Rating of shaft door						
	Water Curtain						
	Fire Dampers						
4	Smoke Management System.						
3	Basements	30 a/c per hour					
9 a	<ul> <li>Upper floors</li> </ul>	12 a/c per hour					
				- 1			
5	Fire Extinguishers						
	Total numbers	6 Nos-	8 Nos	MR			
	• Types		ABC eco2	MR			
	IS marking	ISI marked					
6	First-Aid Hose Reels.						
	Total numbers on each floor			1			
	• Length of hose reel hose	30 m					
	Nozzle diameter	5 mm					
7	Automatic fire detection and alarming system.						
	Automatic fire detection and alarming s	ystem.		1 .			
	Automatic fire detection and alarming s  • Type of detectors	ystem.		<i>1</i> .			
	• Type of detectors	ystem.		· ·			
	<ul><li>Type of detectors</li><li>Location of Main Panel</li></ul>	ystem.					
	<ul> <li>Type of detectors</li> <li>Location of Main Panel</li> <li>Location of Repeater Panel</li> </ul>						
	<ul><li>Type of detectors</li><li>Location of Main Panel</li></ul>						
	<ul> <li>Type of detectors</li> <li>Location of Main Panel</li> <li>Location of Repeater Panel</li> </ul>						
	<ul> <li>Type of detectors</li> <li>Location of Main Panel</li> <li>Location of Repeater Panel</li> <li>Alternate source of power</li> <li>Hooters' Location</li> </ul>						
8	<ul> <li>Type of detectors</li> <li>Location of Main Panel</li> <li>Location of Repeater Panel</li> <li>Alternate source of power</li> <li>Hooters' Location</li> </ul> MOEFA						
8 9	<ul> <li>Type of detectors</li> <li>Location of Main Panel</li> <li>Location of Repeater Panel</li> <li>Alternate source of power</li> <li>Hooters' Location</li> </ul> MOEFA Public Address System.						
8	<ul> <li>Type of detectors</li> <li>Location of Main Panel</li> <li>Location of Repeater Panel</li> <li>Alternate source of power</li> <li>Hooters' Location</li> </ul> MOEFA						

•	Upper Floor				2
	Sprinkler above false ceiling	20 (S)	Y	1	-
11	Internal Hydrants	·			
	<ul> <li>Size of riser/down-comer</li> <li>Number of hydrants per floor</li> <li>Hose Box</li> </ul>				
12	Yard Hydrants.				
2	<ul> <li>Total number of hydrants</li> <li>Hose Box</li> </ul>				
13	Pumping Arrangements.				
u .	<ul><li>Ground Level</li><li>➤ Discharge of main Pump</li></ul>				
	<ul><li>Head of Main pump</li><li>Number of main pumps</li></ul>				
	<ul> <li>Jockey Pump out put</li> <li>Jockey pump head</li> <li>Standby Pump out put</li> </ul>				
200 000	<ul><li>Standby Pump Head</li><li>Auto Starting/ Manual</li><li>stopping</li></ul>				
	<ul> <li>Pump House Access</li> <li>Terrace level</li> <li>Discharge of pump</li> </ul>				
	> Head of the pump > Power Supply				
14	> Auto Starting of pump  Captive Water Storage for fire fighting			h .	, 5
,	<ul> <li>Underground tank capacity</li> <li>Draw-off connection</li> </ul>				

			S 200			-	1
	➤ Fire service inlet	1		1			.4
	> Access to tank				. 1		•
	Overhead Tank capacity						
15	Exit Signage.						
16	Provision of Lifts.			4. 1. 1.	7		
н	Pressurization of Lift Shaft						
	Pressurization of Lift lobby			4.			
	Communication In lift Car						
	Fireman's Grounding Switch						8 8
	• Lift Signage				-		
17 -	Standby power supply	10. 11.4					
18	Refuge Area.	e.				٠.	
	> Total Area						, s
	> Location						
19	Fire Control Room					-	*
	Detector System Panel						
	Flow Switch Panel						
	PA System Panel			g - 150 (1)			
	Batter backup						. Ar
	Building Floor Plans		. AMT.				
20	Special Fire Protection Systems for						
	Protection of special Risks, if any:						
		4				(	

The fire protection systems provided in the building were test checked and found functional at the of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire sa required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the I Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer

Name

Virenda Singh

Name

Designation

Designation