GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110 001.

No. F6/DF3/MS/Cos/2011/3264

Dated: 30/11/2011

FIRE SAFETY CERTIFICATE

Certified that the SHRADHA COSMETICS building comprised of basement, ground plus three upper floors only and thus less than 15 meters located at H-258, Sector-3, Bawana Industrial Area, Delhi-110 039, have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officers concerned of Fire Service on 26.11.2011 in the presence of Shri Rinku, Manager and that the building/ premises is fit for occupancy Class Industrial Building with effect from ___________________________________ for a period of 3 (three) years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the condition under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ______at New Delhi by

Director
Delhi Fire Service

Shri Rinku, Manager SHRADHA COSMETICS, H-258, Sector-3, Bawana Industrial Area, Delhi-110 039.

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

INSPECTION REPORT

1.	Name & address of the building: 5H4	RADHA COS	METICS, BAW	ANA JND. F
2.		TORY		
3.	Type of Case : New Ca	ise/Renewal		100A
4.	Details of previous NOC : Letter N	10. F.5(3) DFS	2006 90 Dates	1: 28/02/06
5.				
6	Date of inspection 26/11	2011		
7	Name of the Inspecting Officers: SHRI		, ADO	
8	Name and designation of officers			
	from the building side : NA			
9	Year of Construction : 2	605		
10	D. Applicant's letter No. : 623	dated 02.	1.2011	5)
S.	Minimum Standards on fire	A NBCBB	Provided at site	Remarks
No.	prevention and fire safety U/R 33	Requirement		MR/NMR
1	Access to building			
	• Road width	9 Melevs	10 mileis	-m R-
	Gate width	5 Melins	6 melins	←u —
	Width of internal road			
2	Number, Width, Type & Arrangement	of Exits		
	a. Number of staircases	one	One	mR
	• Upper Floors	-u- s		-11-
	• Basements	-ti-		-u -
	b. Width of staircases	125 cm	125 cms	mR
*	Upper Floors	-u -		_ 11-
	Basements		_w_	-w-
	c. Protection of exits			-7
	Fire check door	-		-
	 Pressurization 			
	e. No. of continuous staircases to terrace	One	One	-mR-
	g. Width of Corridor	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		
	h. Door Size	-	-	

3	Compartmentation.		N.A	
	Fire check door			7
	Sealing of electrical shafts			,
	Fire Rating of shaft door			
	Water Curtain		-	-
	Fire Dampers			
4	Smoke Management System.		N A	
	Basements	30 a/c per hour		
	Upper floors	12 a/c per hour		
			-	
5	Fire Extinguishers		Provided	
	Total numbers		Ten (10)	mi
	• Types	TOT	ABC Type	-u-
6	• IS marking	ISI marked	151 Marked	- tv
O	First-Aid Hose Reels.		Provided	
	Total numbers on each floor	20	Three	mR
	 Length of hose reel hose Nozzle diameter 	30 m	30 m	-ur
7		auditati ja sa	5 mm	-un
/	Automatic fire detection and alarming s	ystem.	N·M	
	Type of detectors			7
	Location of Main Panel			-
	Location of Repeater Panel		~	
	Alternate source of power		_	
	Hooters' Location			
				-
8.	MOEFA		NA	-
9	Public Address System.		NA	<u></u>
10	Automatic Sprinkler System.		Provided	
	Basement	Ropowel	Provided	An Rs

	Upper Floor Sprinkles also Silvers	Not Redgel-	Promoted	MR
	Sprinkler above false ceiling			
11	Internal Hydrants		NA	
	Size of riser/down-comer	C		
	Number of hydrants per floorHose Box			
10				,
2	Yard Hydrants.		NA	
	Total number of hydrants			9
2	Hose Box		-	
3	Pumping Arrangements.	<u> </u>		
	Ground Level			
	Discharge of main Pump			
	Head of Main pump			- 2
	Number of main pumps			
	> Jockey Pump out put	***		
	> Jockey pump head			
	Standby Pump out putStandby Pump Head			
	> Auto Starting/ Manual	,		
	stopping			
	Pump House AccessTerrace level	Refund	Provided	MR
	> Discharge of pump	goo lom	900 lpm	-u _
	➤ Head of the pump	40 mbrs	40 mms	_n_
	> Power Supply			
	> Auto Starting of pump	and the second s		
	Captive Water Storage for fire fighting.			
	Underground tank capacity		· ·	
	> Draw-off connection			

	> Fire service inlet	3		~		
	> Access to tank			L L		
	Overhead Tank capacity	10,000	10,000	MR		
15	Exit Signage.	Refund	Provided	mR		
16	Provision of Lifts.					
	Pressurization of Lift Shaft					
	Pressurization of Lift lobby					
	Communication In lift Car	7				
	• Fireman's Grounding Switch	•				
	Lift Signage			-		
17	Standby power supply		NA			
18						
	> Total Area	. 7	•			
	> Location	· · · · ·				
19	Fire Control Room					
	Detector System Panel					
	Flow Switch Panel	7		-		
	PA System Panel					
	Batter backup					
	Building Floor Plans	₹ 16.5004				
20	Special Fire Protection Systems for Protection of special Risks, if any:	• -				

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

(E)

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name R.K. DAMYA

Name

Designation $\mathcal{A} \mathcal{D} \mathcal{O}$

Designation