GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI

HEADQUARTERS; DELHI FIRE SERVICE; CONNAUGHT PLACE; NEW DELHI

No F6/DF3/M3/2011/5285

Dated 01 12/2011

FIRE SAFETY CERTIFICATE

Certified that the Delhi Institute of Rural Development (D.I.R.D)comprised of ground plus three upper floor only located at Nangli Poona Delhi-36 occupied by D.I.R.D have complied with the fire prevention and fire safety requirements under Rule 33 of the Delhi Fire rule 2010 and verified by the officer concerned of Fire Service on 23.11.11 in the presence of Sh.Anoop Singh and the building/premises is fit for occupancy Sub Group B-2 of Group B Educational Buildings with effect from of 12/11 for a period of Three Years, subject to conditions mentioned below.

Issue on _____at New Delhi by

Chief Fire Officer Delhi Fire Service

ofc.

Delhi Institute of Rural Development,

Near Kapoor Diesel Works,

GT Karnal Road,

Nangli Poona,

Delhi-36

Conditions for validity of the certificate-

- a) All the fire safety means of escape facilities shall be maintained in good working condition at all time. Any lapse rendering fire safety or means of escape facilities non functional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record maintained.

INSPECTION REPORT 1. Name & address of the building: pethe Institute of Rusal Development Education Mas. (a + three upper from on 3. Type of Case : New Case/ Renewal 4. Details of previous NOC : Letter No. _______ Dated: 5. Fire Safety directives letter No 6. Date of inspection 23.11.11 7. Name of the Inspecting Officers: Vipin Kental. 8. Name and designation of officers from the building side : Sh. Anoop Songh 9. Year of Construction 2003-04 10. Applicant's letter No. 20:10:11 S. Minimum Standards on fire **NBC** Provided at site Remarks No. prevention and fire safety U/R 33 Requirement MR/NMR 1 Access to building Road width 6 mts. 6 mh MIR Gate width 5 mti. may be considered 47 MT Width of internal road 6 mt m/R 2 Number, Width, Type & Arrangement of Exits a. Number of staircases Upper Floors TWO. TWO MIR Basements b. Width of staircases Upper Floors (1) 152 cm-Basements c. Protection of exits Fire check door Pressurization e. No. of continuous staircases to terrace one me MIR g. Width of Corridor 1.50 mt 1.50 mt MIR h. Door Size

1.00 mts

1.00 mh

3	Compartmentation.				
3	Fire check door	N.R			
	3 300 3 30 30 40 4 4				
	Southing of electrical sharts				
	Fire Rating of shaft door Water Curtain				
	Water Curtain Fire Demonstration				
	Fire Dampers	-			
4	Smoke Management System.				
	• Basements	30 a/c per hour			
	Upper floors	12 a/c per hour			
5	Fire Extinguishers	3			
	Total numbers		6 NO. +3 / MIR		
	• Types		ABC HABLA		
	IS marking	ISI marked	CO2 type		
6	First-Aid Hose Reels.				
3	Total numbers on each floor	2	TWO MIR		
	 Length of hose reel hose 	30 m	30 mb		
	Nozzle diameter	5 mm			
7	Automatic fire detection and alarming system.				
	Type of detectors				
59	i,				
	Location of Main Panel				
	Location of Repeater Panel		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
	Alternate source of power				
•	Hooters' Location				
8	MOEFA	NIR			
9	Public Address System.	NIR			
10	Automatic Sprinkler System.	N.A			
	Basement	_			

t site

omt

	Upper Floor				
	Sprinkler above false ceiling	-	-		
11	Internal Hydrants	N/R			
	Size of riser/down-comer	4"	y" p		
	Number of hydrants per floor				
	Hose Box	_		-	
12	Yard Hydrants.	N. D	- z		
	Total number of hydrants				
	Hose Box				
13	Pumping Arrangements.				
e to	Ground Level			_	
	> Discharge of main Pump	_		#*************************************	
	> Head of Main pump	:			
	> Number of main pumps				
	> Jockey Pump out put				
	> Jockey pump head				
	> Standby Pump out put				
	Standby Pump Head				
	> Auto Starting/ Manual	-	2		
	stopping	, –	-	. :	
	▶ Pump House Access		-	-	
	Terrace level	2			
	Discharge of pump	450LPM	450 CPM	mlR	
	➤ Head of the pump	30mti.	4		
	> Power Supply	on main 4	ρ	mr	
	> Auto Starting of pump	N.R	4		
14	Captive Water Storage for fire fighting.	N.R		*	
	Underground tank capacity	30			
	> Draw-off connection				



Signature of the Inspecting Officer

Name

Designation

Signature of the Inspecting Officer

Name VIPIN KENTAL

Designation DO NW