GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110 001.

No. F6/DFS/MS/2011/3617

Dated: 19/12/11

FIRE SAFETY CERTIFICATE

Issued on). 9. /1.2. /. 11........ at New Delhi by

Director Delhi Fire Service

Of All

Shri Rajat Arora, Proprietor Fine Food Product, A-3, Phase-III, Badli Industrial Area, Delhi-110 042.

Conditions for the validity of fire safety certificate:-

- a) All the fire safety means of escape facilities shall be maintained in good conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be responsibility of the management.
- b) Building sanctioning authority may verify any deviation with regard to the construction/ occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c) The staff shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

INSPECTION REPORT 1. Name & address of the building: FINE FOOD PRODUCT, BADLI INDUSTRIPL AREA 2. Type of Occupancy INDUSTRIAL BUILDING 3. Type of Case : New Case/ Renewal 4. Details of previous NOC NA: Letter No. Dated: 5. Fire Safety directives letter No : As per NBC Part IV CBBL 6. Date of inspection 28.11.2011 7. Name of the Inspecting Officers: She R. K. Daluys, ADD 8. Name and designation of officers from the building side · N.A. 9. Year of Construction 2004 10. Applicant's letter No. : NIL deted Mu S. Minimum Standards on fire NBC Provided at site Remarks No. prevention and fire safety U/R 33 Requirement **MR/NMR** Access to building 9 Melera MR Road width 10 Melera Accessible Gate widt Accessible -us Width of aternal road Number, Width, Type & Arrangement of Exits 2 a. Number of staircases MR The TWO Upper Floors -u--uc -1 - Basements Au--u-35 au 125 cm b. Width of staircases MR eah Upper Floors -u--4 -Basements - 11 --Mc. Protection of exits Fire check door Pressurization e. No. of continuous staircases to terrace TNO ma Tous g. Width of Corridor h. Door Size 100 cms MR

125 cms

0					
3	Compartmentation.		NA		
	Fire check door				
	Sealing of electrical shafts				
	Fire Rating of shaft door	-		-	
	Water Curtain		45		
	Fire Dampers			-	
4	Smoke Management System.		NA .		
	Basements	30 a/c per hour			
	Upper floors	12 a/c per hour		7	
5	Fire Extinguishers Provided				
	Total numbers		12 (MR	
	• Types		ABC Type	-u-	
	• IS marking	ISI marked	ISI Marked	- u -	
6	First-Aid Hose Reels.				
	Total numbers on each floor		Two	MR	
	Length of hose reel hose	30 m	30 melus	-u-	
	Nozzle diameter	5 mm	5 mm	-u-	
7	Automatic fire detection and alarming system.				
	Type of detectors				
	Location of Main Panel				
	Location of Repeater Panel			_	
	Alternate source of power				
	Hooters' Location				
	THOOLES LOCATION				
8.	MOEFA	Not Romine	1	-	
9	Public Address System.	Not Required.			
10	Automatic Sprinkler System. Provided Repuired Provided MR				
	Basement	Repured	I v toxivize helical favoroni		

100 mg				(3)
10		T		
	Upper FloorSprinkler above false ceiling		•	-
11	Internal Hydrants			
	Size of riser/down-comer	Required	Provided	ma
	Number of hydrants per floorHose Box			•
A say	TIOSE DOX	Repund	Provided	mR
12	Yard Hydrants.			
	Total number of hydrants		N.A	
	Hose Box	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
13	Pumping Arrangements.			
	Ground Level	-	2	~
	Discharge of main Pump	-		
	> Head of Main pump			
+ 17	> Number of main pumps			
	Jockey Pump out put	.4	7	
	> Jockey pump head	7	7	
	> Standby Pump out put	-	-	•
	Standby Pump Head		-	7
. 15	Auto Starting/ Manual			
	stopping			
194 1940 and	Pump House Access		1	
	• Terrace level	A - 1		
	Discharge of pump	900 Lpm	90x Lpm	mR
	► Head of the pump	40 melis	40 melus	- u-
	Power Supply	Reguned	Provided	<u> </u>
	➤ Auto Starting of pump	Repuried	Provided	-11-
4	Captive Water Storage for fire fighting.			
	Underground tank capacity	_		
	> Draw-off connection		_	

	N 77:				
	Fire service inlet	2		2	
	Access to tank				
	Overhead Tank capacity	10,000 Lins	12,000 4/2	mp	
15	Exit Signage.	Repaired	Provided	MR	
16	Provision of Lifts.		NA		
	Pressurization of Lift Shaft	5 5 m (9 m) 4 m) 6 m) 7 m) 6 m) 7 m)			
	Pressurization of Lift lobby				
	Communication In lift Car				
	• Fireman's Grounding Switch			1	
	• Lift Signage				
17			0		
17	Standby power supply	Repurid	Provided 63 KVA	mR	
18	Refuge Area.				
	> Total Area	-			
	> Location				
19	Fire Control Room				
	Detector System Panel	3		7	
	Flow Switch Panel	7			
	PA System Panel			-	
	Batter backup		. Za s antan		
	Building Floor Plans				
20	Special Fire Protection Systems for Protection of special Risks, if any:				

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Laspecting Officer

Signature of the Inspecting Officer

R. K. Dahiys

Name

Designation

Designation