GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.

F6/D73/ms/schrel2011/3715

Dated: 27/12/2011

FIRE SAFETY CERTIFICATE

Issued on 27/12/2011 at New Delhi by

CHIEF FIRE OFFICER FOR DIRECTOR DELHI FIRE SERVICE

To,

Crescent School, Jamaloo Ka Bagh, Road No.66, Maujpur, New Delhi

Copy to:-

The Joint Director of Education (Land & Estate) Directorate of Education, Lucknow Road, Delhi -54.

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1	Name & address of the building: _ C R	ESCENT	SCHOOL	
2				
3	Type of Case : New Ca	ise/Renewal	eg .	
4	Details of previous NOC : Letter N	Io	Date	d:
5				
6	T			
7	Name of the Inspecting Officers: ADD			
8	Name and designation of officers			
	from the building side : Mrs	Naushabe	kfd wei	
9	Year of Construction : 19°	15		
. 1	O. Applicant's letter No. : Ni	l dated 5	1. 12. 2011	
S.	Minimum Standards on fire	i,	Provided at site	Remarks
No.	prevention and fire safety U/R 33	Requirement		MR/NMR
1	Access to building			r
	Road width	6 m	20 M	MR
	Gate width	-	3.80 M	
	Width of internal road	-		
2	Number, Width, Type & Arrangement of	of Exits		
	a. Number of staircases	3	3	MR
	Upper Floors	-3	3	MR
	Basements	3	3	MR
	b. Width of staircases	1. 50, 1.50	1.80 , 1.50	mr.
	Upper Floors	1.50	1.80 1.50	MR
•	Basements	1.50	1.80 1.50	MR
	c. Protection of exits			_
	Fire check door	-		
	Pressurization			- 1
	e. No. of continuous staircases to terrace	2	2	MR
	g. Width of Corridor	1.50	1.55 - 1.657	
	h. Door Size	111	1 4	MR

			্ স্	•
3	Compartmentation.		Provided	
(4)	Fire check door			
	Sealing of electrical shafts			
	Fire Rating of shaft door			
	Water Curtain			
	Fire Dampers			
4	Smoke Management System.			*
	• Basements	30 a/c per hour	Provided	ng
	Upper floors	12 a/c per hour	in Bayerum. exhaust	
5	Fire Extinguishers	Required-		
	Total numbers	16 NO	16 No	MR
	• Types		Co2+ ABC	MR
	IS marking	ISI marked	151	MR
6	First-Aid Hose Reels. Required			
150	Total numbers on each floor		One at each floor. Basement	MR
	• Length of hose reel hose	30 m	304	MIR
	Nozzle diameter	5 mm	5 mm	MR
7	Automatic fire detection and alarming system.			
	Type of detectors		_	
	Location of Main Panel			
	Location of Repeater Panel			
٠.	Alternate source of power			~
	Hooters' Location			
8	MOEFA	Provided	Provided	MR.
9	Public Address System.		74	
10	Automatic Sprinkler System. Resurce			
-	• Basement	Basemond.	Provided	HR

. •

	Upper Floor			gasana .
	Sprinkler above false ceiling			
11	Internal Hydrants	MIA		
	Size of riser/down-comer			
	Number of hydrants per floor			
	Hose Box			-
12	Yard Hydrants.	HIA		
	Total number of hydrants			
	Hose Box			
13	Pumping Arrangements.	Rejulved	T	
	Ground Level	•		gagarasi .
	> Discharge of main Pump			
	> Head of Main pump	:		-
	> Number of main pumps			
	> Jockey Pump out put			
	> Jockey pump head			
	> Standby Pump out put			
	> Standby Pump Head			
	> Auto Starting/ Manual			
	stopping			
	> Pump House Access			
	Terrace level	2 No 4504	ph provided	MR
	> Discharge of pump	4504	y provided	MR
	> Head of the pump	-		_
	> Power Supply			-
	> Auto Starting of pump			
1	4 Captive Water Storage for fire fighting	ig. Required		
1	Underground tank capacity			
	> Draw-off connection			
			The state of the s	

	> Fire service inlet			
	> Access to tank			
	Overhead Tank capacity	15000 44	15000 41	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.	HIA		1
	 Pressurization of Lift Shaft 		-	
	 Pressurization of Lift lobby 	-	-	
	Communication In lift Car			<u> </u>
	 Fireman's Grounding Switch 			
	• Lift Signage			
	zar bigingo	-		-
17	Standby power supply	NIA		~
18	Refuge Area.	NIA		
	> Total Area			~
	> Location		-	
19	Fire Control Room	HIA		<u> </u>
	Detector System Panel			
	Flow Switch Panel			-
	PA System Panel			
	Batter backup	-		
	Building Floor Plans			
20	Special Fire Protection Systems for	MIA		-
	Protection of special Risks, if any:	~~~		_

The fire protection systems provided in the building were test checked and found functional at the tof inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire sarequired under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the D-Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer Signature of the Inspecting Officer Suresh Singh Name Name ADO Designation Designation Submitted for approval please.